

UAPI Functions - DAV::get_calendar_contacts_config

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

- Backup
- Backup:: fullbackup
- p_to_ftp
- Backup:: fullbackup
- p_to_homedir
- Backup:: fullbackup
- p_to_scp_with_key

- Backup:: fullbackup
- p_to_scp_with_password

- Backup:: list_backups

Bandwidth

- Bandwidth:: get_enabled_protocols
- Bandwidth:: get_retention_periods
- Bandwidth:: query

Batch

- Batch:: strict

Brand

- Brand:: read

Branding

- Branding:: file
- Branding:: get_applications
- Branding:: get_application_information
- Branding:: get_available_applications
- Branding:: get_info

Description

This function returns the connection information to set up the CalDAV and CardDAV clients.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/DAV/get_calendar_contacts_config?user=example
```

```
https://hostname.example.com:2083/cpsess#####/execute/DAV/get_calendar_contacts_config?user=example2@example.com
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

Function information

About this module

The DAV module provides cPanel *Calendar and Contacts* settings, and provides tools for file lock management to the DAV server.

About UAPI

information_for_applications

Branding:: image

Branding:: include

Branding:: spritelist

CacheBuster

CacheBuster:: read

CacheBuster:: update

Chkserverd

Chkserverd:: get_external_ports

Chkserverd:: get_external_ports_ssl

Chrome

Chrome:: get_domain

Contactus

Contactus:: is_enabled

cPAddons

cPAddons:: get_available_addons

cPAddons:: get_instance_settings

cPAddons:: list_addon_instances

cPGreyList

cPGreyList:: disable_all_domains

cPGreyList:: disable_domains

cPGreyList:: enable_all_domains

cPGreyList:: enable_domains

cPGreyList:: has_greylisting_enabled

cPGreyList:: list_domains

DAV

DAV:: disable_shared_global_addressbook

DAV:: enable_shared_global_addressbook

DAV:: get_calendar_contacts_config

DAV:: has_shared_global_addressbook

LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.
```

```
// List the account's  
CalDAV and CardDAV  
connection  
information.  
$get_calendar_contact  
s_config =  
$cpanel->uapi(  
    'DAV',  
    'get_calendar_contact  
s_config'  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# List the account's  
CalDAV and CardDAV  
connection  
information.  
my  
$get_calendar_contact  
s_config =  
$cpliveapi->uapi(  
    'DAV',  
    'get_calendar_contact  
s_config',  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

UAPI accesses and modifies data for cPanel accounts.

Notes:

- The `int` `Urmus` 20 or 20).
- The `int` `Urmus` 20 or 20).

Find a function

- UAPI Functions - DAV: `is_horde_enabled` — This function checks whether Horde is enabled.

DAV:: is_dav_service_enabled

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

▼ cPanel Template Toolkit

```
<!-- List the account's CalDAV and CardDAV connection information. -->[% data = execute('DAV', 'get_calendar_contacts_config' ); %]  
[% FOREACH q = data %]  
    <p>  
        [% q %]  
    </p>  
[% END %]
```

Note:

For more information, read our [Guide to Template Toolkit](#) documentation.

▼ Command Line

```
uapi --user=username  
DAV  
get_calendar_contacts_config user=example
```

Notes:

- You **must** [URI-encode](#) values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local  
/cpanel/bin  
uapi
```

▼ Output (JSON)

- UAPI Functions - DAV:: is_dav_service_enabled — This function checks whether the DAV service is enabled.

- UAPI Functions - DAV:: disable_share_global_addressbook — This function disables the shared global address book for the current cPanel account's web mail accounts.

Email: add_spam_filter
Email: browse_mailbox
Email: change_mx
Email: check_fast_mail
Email: check_pipe_forwarder
Email: delete_auto_responder
Email: delete_dominant_forwarder
Email: delete_filter
Email: delete_forwarder
Email: delete_held_messages
Email: delete_list
Email: delete_mx
Email: delete_pop
Email: disable_filter
Email: disable_mailbox_autocreate
Email: disable_spam_assassin
Email: disable_spam_autodelete
Email: disable_spam_box
Email: dispatch_client_settings
Email: edit_pop_quota
Email: enable_filter
Email: enable_mailbox_autocreate
Email: enable_spam_assassin
Email: enable_spam_box
Email: fetch_charmaps
Email: fts_rescan_mailbox
Email: generate_mailman_otp
Email: get_auto_r

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {},
  "data": {
    "ssl": {

"contacts": [
  {
    "url":
    "https://example.com:2080/addressbooks/example/contacts:E-KKA5uQZyQZyQJbTBKcGP3OQ6",
    "name": "Address book of example",
    "path":
    "/addressbooks/example/contacts:E-KKA5uQZyQJbTBKcGP3OQ6",
    "description": null
  },
  {
    "url":
    "https://example.com:2080/addressbooks/example/contacts:pn7DhZKYPeqebgmOdUCw7g7",
    "name": "Custom 1",
    "path":
    "/addressbooks/example/contacts:pn7DhZKYPeqebgmOdUCw7g7",
    "description":
    "Custom address book 1"
  },
  {
    "url":
    "https://example.com:2080/addressbooks/example/contacts:qxmwxgVfJ7jqrDLwrvdmYA1",
```

- UAPI Functions - DAV:enable_shared_global_address_book - This function enables the shared global address book for the current cPanel account's web mail accounts.

esponder
Email: get_charts
Email: get_client_settings
Email: get_default_email_quota
Email: get_default_email_quota_mib
Email: get_disk_usage
Email: get_filter
Email: get_held_message_count
Email: get_mailbox_autocreate
Email: get_mailman_delegates
Email: get_main_account_disk_usage
Email: get_main_account_disk_usage_bytes
Email: get_max_email_quota
Email: get_max_email_quota_mib
Email: get_pop_quota
Email: get_spam_settings
Email: get_webmail_settings
Email: has_delegated_mailman_lists
Email: has_plaintext_authentication
Email: hold_outgoing
Email: is_integer
Email: list_auto_responders
Email: list_default_address
Email: list_domain_forwarders
Email: list_filters
Email: list_filters_backups
Email: list_forward

```
"name": "Custom 2",  
"path":  
  "/addressbooks/example/contacts:qxmwxgVfJ7jqrDLwrvdmYA1",  
"description":  
  "Custom address book 2."  
    },  
  ],  
"calendars": [  
  {  
    "url":  
      "https://example.com:2080/calendars/example/calendar:ZcG9JBH68WXxfMVUgvSrUw1",  
    "name": "Calendar of example",  
    "path":  
      "/calendars/example/calendar:ZcG9JBH68WXxfMVUgvSrUw1",  
    "description": null  
      },  
  {  
    "url":  
      "https://example.com:2080/calendars/example/calendar:hblGz0wgSmJxIsOkIcw42g1",  
    "name": "Custom 1",  
    "path":  
      "/calendars/example/calendar:hblGz0wgSmJxIsOkIcw42g1",  
    "description":  
      "Custom calendar 1"  
      },  
  }
```

ers
Email: list_forward_ers_backups
Email: list_lists
Email: list_mail_domains
Email: list_mx
Email: list_pops
Email: list_pops_with_disk
Email: list_system_filter_info
Email: passwd_list
Email: passwd_pop
Email: release_outgoing
Email: remove_mailman_delegates
Email: reorder_filters
Email: set_always_accept
Email: set_default_address
Email: set_list_privacy_options
Email: stats_db_status
Email: store_filter
Email: suspend_incoming
Email: suspend_login
Email: suspend_outgoing
Email: trace_filter
Email: unsuspend_incoming
Email: unsuspend_login
Email: unsuspend_outgoing
Email: verify_password
▼ EmailAuth
EmailAuth: disable_dkim
EmailAuth: enable_dkim

```
"url":  
"https://example.com:2080/calendars/example/calendar:vxY4ACROc-1tx4TgrTb4Q3",  
  
"name": "Custom 2",  
  
"path":  
"/calendars/example/calendar:vxY4ACROc-1tx4TgrTb4Q3",  
  
"description":  
"Custom calendar 2."  
    }  
    ],  
  
"is_self_signed": 1,  
  
"full_server":  
"https://server.example.com:2080/rpc/principals/example",  
    "server":  
"https://server.example.com:2080",  
    "port":  
"2080"  
    },  
    "user":  
"example",  
    "no_ssl": {  
  
"contacts": [  
    {  
  
"url":  
"http://example.com:2079/addressbooks/example/contacts:E-KKA5uQZyQJbTBKcGP3OQ6",  
  
"name": "Address book of example",  
  
"path":  
"/addressbooks/example/contacts:E-KKA5uQZyQJbTBKcGP3OQ6",  
  
"description": null  
    }  
    ],
```

EmailAuth:: ensure_dkim_keys_exist

EmailAuth:: fetch_dkim_private_keys

EmailAuth:: install_dkim_private_keys

EmailAuth:: install_spf_records

EmailAuth:: validate_current_dkims

EmailAuth:: validate_current_ptrs

EmailAuth:: validate_current_spfs

ExternalAuthentication

ExternalAuthentication:: add_authn_link

ExternalAuthentication:: configured_modules

ExternalAuthentication:: get_authn_links

ExternalAuthentication:: has_external_auth_modules_configured

ExternalAuthentication:: remove_authn_link

Features

Features:: get_feature_metadata

Features:: has_feature

Features:: list_features

Fileman

Fileman:: autocompletedir

Fileman:: empty_trash

Fileman:: get_file_content

Fileman:: get_file_information

Fileman:: list_files

Fileman:: save_file_content

Fileman:: transcode

```
{
  "url":
  "http://example.com:2079/addressbooks/example/contacts:pn7DhZKYPeqebgmOdUCw7g7",
  "name": "Custom 1",
  "path":
  "/addressbooks/example/contacts:pn7DhZKYPeqebgmOdUCw7g7",
  "description":
  "Custom address book 1"
},
{
  "url":
  "http://example.com:2079/addressbooks/example/contacts:qxmwxgVfJ7jqrdLwrvdmYA1",
  "name": "Custom 2",
  "path":
  "/addressbooks/example/contacts:qxmwxgVfJ7jqrdLwrvdmYA1",
  "description":
  "Custom address book 2."
}
],
"calendars": [
  {
    "url":
    "http://example.com:2079/calendars/example/calendar:ZcG9JBH68WxfMVUgvSrUw1",
    "name": "Calendar of example",
    "path":
```

```
Fileman:: upload_files
  Ftp
    Ftp:: add_ftp
    Ftp:: allows_anonymous_ftp
    Ftp:: allows_anonymous_ftp_incoming
    Ftp:: delete_ftp
    Ftp:: ftp_exists
    Ftp:: get_ftp_daemon_info
    Ftp:: get_port
    Ftp:: get_quota
    Ftp:: get_welcome_message
    Ftp:: kill_session
    Ftp:: list_ftp
    Ftp:: list_ftp_with_disk
    Ftp:: list_sessions
    Ftp:: passwd
    Ftp:: server_name
    Ftp:: set_anonymous_ftp
    Ftp:: set_anonymous_ftp_incoming
    Ftp:: set_homedir
    Ftp:: set_quota
    Ftp:: set_welcome_message
  Integration
    Integration:: fetch_url
  KnownHosts
    KnownHosts:: create
    KnownHosts:: delete
    KnownHosts:: update
    KnownHosts:: verify
  LangPHP
    LangPHP:: php_get_domain_handler
    LangPHP:: php_get_impacted_domains
```

```
"/calendars/example/calendar:ZcG9JBH68WXxfMVUgvSrUw1",
  "description": null
},
{
  "url":
  "http://example.com:2079/calendars/example/calendar:hblGz0wgSmJxIsOkIcw42g1",
  "name": "Custom 1",
  "path":
  "/calendars/example/calendar:hblGz0wgSmJxIsOkIcw42g1",
  "description":
  "Custom calendar 1"
},
{
  "url":
  "http://example.com:2079/calendars/example/calendar:vxdY4ACROc-1tx4TgrTb4Q3",
  "name": "Custom 2",
  "path":
  "/calendars/example/calendar:vxdY4ACROc-1tx4TgrTb4Q3",
  "description":
  "Custom calendar 2."
},
],
  "full_server":
  "http://example.com:2079/rpc/principals/example",
  "server":
  "http://example.com:2079",
  "port":
  "2079"
```


LangPHP:: php_get_installed_versions

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_mailbox_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url



Parameters

Parameter	Type	Description	Possible values	Example
user	string	The cPanel account. If you do not include this parameter, the function defaults to the current authenticated user.	<ul style="list-style-type: none">• A valid cPanel account user.• A valid email account user.	example

Returns

Return	Type	Description	Possible values	Example
user	string	The specified cPanel user or email account user to whom the returned connection information pertains. If you do not specify a <code>user</code> value, this function returns the authenticated cPanel user.	<ul style="list-style-type: none">• A cPanel account user.• An email account user.	example2@example.com
ssl	hash	A hash that contains the SSL connections.	This hash includes the <code>is_self_signed</code> , <code>port</code> , <code>server</code> , and <code>full_server</code> returns and the <code>contacts</code> and <code>calendars</code> arrays.	

Market:: get_pending_ssl_certificates

Market:: get_provider_specific_dcv_constraints

Market:: get_providers_list

Market:: get_ssl_certificate_if_available

Market:: process_ssl_pending_queue

Market:: request_ssl_certificates

Market:: set_status_of_pending_queue_items

Market:: set_url_after_checkout

Market:: validate_login_token

▼ Mime

Mime:: add_handler

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redirect

Mime:: delete_handler

Mime:: delete_hotlink

Mime:: delete_mime

Mime:: delete_redirect

Mime:: list_handlers

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirects

Mime:: redirect_info

▼ ModSecurity

ModSecurity:: disable_all_domains

ModSecurity:: disable_domains

ModSecurity:: enable_all_domains

is_self_signed	<i>Boolean</i>	Whether the server uses a self-signed certificate. The function returns this value in the <code>ssl</code> hash.	<ul style="list-style-type: none"> 1 — Self-signed. 0 — Not self-signed. 	1
port	<i>integer</i>	The port number that the system uses for SSL connection. The function returns this value in the <code>ssl</code> hash.	A positive integer.	2080
server	<i>string</i>	The short server connection string. The function returns this value in the <code>ssl</code> hash.	A domain name and port that uses the HTTP protocol.	<code>https://server.example.com:2080</code>
full_server	<i>string</i>	The absolute URL path to the user's CalDAV and CardDAV connection. The function returns this value in the <code>ssl</code> hash.	A domain name and port with the absolute path that uses the HTTP protocol.	<p>▼ Click to view...</p> <p><code>https://server.example.com:2080/rpc/principal/example</code></p>

Note
: This value is useful for clients that support Auto discovery.

Note
: This information is useful for clients that do not support Auto discovery.

ModSecurity:: enable_domains

ModSecurity:: has_modsecurity_installed

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql:: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

contacts	array	The list of address books for the user. The function returns this array in the ssl hash.	This array contains the name, description, path, and url returns.	
name	string	The name of the address book. The function returns this value in the contacts array.	A valid string.	Custom 1
description	string	The description of the address book. The function returns this value in the contacts array.	A valid string.	Custom address book 1.
path	string	The relative URL to the address book. The function returns this value in the contacts array.	A valid string.	▼ Click to view... /address books/example/contacts:EKKA5uQZyQJbTBKcGP3OQ6
url	string	The absolute URL to the address book. This function returns this value in the contacts array.	A valid URL.	▼ Click to view... https://example.com:2080/address books/example/contacts:EKKA5uQZyQJbTBKcGP3OQ6
calendars	array	The list of address books for the user. The function returns this array in the ssl hash.	This array contains the name, description, path, and url returns.	
name	string	The name of the calendar. The function returns this value in the calendars array.	A valid string.	Custom 1

- Parser
 - Parser:: firstfile_relative_uri
- PassengerApps
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: ensure_deps
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- PasswdStrength
 - PasswdStrength:: get_required_strength
- Personalization
 - Personalization::set
 - Personalization::get
- Postgresql
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- Pushbullet
 - Pushbullet:: send_test_message

	description	<i>string</i>	The description of the calendar. The function returns this value in the calendars array.	A valid string.	Custom address book 1.
	path	<i>string</i>	The relative URL path to the calendar. The function returns this value in the calendars array.	A valid string.	<ul style="list-style-type: none"> Click to view... /calendars/example/calendar:ZcG9JBH68WXxfMVUgvSrUw1
	url	<i>string</i>	The absolute URL to the calendar. The function returns this value in the calendars array.	A valid URL.	<ul style="list-style-type: none"> Click to view... https://example.com:2080/calendars/example/calendar:ZcG9JBH68WXxfMVUgvSrUw1
no_ssl		<i>hash</i>	The configuration for non-SSL connections. The function returns this hash in the ssl hash.	This hash includes the port, server, and full_server returns and the contacts and calendars arrays.	
	port	<i>integer</i>	The port number that the system uses for non-SSL connections. The function returns this value in the no_ssl hash.	A positive integer.	2079
	server	<i>string</i>	The short server connection string. The function returns this value in the no_ssl hash.	A domain name and port that uses the HTTP protocol.	http://example.com:2079

- Quota:: [get_quota_info](#)
- Resellers:: [list_accounts](#)
- ResourceUsage:: [get_usages](#)
- Restore:: [directory_listing](#)
 - Restore:: [get_users](#)
 - Restore:: [query_file_info](#)
 - Restore:: [restore_file](#)
- Session:: [create_temp_user](#)
- SiteTemplates:: [list_site_templates](#)
 - SiteTemplates:: [list_user_settings](#)
 - SiteTemplates:: [publish](#)
- SpamAssassin:: [clear_spam_box](#)
 - SpamAssassin:: [get_symbolic_test_names](#)
 - SpamAssassin:: [get_user_preferences](#)
 - SpamAssassin:: [update_user_preference](#)
- SSH:: [get_port](#)
- SSL:: [add_autossl_excluded_domains](#)
 - SSL:: [can_ssl_redirect](#)
 - SSL:: [check_shared_cert](#)
 - SSL:: [delete_cert](#)
 - SSL:: [delete_csr](#)
 - SSL:: [delete_key](#)

full_server	string	<p>The absolute URL path to the user's CalDAV and CardDAV connection information.</p> <p>The function returns this value in the no_ssl hash.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note: This information is useful for clients that do not support Auto discovery.</p> </div>	A domain name and port with the absolute path that uses the HTTP protocol.	<ul style="list-style-type: none"> <ul style="list-style-type: none"> Click to view... http://example.com:2079/rpc/principal/example
contacts	array	<p>The list of address books for the user.</p> <p>The function returns this array in the no_ssl hash.</p>	This array contains the name, description, path, and url returns.	
name	string	<p>The name of the address book.</p> <p>The function returns this value in the contacts array.</p>	A valid string.	Custom 1
description	string	<p>The description of the address book.</p> <p>The function returns this value in the contacts array.</p>	A valid string.	Custom address book 1.
path	string	<p>The relative URL to the address book.</p> <p>The function returns this value in the contacts array.</p>	A valid string.	<ul style="list-style-type: none"> <ul style="list-style-type: none"> Click to view... /addressbooks/example/contacts:EKKA5uQZyQJbTBKcGP30Q6

SSL:: delete_ssl
 SSL:: disable_mail_sni
 SSL:: enable_mail_sni
 SSL:: fetch_best_for_domain
 SSL:: fetch_certificate_for_fqdns
 SSL:: fetch_key_and_certificate_for_certificate
 SSL:: find_certificates_for_key
 SSL:: find_csrs_for_key
 SSL:: generate_certificate
 SSL:: generate_certificate
 SSL:: generate_key
 SSL:: get_autossl_excluded_domains
 SSL:: get_autossl_pending_queue
 SSL:: get_autossl_problems
 SSL:: get_certificate
 SSL:: get_cn_name
 SSL:: install_ssl
 SSL:: installed_hosts
 SSL:: installed_hosts
 SSL:: is_autossl_check_in_progress
 SSL:: is_mail_sni_supported
 SSL:: is_sni_supported
 SSL:: list_certs
 SSL:: list_csrs
 SSL:: list_keys
 SSL:: list_ssl_items
 SSL:: mail_sni_status

url	string	<p>The absolute URL to the address book.</p> <p>The function returns this value in the contacts array.</p>	A valid URL.	<p>Click to view...</p> <p>https://example.com:2080/addressbooks/example/contacts:EKKA5uQZyQJbTBKcGP30Q6</p>
calendars	array	<p>The list of address books for the user.</p> <p>The function returns this array in the no_ssl hash.</p>	This array contains the name, description, path, and url returns.	
name	string	<p>The name of the calendar.</p> <p>The function returns this value in the calendars array.</p>	A valid string.	Custom 1
description	string	<p>The description of the calendar.</p> <p>The function returns this value in the calendars array.</p>	A valid string.	Custom address book 1.
path	string	<p>The relative URL path to the calendar.</p> <p>The function returns this value in the calendars array.</p>	A valid string.	<p>Click to view...</p> <p>/calendars/example/calendar:ZcG9JBH68WXxfMVUgvSrUw1</p>
url	string	<p>The absolute URL to the calendar.</p> <p>The function returns this value in the calendars array.</p>	A valid URL.	<p>Click to view...</p> <p>http://example.com:2079/calendars/example/calendar:ZcG9JBH68WXxfMVUgvSrUw1</p>

tus

SSL:: rebuild_mail
_snl_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDepl

oyment

VersionControlDep
loyment:: **create**

VersionControlDep
loyment:: **delete**

VersionControlDep
loyment:: **retrieve**

▼ WebDisk

WebDisk:: **delete_**
user

WebDisk:: **set_ho**
medir

WebDisk:: **set_pas**
sword

WebDisk:: **set_per**
missions

▼ WebmailApps

WebmailApps:: **list**
webmailapps

▼ WebVhosts

WebVhost:: **list_do**
main

WebVhost:: **list_ssl**
_capable_domains

▼ WordPressBackup

WordPressBackup
:: **any_running**

WordPressBackup
:: **cancel**

WordPressBackup
:: **cleanup**

WordPressBackup
:: **get_available_ba**
ckups

WordPressBackup
:: **is_running**

WordPressBackup
:: **start**

▼ WordPressInstance

Manager

WordPressInstanc
eManager:: **cancel**
_scan

WordPressInstanc
eManager:: **cleanu**
p_scan

WordPressInstanc
eManager:: **chang**
e_admin_passwor
d

WordPressInstanc
eManager:: **config**
ure_autoupdate

WordPressInstanc
eManager:: **get_ap**

i_version

WordPressInstanceManager:: **get_instance_by_id**

WordPressInstanceManager:: **get_instances**

WordPressInstanceManager:: **get_latest_wordpress_version_from_wordpress_org**

WordPressInstanceManager:: **get_scan_results**

WordPressInstanceManager:: **is_installable_addon_available**

WordPressInstanceManager:: **start_scan**

▼ WordPressRestore

WordPressRestore:: **any_running**

WordPressRestore:: **cleanup**

WordPressRestore:: **start**