

UAPI Functions - EmailAuth::install_dkim_private_keys

Guide to UAPI

Return Data
Filter Output
Sort Output
Paginate Output
Output Columns
Calls from the WHM API
Custom UAPI Modules

Backup
Backup::
fullbacku

p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_password

Backup:: list_backups

Bandwidth

Bandwidth:: get_enabled_protocols

Bandwidth:: get_retention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_applications

Branding:: get_application_information

Branding:: get_available_applications

Branding:: get_information_for_applications

Description

This function installs existing keys for use in a Domain Keys Identified Mail (DKIM) record. This is useful if you do not want the system to generate keys for DKIM records.

Important:

When you disable the MailSend role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Note:

- This function does **not** update the local DNS server's records.
- If the local DNS server is authoritative for the domain's DNS records, use the UAPI `EmailAuth::enable_dkim` function to update the local DNS server's DNS records.
 - We recommend that you use the UAPI `EmailAuth::install_dkim_private_keys` and `EmailAuth::enable_dkim` functions in a batch UAPI call.

Examples

Function information

About this module

The EmailAuth module manages email authentication to ensure email deliverability.

About UAPI

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster:: read
 - CacheBuster:: update
 - Chkservd:: get_exim_ports
 - Chkservd:: get_exim_ports_ssl
 - Chrome:: get_domain
 - Contactus:: is_enabled
 - cPAddons:: get_available_addons
 - cPAddons:: get_instance_settings
 - cPAddons:: list_addon_instances
 - cPGreyList:: disable_all_domains
 - cPGreyList:: disable_domains
 - cPGreyList:: enable_all_domains
 - cPGreyList:: enable_domains
 - cPGreyList:: has_reylisting_enabled
 - cPGreyList:: list_domains
 - DAV:: disable_shared_global_addressbook
 - DAV:: enable_shared_global_addressbook
 - DAV:: get_calendar_contacts_config
 - DAV:: has_shared_global_addressbook
 - DAV:: is_dav_service_enabled

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/EmailAuth/install_dkim_private_keys?domain=example.com&key=-----BEGIN%20RSA%20PRIVATE%20KEY-----%0aAAAAAB3NzaC1yc2EAAAABIwAAAQEA5kSiV0qhs0U9ZMN20nxFe27QZ3t01T2zbH7OSXylKd%0a1rjAjYXGnSXC9j2uaZlemHlptBKVziMJC86ha7Hcj6dVOVrDQ6vF4q34bOCjtKLphQ0IjB%0azVIvqILH9eLJdRaOrS34CmgmPaisrCk5wKVlakygvUfcj3HzaTKS6THyZDGx5shdTpa9lb%0ay8tpOD3JceV7ay4w8r0DipokPC00LpvS4EABEeMo9sx8zQEaKv03XygjNCCYtFvx1QQIRG%0a1VoL7mPaHSaL3anI05RpNbm/PS+9BhZg+BqNjU4ofHBbfkXk5MiN6M7ieR4Sk5BquccboG%0aF13U5s1NgmCEekdt0amw%0a-----END%20RSA%20PRIVATE%20KEY-----%0a
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI documentation](#).

UAPI accesses and modifies data for cPanel accounts.

Notes:

- This
- Example

Find a function

- DAV:: is_horde_enabled
- DCV
 - DCV:: check_domains_via_dns
 - DCV:: check_domains_via_http
 - DCV:: ensure_domains_can_pass_dcv
 - DomainInfo
 - DomainInfo:: domains_data
 - DomainInfo:: list_domains
 - DomainInfo:: main_domain_builtin_subdomain_aliases
 - DomainInfo:: single_domain_data
- DNS
 - DNS:: ensure_domains_reside_only_locally
 - DNS:: has_local_authority
- DNSSEC
 - DNSSEC:: disable_dnssec
 - DNSSEC:: enable_dnssec
 - DNSSEC:: fetch_s_records
 - DNSSEC:: set_nsec3
 - DNSSEC:: unset_nsec3
- Email
 - Email:: account_name
 - Email:: add_auto_responder
 - Email:: add_domain_forwarder
 - Email:: add_forwarder
 - Email:: add_list
 - Email:: add_mailman_delegates
 - Email:: add_mx
 - Email:: add_pop
 - Email:: add_spam_filter

LiveAPI PHP Class

```

$cpanel = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Install a DKIM
private key to a
local server.
$poll =
$cpanel->uapi(
    'EmailAuth',
    'install_dkim_private
_keys',
    array(
        'domain' =>
'example.com',
        'key' =>
'-----BEGIN%20RSA%20P
RIVATE%20KEY-----%0aA
AAAB3NzaC1yc2EAAAABIw
AAAEAA5kSivOqhs0U9ZMN
20nxF27QZ3t01T2zbH70
SXylKd%0a1rjAjYXGnSXC
9j2uaZlemHlptBKVziMJC
86ha7Hcj6dVOVrDQ6vF4q
34bOCjtKLphQ0IjB%0azV
IvqILH9eLJdRaOrS34Cmg
mPairCk5wKVlakygvUfc
j3HzaTKS6THyZDGx5shdT
pa9lb%0ay8tpOD3JceV7a
y4w8r0DipoKPC00LpvS4E
ABEeMo9sx8zQEaKv03Xyg
jNCCYtFvx1QQIRG%0a1Vo
L7mPaHSaL3anI05RpNbm/
PS+9BhZg+BqNjU4ofHBbf
kXk5MiN6M7ieR4Sk5Bquc
cboG%0aF13U5s1NgmCEek
dt0amw%0a-----END%20R
SA%20PRIVATE%20KEY---
--%0a'
    )
);

```

Note:

For more information, read our [Guide to the LiveAPI System](#).

- UAPI Functions
 - DCV::ensure_domains_can_pass_dcv
 - This function indicates whether the account's domains can pass a Domain Control Validation (DCV) check.
- UAPI Modules
 - DCV
 - The DCV module checks Domain Control Validation (DCV).

Email: browse_mailbox

Email: change_mx

Email: check_fastmail

Email: check_pipe_forwarder

Email: delete_auto_responder

Email: delete_do_main_forwarder

Email: delete_filter

Email: delete_forwarder

Email: delete_held_messages

Email: delete_list

Email: delete_mx

Email: delete_pop

Email: disable_filter

Email: disable_mailbox_autocreate

Email: disable_spam_assassin

Email: disable_spam_autodelete

Email: disable_spam_box

Email: dispatch_client_settings

Email: edit_pop_quota

Email: enable_filter

Email: enable_mailbox_autocreate

Email: enable_spam_assassin

Email: enable_spam_box

Email: fetch_charmaps

Email: fts_rescan_mailbox

Email: generate_mailman_otp

Email: get_auto_responder

Email: get_chase

LiveAPI Perl Module

```
my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Install a DKIM
private key to a
local server.
my $poll =
$cpliveapi->uapi(
    'EmailAuth',
    'install_dkim_private
_keys',
    {
        'domain' =>
'example.com',
        'key' =>
'-----BEGIN%20RSA%20P
RIVATE%20KEY-----%0aA
AAAB3NzaC1yc2EAAAABIw
AAAEAA5kSivOqhs0U9ZMN
20nxFe27QZ3t01T2zbH7O
SXylKd%0a1rjAjYXGnSXC
9j2uaZlemHlptBKVziMJC
86ha7Hcj6dVOVrDQ6vF4q
34bOCjtKLphQ0IjB%0azV
IvqILH9eLJdRaOrS34Cmg
mPaisrCk5wKVLakygvUfc
j3HzaTKS6THyZDGx5shdT
pa9lb%0ay8tpOD3JceV7a
y4w8r0DipoKPC00LpvS4E
ABEeMo9sx8zQEaKv03Xyg
jNCCYtFvx1QQIRG%0a1Vo
L7mPaHSaL3anI05RpNbm/
PS+9BhZg+BqNjU4ofHBbf
kXk5MiN6M7ieR4Sk5Bquc
choG%0aF13U5s1NgmCEek
dt0amw%0a-----END%20R
SA%20PRIVATE%20KEY---
--%0a'
    }
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

- UAPI Modules - DNS - The DNS module checks DNS resolution issues.
- UAPI Functions - DCV: :check_domain_via_dns - This function checks whether the account's domains can pass Domain Control Validation (DCV) via a DNS request.

ts

Email: get_client_settings

Email: get_default_email_quota

Email: get_default_email_quota_mib

Email: get_disk_usage

Email: get_filter

Email: get_held_message_count

Email: get_mailbox_autocreate

Email: get_mailman_delegates

Email: get_main_account_disk_usage

Email: get_main_account_disk_usage_bytes

Email: get_max_email_quota

Email: get_max_email_quota_mib

Email: get_pop_quota

Email: get_spam_settings

Email: get_webmail_settings

Email: has_delegated_mailman_lists

Email: has_plaintext_authentication

Email: hold_outgoing

Email: is_integer

Email: list_autoresponders

Email: list_default_address

Email: list_domain_forwarders

Email: list_filters

Email: list_filters_backups

Email: list_forwarders

Email: list_forward

▼ cPanel Template Toolkit

```
<!-- Install a DKIM
private key to a
local server. -->
[% execute(
'EmailAuth',
'install_dkim_private
_keys', { 'domain' =>
'example.com', 'key'
=>
'-----BEGIN%20RSA%20P
RIVATE%20KEY-----%0aA
AAAB3NzaC1yc2EAAAABIw
AAAQEA5kSivOqhs0U9ZMN
20nxFe27QZ3t01T2zbH7O
SXylKd%0a1rjAjYXGnSXC
9j2uaZlemHlptBKVzimJC
86ha7Hcj6dVOVrDQ6vF4q
34bOCjtKLphQ0IjB%0azV
IvqILH9eLJdRaOrS34Cmg
mPaisrCk5wKvLakygvUfc
j3HzaTKS6THyZDGx5shdT
pa9lb%0ay8tpOD3JceV7a
y4w8r0DipoKPC00LpvS4E
ABEeMo9sx8zQEaKv03Xyg
jNCCYtFvx1QQIRG%0a1Vo
L7mPaHSaL3anI05RpNbm/
PS+9BhZg+BqNjU4ofHBbf
kXk5MiN6M7ieR4Sk5Bquc
cboG%0aF13U5s1NgmCEek
dt0amw%0a-----END%20R
SA%20PRIVATE%20KEY---
--%0a' } ) %]
```

Note:

For more information, read our [Guide to Template Toolkit](#) documentation.

ers_backups

Email:: list_lists

Email:: list_mail_domains

Email:: list_mx

Email:: list_pops

Email:: list_pops_with_disk

Email:: list_system_filter_info

Email:: passwd_list

Email:: passwd_pop

Email:: release_outgoing

Email:: remove_mailman_delegates

Email:: reorder_filters

Email:: set_always_accept

Email:: set_default_address

Email:: set_list_privacy_options

Email:: stats_db_status

Email:: store_filter

Email:: suspend_incoming

Email:: suspend_login

Email:: suspend_outgoing

Email:: trace_filter

Email:: unsuspend_incoming

Email:: unsuspend_login

Email:: unsuspend_outgoing

Email:: verify_password

▼ EmailAuth

EmailAuth:: disable_dkim

EmailAuth:: enable_dkim

EmailAuth:: ensure_dkim_keys_exist

▼ Command Line

```
uapi --user=username
EmailAuth
install_dkim_private_
keys
domain=example.com
key-----BEGIN%20RSA%
20PRIVATE%20KEY-----%
0aAAAAAB3NzaC1yc2EAAA
BIwAAAE5kSivOqhs0U9
ZMN20nxFe27QZ3t01T2zb
H7OSXylKd%0a1rjAjYXGn
SXC9j2uaZlemHlptBKVzi
MJC86ha7Hcj6dVOVrDQ6v
F4q34bOCjtKLphQ0IjB%0
azVIvqILH9eLJdRaOrS34
CmgmPaisrCk5wKVlakygv
Ufcj3HzaTKS6THyZDGx5s
hdTpa9lb%0ay8tpOD3Jce
V7ay4w8r0DipoKPC00Lpv
S4EABEeMo9sx8zQEaKv03
XygjNCCYtFvx1QQIRG%0a
lVoL7mPaHSaL3anI05RpN
bm/PS+9BhZg+BqNjU4ofH
BbfkXk5MiN6M7ieR4Sk5B
quccboG%0aF13U5s1NgmC
Eekdt0amw%0a-----END%
20RSA%20PRIVATE%20KEY
-----%0a
```

Notes:

- You **must** URI-encode values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bi
n/uapi
```

EmailAuth:: fetch_ dkim_private_keys

EmailAuth:: install _dkim_private_key s

EmailAuth:: install _spf_records

EmailAuth:: validat e_current_dkims

EmailAuth:: validat e_current_ptrs

EmailAuth:: validat e_current_spfs

ExternalAuthenticat ion

ExternalAuthenticat ion:: add_authn_li nk

ExternalAuthenticat ion:: configured_ modules

ExternalAuthenticat ion:: get_authn_lin ks

ExternalAuthenticat ion:: has_external _auth_modules_co nfigured

ExternalAuthenticat ion:: remove_auth n_link

Features

Features:: get_feat ure_metadata

Features:: has_fea ture

Features:: list_feat ures

Fileman

Fileman:: autocom pletedir

Fileman:: empty_tr ash

Fileman:: get_file_ content

Fileman:: get_file_i nformation

Fileman:: list_files

Fileman:: save_file _content

Fileman:: transcod e

Fileman:: upload_fi les

Output (JSON)

```
{
  "apiversion": 3,
  "module":
  "EmailAuth",
  "func":
  "install_dkim_private
_keys",
  "result": {
    "data": [
      {
        "domain":
        "example.com",
        "msg":
        "[ADD:TXT@default._do
mainkey:v=DKIM1;
k=rsa;
p=AAAAB3NzaC1yc2EAAA
BIwAAAE5kSivOqhs0U9
ZMN20nxFe27QZ3t0lT2zb
H7OSXylKd1rjAjYXGnSXC
9j2uaZlemHlptBKVziMJC
86ha7Hcj6dVOVrDQ6vF4q
34bOCjtKLphQ0IjBzVIvq
ILH9eLJdRaOrS34CmgmPa
isrCk5wKVlakygvUfcj3H
zaTKS6THyZDGx5shdTpa9
lby8tpOD3JceV7ay4w8r0
DipoKPC00LpvS4EABEeMo
9sx8zQEaKv03XyggjNCCYt
Fvx1QQIRG1VoL7mPaHSaL
3anI05RpNbm/PS+9BhZg+
BqNjU4ofHBb fkXk5MiN6M
7ieR4Sk5BqucchoGF13U5
slNgmCEekdt0amw;]",
        "status":
        1
      }
    ],
    "errors": null,
    "messages": null,
    "metadata": {
      "transformed": 1
    },
    "status": 1,
    "warnings": null
  }
}
```

▼ Ftp

- Ftp:: add_ftp
- Ftp:: allows_anonymous_ftp
- Ftp:: allows_anonymous_ftp_incoming
- Ftp:: delete_ftp
- Ftp:: ftp_exists
- Ftp:: get_ftp_daemon_info
- Ftp:: get_port
- Ftp:: get_quota
- Ftp:: get_welcome_message
- Ftp:: kill_session
- Ftp:: list_ftp
- Ftp:: list_ftp_with_disk
- Ftp:: list_sessions
- Ftp:: passwd
- Ftp:: server_name
- Ftp:: set_anonymous_ftp
- Ftp:: set_anonymous_ftp_incoming
- Ftp:: set_homedir
- Ftp:: set_quota
- Ftp:: set_welcome_message

▼ Integration

- Integration:: fetch_url

▼ KnownHosts

- KnownHosts:: create
- KnownHosts:: delete
- KnownHosts:: update
- KnownHosts:: verify

▼ LangPHP

- LangPHP:: php_get_domain_handler
- LangPHP:: php_get_impacted_domains
- LangPHP:: php_get_installed_version

Note:
 Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

Parameter	Type	Description	Possible values	Example
-----------	------	-------------	-----------------	---------

<p>s</p> <p>LangPHP:: php_get_system_default_version</p> <p>LangPHP:: php_get_vhost_versions</p> <p>LangPHP:: php_ini_get_user_basic_directives</p> <p>LangPHP:: php_ini_get_user_content</p> <p>LangPHP:: php_ini_get_user_paths</p> <p>LangPHP:: php_ini_set_user_basic_directives</p> <p>LangPHP:: php_ini_set_user_content</p> <p>LangPHP:: php_set_vhost_versions</p> <p>▼ LastLogin</p> <p>LastLogin:: get_last_or_current_logged_in_ip</p> <p>▼ Locale</p> <p>Locale:: get_attributes</p> <p>▼ Mailboxes</p> <p>Mailboxes:: expunge_mailbox_messages</p> <p>Mailboxes:: expunge_messages_for_mailbox_guid</p> <p>Mailboxes:: get_mailbox_status</p> <p>Mailboxes:: has_utf8_mailbox_names</p> <p>Mailboxes:: set_utf8_mailbox_names</p> <p>▼ Market</p> <p>Market:: cancel_pending_ssl_certificate</p> <p>Market:: create_shipping_cart</p> <p>Market:: get_all_products</p> <p>Market:: get_certificate_status_details</p> <p>Market:: get_login_url</p> <p>Market:: get_pending_ssl_certificates</p>	<p>domain</p> <p>string</p>	<p>Required</p> <p>The domain for which to install a DKIM private key on the local server.</p> <div style="border: 1px solid orange; padding: 5px;"> <p>Note</p> <p>:</p> <p>To install multiple RSA private keys for multiple domains, duplicate the parameter name. For example, use the domain=example.com, and domain=example3.com parameters.</p> </div>	<p>A valid domain.</p>	<p>example.com</p>
---	-----------------------------	---	------------------------	--------------------

- Market:: get_provider_specific_dcvc_constraints
- Market:: get_providers_list
- Market:: get_ssl_certificate_if_available
- Market:: process_ssl_pending_queue
- Market:: request_ssl_certificates
- Market:: set_status_of_pending_queue_items
- Market:: set_url_after_checkout
- Market:: validate_login_token
- ▼ Mime
 - Mime:: add_handler
 - Mime:: add_hotlink
 - Mime:: add_mime
 - Mime:: add_redirect
 - Mime:: delete_handler
 - Mime:: delete_hotlink
 - Mime:: delete_mime
 - Mime:: delete_redirect
 - Mime:: list_handlers
 - Mime:: list_hotlinks
 - Mime:: list_mime
 - Mime:: list_redirects
 - Mime:: redirect_info

key	string	Required An RSA key in Privacy-Enhanced Mail (PEM) format.	A valid Base64-encoded private key.	▼ Click to view... <pre>-----BEGIN%20RSA%20PRIVATE%20KEY-----%0aAAAAB3NzaC1yc2EAAAABIwAAQEA5kSiv0qhs0U9ZMN20nxFe27QZ3t01T2zbH70SXYlKd%0a1rjAjYXGnSXC9j2uaZ1emH1ptBKVziMJC86ha7Hcj6dVOVrDQ6vF4q34bOCjtKLphQ0IjB%0azVIvqILH9eLJdRaOrS34CmgmPaisrCk5wKVlakygvUfcj3HzaTKS6THyZDGx5shdTpa91b%0ay8tpOD3JceV7ay4w8r0DipoKPC0OLpvS4EABEeMo9sx8zQEaKv03XygnCCYtFvx1QQIRG%0a1VoL7mPaHSaL3anI05RpNbm/PS+9BhZg+BqNjU4ofHBbfkXk5MiN6M7ier4Sk5Bquccbog%0aF13U5s1NgmCEekdt0amw%0a-----END%20RSA%20PRIVATE%20KEY-----%0a</pre>
-----	--------	--	-------------------------------------	---

Note
: You must provide this parameter for each domain parameter.

Returns

Return	Type	Description	Possible values	Example
data	array of hashes	An array that contains information about the DKIM private key installation to the local server.	Each hash contains the domain, msg, and status returns.	

- ▼ ModSecurity
 - ModSecurity:: disable_all_domains
 - ModSecurity:: disable_domains
 - ModSecurity:: enable_all_domains
 - ModSecurity:: enable_domains

ModSecurity:: has_modsecurity_installed

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql:: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_relative_uri

domain	string	The DKIM private key's associated domain. This function returns this value in the data array.	A valid domain.	example.com
msg	string	The DKIM private key's installation status message. This function returns this value in the data array.	A valid string.	▼ Click to view... [ADD: TXT @default._domainkey:v=DKIM1;k=rsa;p=AAAAB3NzaC1yc2EAAAABIwAAAQEA5kSivOqhs0U9ZMN20nxFe27QZ3t01T2zbH7OSxylKd1rjAjYXGnSXC9j2uaZ1emH1ptBKVziMJC86ha7Hcj6dVOvRdQ6vF4q34bOCjtKLp hQ0IjBzV IvqILH9e LwJdRaOrS34CmgmPaisrCk5wKVlakygvUfcj3HzaTKS6THyZD Gx5shdTp a91by8tp OD3JceV7 ay4w8r0D ipoKPC00 LpvS4EAB EeMo9sx8 zQEaKv03 XygnNCCY tFvx1QQI RGlVoL7m PaHSaL3a nI05RpNbm/PS+9Bh Zg+BqNjU 4ofHBbfk Xk5MiN6M 7ieR4Sk5 BquccboG F13U5s1N gmCEekdt 0amw;]
status	Boolean	Whether the system installed the DKIM private key to the local server. This function returns this value in the data array.	<ul style="list-style-type: none">1 — The system installed the DKIM private key.0 — The system cannot install the DKIM private key.	1

- ▼ PassengerApps
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: ensure_deps
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- ▼ PasswdStrength
 - PasswdStrength:: get_required_strength
- ▼ Personalization
 - Personalization::set
 - Personalization::get
- ▼ Postgresql
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- ▼ Pushbullet
 - Pushbullet:: send_test_message
- ▼ Quota
 - Quota:: get_quota_info

- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL :: disable_mail_sni

SSL:: enable_mail
_sni

SSL:: fetch_best_f
or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autossl_
excluded_domains

SSL:: get_autossl_
pending_queue

SSL:: get_autossl_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autossl_c
heck_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_homedir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list_webmailapps

▼ WebVhosts

WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressBackup

WordPressBackup:: any_running

WordPressBackup:: cancel

WordPressBackup:: cleanup

WordPressBackup:: get_available_backups

WordPressBackup:: is_running

WordPressBackup:: start

▼ WordPressInstance

Manager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_in

stance_by_id

WordPressInstanceManager::get_instances

WordPressInstanceManager::get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager::get_scan_results

WordPressInstanceManager::is_installable_addon_available

WordPressInstanceManager::start_scan

▼ WordPressRestore

WordPressRestore::any_running

WordPressRestore::cleanup

WordPressRestore::start