

UAPI Functions - UserManager::edit_user

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::
fullbackup

p_to_ftp

Backup:: fullbackup
p_to_homedir

Backup:: fullbackup
p_to_scp_with_key

Backup:: fullbackup
p_to_scp_with_password

Backup:: list_backups

Bandwidth

Bandwidth:: get_enabled_protocols

Bandwidth:: get_retention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_applications

Branding:: get_application_information

Branding:: get_available_applications

Branding:: get_information_for_applications

Description

This function edits a Subaccount.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess#####/execute/UserManager/edit_user?alternate_email=robert%40example.com&domain=example.com&password=12345luggage&real_name=Bob%20Doe&services.email.enabled=1&services.email.quota=2&services.ftp.enabled=1&services.ftp.homedir=%2Fbob&services.webdisk.enabled=1&services.webdisk.private=0&services.webdisk.homedir=%2Fbob&services.webdisk.perms=0&type=sub&username=example1
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

▼ LiveAPI PHP Class

Function information

About this module

The `UserManager` module modifies a cPanel account's Subaccounts.

About UAPI

UAPI accesses and modifies data for cPanel accounts.

- Branding:: image
- Branding:: include
- Branding:: spritelist
- CacheBuster
 - CacheBuster:: read
 - CacheBuster:: update
- Chkservd
 - Chkservd:: get_exim_ports
 - Chkservd:: get_exim_ports_ssl
- Chrome
 - Chrome:: get_domain
- Contactus
 - Contactus:: is_enabled
- cPAddons
 - cPAddons:: get_available_addons
 - cPAddons:: get_instance_settings
 - cPAddons:: list_addon_instances
- cPGreyList
 - cPGreyList:: disable_all_domains
 - cPGreyList:: disable_domains
 - cPGreyList:: enable_all_domains
 - cPGreyList:: enable_domains
 - cPGreyList:: has_greylisting_enabled
 - cPGreyList:: list_domains
- DAV
 - DAV:: disable_shared_global_addressbook
 - DAV:: enable_shared_global_addressbook
 - DAV:: get_calendar_contacts_config
 - DAV:: has_shared_global_addressbook
 - DAV:: is_dav_service_enabled

```

$cpanel = new
CPANEL(); // Connect
to cPanel - only do
this once.

// Edit Subaccount.
$Usermanager =
$cpanel->uapi(
    'UserManager',
    'edit_user',
    array(
        'alternate_email'
=>
'robert@example.com',
        'domain' =>
'example.com',
        'password' =>
'12345luggage',
        'real_name' =>
'Bob Doe',

        'services.email.enabled' => '1',

        'services.email.quota'
=> '2',

        'services.ftp.enabled'
=> '1',

        'services.ftp.homedir'
=> '/bob',

        'services.webdisk.enabled' => '1',

        'services.webdisk.private' => '0',

        'services.webdisk.homedir' => '/bob',

        'services.webdisk.perms' => '0',
        'type' =>
'sub',
        'username' =>
'example1',
    )
);

```

Notes:

- Th
- Fe
- int
- Ur
- mu
- us
- 20
- or
- 20
-).'
- 20
- or
- 20
-).

Find a function

- UAPI Functions - DomainInfo::list_domains — This function lists the cPanel account's domains.

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

Email:: add_spam_filter

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ LiveAPI Perl Module

- UAPI Functions -

- Contac^tact^us^{::}is^{_}enabled — This function checks whether the account's contact option is enabled.

- UAPI Functions -

- Chks^{er}vd[:]:get^{_}exim^{_}ports — This function lists the ports on which Exim listens.

- UAPI Functions -

- Chks^{er}vd[:]:get^{_}exim^{_}ports^{_}ssl — This function retrieves Exim's SSL port.

Email: browse_mailbox
Email: change_mx
Email: check_fastmail
Email: check_pipe_forwarder
Email: delete_auto_responder
Email: delete_do_main_forwarder
Email: delete_filter
Email: delete_forwarder
Email: delete_held_messages
Email: delete_list
Email: delete_mx
Email: delete_pop
Email: disable_filter
Email: disable_mailbox_autocreate
Email: disable_spam_assassin
Email: disable_spam_autodelete
Email: disable_spam_box
Email: dispatch_client_settings
Email: edit_pop_quota
Email: enable_filter
Email: enable_mailbox_autocreate
Email: enable_spam_assassin
Email: enable_spam_box
Email: fetch_charmaps
Email: fts_rescan_mailbox
Email: generate_mailman_opt
Email: get_auto_responder
Email: get_chase

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.  
  
# Edit Subaccount.  
my $Usermanager =  
$cpliveapi->uapi(  
    'UserManager',  
    'edit_user',  
    {  
        'alternate_email'  
=>  
    'robert@example.com',  
        'domain' =>  
    'example.com',  
        'password' =>  
    '12345luggage',  
        'real_name' =>  
    'Bob Doe',  
  
        'services.email.enabled'  
=> '1',  
  
        'services.email.quota'  
=> '2',  
  
        'services.ftp.enabled'  
=> '1',  
  
        'services.ftp.homedir'  
=> '/bob',  
  
        'services.webdisk.enabled'  
=> '1',  
  
        'services.webdisk.private'  
=> '0',  
  
        'services.webdisk.homedir'  
=> '/bob',  
  
        'services.webdisk.perms'  
=> '0',  
        'type' =>  
    'sub',  
        'username' =>  
    'example1',  
    }  
);
```

ts

Email: `get_client_settings`

Email: `get_default_email_quota`

Email: `get_default_email_quota_mib`

Email: `get_disk_usage`

Email: `get_filter`

Email: `get_held_message_count`

Email: `get_mailbox_autocreate`

Email: `get_mailman_delegates`

Email: `get_main_account_disk_usage`

Email: `get_main_account_disk_usage_bytes`

Email: `get_max_email_quota`

Email: `get_max_email_quota_mib`

Email: `get_pop_quota`

Email: `get_spam_settings`

Email: `get_webmail_settings`

Email: `has_delegated_mailman_lists`

Email: `has_plaintext_authentication`

Email: `hold_outgoing`

Email: `is_integer`

Email: `list_autoresponders`

Email: `list_default_address`

Email: `list_domain_forwarders`

Email: `list_filters`

Email: `list_filters_backups`

Email: `list_forwarders`

Email: `list_forward`

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ **cPanel Template Toolkit**

```
<!-- Edit Subaccount.
-->
[%
execute('UserManager'
, 'edit_user',
{'alternate_email' =>
'robert@example.com',
'domain' =>
'example.com',
'password' =>
'12345luggage',
'real_name' => 'Bob
Doe',
'services.email.enabled' => '1',
'services.email.quota'
=> '2',
'services.ftp.enabled'
=> '1',
'services.ftp.homedir'
=> '/bob',
'services.webdisk.enabled' => '1',
'services.webdisk.private' => '0',
'services.webdisk.homedir' => '/bob',
'services.webdisk.perms' => '0', 'type' =>
'sub', 'username' =>
'example1'} ) %]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

ers_backups

Email:: list_lists

Email:: list_mail_domains

Email:: list_mx

Email:: list_pops

Email:: list_pops_with_disk

Email:: list_system_filter_info

Email:: passwd_list

Email:: passwd_pop

Email:: release_outgoing

Email:: remove_mailman_delegates

Email:: reorder_filters

Email:: set_always_accept

Email:: set_default_address

Email:: set_list_privacy_options

Email:: stats_db_status

Email:: store_filter

Email:: suspend_incoming

Email:: suspend_login

Email:: suspend_outgoing

Email:: trace_filter

Email:: unsuspend_incoming

Email:: unsuspend_login

Email:: unsuspend_outgoing

Email:: verify_password

▼ EmailAuth

EmailAuth:: disable_dkim

EmailAuth:: enable_dkim

EmailAuth:: ensure_dkim_keys_exist

▼ Command Line

```
uapi --user=username
UserManager edit_user
alternate_email=robert%40example.com
domain=example.com
password=12345luggage
real_name='Bob Doe'
services.email.enabled=1
services.email.quota=2
services.ftp.enabled=1
services.ftp.homedir=%2Fbob
services.webdisk.enabled=1
services.webdisk.private=0
services.webdisk.homedir=\/bob
services.webdisk.permissions=0 type=sub
username=example1
```

Notes:

- You **must** [URI-encode](#) values.
- `username` represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

▼ Output (JSON)

```
{
  "errors": null,
  "status": 1,
  "messages": null,
```

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat
ion

ExternalAuthenticat
ion:: add_auth_li
nk

ExternalAuthenticat
ion:: configured_
modules

ExternalAuthenticat
ion:: get_authn_lin
ks

ExternalAuthenticat
ion:: has_external
_auth_modules_co
nfigured

ExternalAuthenticat
ion:: remove_auth
n_link

Features

Features:: get_feat
ure_metadata

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file
_content

Fileman:: transcod
e

Fileman:: upload_fi
les

```
"metadata":{
},
"data":{
"dismissed_merge_cand  
idates":[
],
"invite_expiration":n  
ull,
"avatar_url":null,
"synced_password":1,
"full_username":"exam  
ple1@example.com",
"merge_candidates":[
],
"type":"sub",
"real_name":"Bob  
Doe",
"can_set_quota":0,
"domain":"example.com",
,
"parent_type":null,
"alternate_email":"ro  
b@example.com",
"can_delete":1,
"sub_account_exists":  
0,
"special":0,
"username":"example1",
,
"issues":[
],
"has_expired_invite":  
0,
"dismissed":0,
```

▼ Ftp

Ftp:: add_ftp
Ftp:: allows_anonymous_ftp
Ftp:: allows_anonymous_ftp_incoming
Ftp:: delete_ftp
Ftp:: ftp_exists
Ftp:: get_ftp_daemon_info
Ftp:: get_port
Ftp:: get_quota
Ftp:: get_welcome_message
Ftp:: kill_session
Ftp:: list_ftp
Ftp:: list_ftp_with_disk
Ftp:: list_sessions
Ftp:: passwd
Ftp:: server_name
Ftp:: set_anonymous_ftp
Ftp:: set_anonymous_ftp_incoming
Ftp:: set_homedir
Ftp:: set_quota
Ftp:: set_welcome_message

▼ Integration

Integration:: fetch_url

▼ KnownHosts

KnownHosts:: create
KnownHosts:: delete
KnownHosts:: update
KnownHosts:: verify

▼ LangPHP

LangPHP:: php_get_domain_handler
LangPHP:: php_get_impacted_domains
LangPHP:: php_get_installed_version

```
"can_set_password":1,  
  
"guid":"EXAMPLE1:EXAMPLE.COM:577D1D1A:69E2308AFB4F1FDAFE67CCCD8A33785DCCDEC199124A6CC0397F86A2789B7E03",  
  "services":{  
    "email":{  
  
"enabled":1,  
      "quota":2  
    },  
    "ftp":{  
  
"enabled":1,  
  
"quota":"42.00",  
  
"homedir":"bob",  
    },  
    "webdisk":{  
  
"homedir":"bob",  
  
"enabled":1,  
  
"enabledigest":1,  
  
"private":0,  
  
"perms":"rw"  
    }  
  },  
  
"phone_number":null,  
  
"has_siblings":0,
```


s

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_get_user_basic_directives

LangPHP:: php_get_user_content

LangPHP:: php_get_user_paths

LangPHP:: php_set_user_basic_directives

LangPHP:: php_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_mailbox_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

```

    "has_invite":0
  }
}

```

Note:
Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

Parameters

Parameter	Type	Description	Possible values	Example
alternate_email	string	An alternate email address for the Subaccount's user.	A valid email address.	user@example.com
		<div data-bbox="732 957 870 1871" style="border: 1px solid yellow; padding: 5px;"> <p>Note: The cPanel account user could use this email address to contact the Subaccount user if their primary email address's domain is unavailable.</p> </div> <p>This parameter defaults to null.</p>		

Market:: [get_provider_specific_dcw_constraints](#)

Market:: [get_providers_list](#)

Market:: [get_ssl_certificate_if_available](#)

Market:: [process_ssl_pending_queue](#)

Market:: [request_ssl_certificates](#)

Market:: [set_status_of_pending_queue_items](#)

Market:: [set_url_after_checkout](#)

Market:: [validate_login_token](#)

▼ Mime

Mime:: [add_handler](#)

Mime:: [add_hotlink](#)

Mime:: [add_mime](#)

Mime:: [add_redirect](#)

Mime:: [delete_handler](#)

Mime:: [delete_hotlink](#)

Mime:: [delete_mime](#)

Mime:: [delete_redirect](#)

Mime:: [list_handlers](#)

Mime:: [list_hotlinks](#)

Mime:: [list_mime](#)

Mime:: [list_redirects](#)

Mime:: [redirect_info](#)

▼ ModSecurity

ModSecurity:: [disable_all_domains](#)

ModSecurity:: [disable_domains](#)

ModSecurity:: [enable_all_domains](#)

ModSecurity:: [enable_domains](#)

<p>avatar_url</p>	<p>string</p>	<p>Warning : We reserved this parameter for future use. Do not use this parameter.</p> <p>The user's Subaccount profile photo.</p> <p>This parameter defaults to null.</p>	<p>A valid HTTPS URL that points to an image file.</p> <p>Note : You must use the HTTPS protocol to prevent mixed content warnings when users view the photo from another HTTPS URL.</p>	<p>▼ Click to view...</p> <p>https://img.example.com/avatars/example.jpg</p>
<p>domain</p>	<p>string</p>	<p>Required</p> <p>The Subaccount user's associated domain.</p>	<p>A domain that the cPanel account owns.</p>	<p>example.com</p>
<p>password</p>	<p>string</p>	<p>Required</p> <p>The Subaccount's password.</p> <p>Note : The Subaccount uses this password for email, FTP, and Web Disk services.</p>	<p>A secure password.</p>	<p>12345luggage</p>

ModSecurity:: has_modsecurity_installed

ModSecurity:: list_domains

▼ Mysql

Mysql:: add_host

Mysql:: add_host_note

Mysql:: check_database

Mysql:: create_database

Mysql:: create_user

Mysql:: delete_database

Mysql:: delete_host

Mysql:: delete_user

Mysql:: get_host_notes

Mysql:: get_privileges_on_database

Mysql:: get_restrictions

Mysql:: get_server_information

Mysql:: locate_server

Mysql:: rename_database

Mysql:: rename_user

Mysql:: repair_database

Mysql:: revoke_access_to_database

Mysql:: set_password

Mysql:: set_privileges_on_database

▼ Notifications

Notifications:: get_notifications_count

▼ NVData

NVData:: get

NVData:: set

▼ Parser

Parser:: firstfile_relative_uri

phone_number	string	<p>Warning : We reserved this parameter for future use. Do not use this parameter.</p> <p>The Subaccount user's phone number.</p> <p>This parameter defaults to null.</p>	A valid phone number that conforms to ITU-T's E.164 -recommended standard for the representation of telephone numbers.	+15551234567
real_name	string	<p>The Subaccount user's name.</p> <p>This parameter defaults to null.</p>	<ul style="list-style-type: none"> • A first name. • A last name. • A first name and last name. • An empty string. 	John Doe
services.email.enabled	Boolean	<p>Whether to grant the Subaccount email access.</p> <p>This parameter defaults to 0.</p>	<ul style="list-style-type: none"> • 1 — Can access. • 0 — Cannot access. 	1

- ▼ **PassengerApps**
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: ensure_deps
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- ▼ **PasswdStrength**
 - PasswdStrength:: get_required_strength
- ▼ **Personalization**
 - Personalization::set
 - Personalization::get
- ▼ **Postgresql**
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- ▼ **Pushbullet**
 - Pushbullet:: send_test_message
- ▼ **Quota**
 - Quota:: get_quota_info

<pre>services.email.quota</pre>	<i>integer</i>	<p>The maximum amount of disk space that the subaccount's email account may use.</p> <div data-bbox="732 296 870 726" style="border: 1px solid orange; padding: 5px;"> <p>Note : We introduced this functionality in cPanel & WHM version 70.</p> </div> <p>This parameter defaults to the defined system value.</p>	<ul style="list-style-type: none"> • A positive integer that represents the maximum amount of disk space, in Megabytes (MB). <div data-bbox="935 386 1029 1667" style="border: 1px solid orange; padding: 5px;"> <p>Note : This is available since version 70.</p> </div> <ul style="list-style-type: none"> • 0 or unlimited — The subaccount possesses unlimited disk space. 	500
---------------------------------	----------------	---	---	-----

- Resellers:: list_accounts
- ResourceUsage:: get_usages
- Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- Session:: create_temp_user
- SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- SpamAssassin:: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- SSH:: get_port
- SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL:: disable_mail_sni

services.ftp.enabled	Boolean	Whether to grant the Subaccount FTP access. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Can access. • 0 — Cannot access. 	1
services.ftp.homedir	string	The Subaccount's FTP home directory. Note : This parameter is required if you enabled FTP access.	A relative path from the cPanel account's home directory. Note : The specified directory must exist.	/Subaccount
services.webdisk.enabled	Boolean	Whether to grant the Subaccount Web Disk access. This parameter defaults to 0.	<ul style="list-style-type: none"> • 1 — Can access. • 0 — Cannot access. 	1
services.webdisk.enabledigest	Boolean	Whether to enable Web Disk digest authentication. Note : <ul style="list-style-type: none"> • Only enable Digest Authentication if o 	<ul style="list-style-type: none"> • 1 — Enabled. • 0 — Disabled. 	0

SSL:: enable_mail_sni
SSL:: fetch_best_for_domain
SSL:: fetch_cert_info
SSL:: fetch_certificates_for_fqdns
SSL:: fetch_key_and_cabundle_for_certificate
SSL:: find_certificates_for_key
SSL:: find_csrs_for_key
SSL:: generate_certificate
SSL:: generate_csr
SSL:: generate_key
SSL:: get_autossl_excluded_domains
SSL:: get_autossl_pending_queue
SSL:: get_autossl_problems
SSL:: get_cabundle
SSL:: get_cn_name
SSL:: install_ssl
SSL:: installed_hosts
SSL:: installed_hosts
SSL:: is_autossl_check_in_progress
SSL:: is_mail_sni_supported
SSL:: is_sni_supported
SSL:: list_certs
SSL:: list_csrs
SSL:: list_keys
SSL:: list_ssl_items
SSL:: mail_sni_status
SSL:: rebuild_mail_sni_config

c
l
i
e
n
t
s
t
h
a
t
r
e
q
u
i
r
e
a
d
d
i
t
i
o
n
a
l
c
o
m
p
a
t
i
b
i
l
i
t
y
s
u
p
p
o
r
t
o
n
c
e
r
t
a
i
n
v
e
r
s
i
o
n
s
o
f
W
i
n
d
o
w
s
®
o
p
e
r
a

SSL:: rebuildssldb
SSL:: remove_aut
ossl_excluded_do
mains
SSL:: set_autossl_
excluded_domains
SSL:: set_cert_frie
ndly_name
SSL:: set_csr_frien
dly_name
SSL:: set_key_frie
ndly_name
SSL:: set_primary
_ssl
SSL:: set_ssl_shar
e
SSL:: show_cert
SSL:: show_csr
SSL:: show_key
SSL:: start_autossl
_check
SSL:: toggle_ssl_r
edirects_for_doma
ins
SSL:: upload_cert
SSL:: upload_key
▼ StatsBar
StatsBar:: get_stat
s
▼ Styles
Styles:: current
Styles:: list
Styles:: set_default
Styles:: update
▼ SubDomain
SubDomain:: adds
ubdomain
▼ Themes
Themes:: get_the
me_base
Themes:: list
Themes:: update
▼ Tokens
Tokens:: create_fu
ll_access
Tokens:: list
Tokens:: rename
Tokens:: revoke

t
i
n
g
s
y
s
t
e
m
s
.
T
h
i
s
c
o
m
p
a
t
i
b
i
l
i
t
y
s
u
p
p
o
r
t
i
s
o
n
l
y
r
e
q
u
i
r
e
d
o
n
s
e
r
v
e
r
s
t
h
a
t
u
s
e
a
s
e
l
f
-
s
i
g
n
e
d
c
e

- TwoFactorAuth: generate_user_configuration
 - TwoFactorAuth: get_user_configuration
 - TwoFactorAuth: remove_user_configuration
 - TwoFactorAuth: set_user_configuration
- UserManager: check_account_conflicts
 - UserManager: create_user
 - UserManager: delete_user
 - UserManager: dismiss_user
 - UserManager: edit_user
 - UserManager: list_users
 - UserManager: lookup_service_account
 - UserManager: lookup_user
 - UserManager: merge_service_account
 - UserManager: unlink_service_account
- UserTasks: delete
 - UserTasks: retrieve
- VersionControl: create
 - VersionControl: delete
 - VersionControl: retrieve
 - VersionControl: update
- VersionControlDeployment: create

r
t
i
f
i
c
a
t
e
f
o
r
t
h
e
c
p
s
r
v
d
a
n
d
c
p
d
a
v
d
d
a
e
m
o
n

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_homedir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list_webmailapps

▼ WebVhosts

WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressBackup

WordPressBackup:: any_running

WordPressBackup:: cancel

WordPressBackup:: cleanup

WordPressBackup:: get_available_backups

WordPressBackup:: is_running

WordPressBackup:: start

▼ WordPressInstanceManager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_in

s .
• W
e
r
e
c
o
m
m
e
n
d
t
h
a
t
y
o
u
d
o
n
o
t
u
s
e
D
i
g
e
s
t
A
u
t
h
e
n
t
i
c
a
t
i
o
n
.

This parameter defaults to 0.

services.webdisk.private	Boolean	Whether to set the Web Disk directory's permissions to public or private. This parameter defaults to 0.	<ul style="list-style-type: none"> 1 — Private (0700). 0 — Public (0755). 	1
--------------------------	---------	--	---	---

stance_by_id
 WordPressInstanceManager:: **get_instances**
 WordPressInstanceManager:: **get_latest_wordpress_version_from_wordpress_org**
 WordPressInstanceManager:: **get_scan_results**
 WordPressInstanceManager:: **is_installable_addon_available**
 WordPressInstanceManager:: **start_scan**
 WordPressRestore
 WordPressRestore:: **any_running**
 WordPressRestore:: **cleanup**
 WordPressRestore:: **start**

services.webdisk.homedir	<i>string</i>	<p>The Subaccount's Web Disk home directory.</p> <div style="border: 1px solid orange; padding: 5px;"> <p>Note: This parameter is required if you enable Web Disk access.</p> </div>	A valid path, relative to the cPanel account's home directory.	/Subaccount
services.webdisk.perms	<i>string</i>	<p>Whether to grant write permissions to the Subaccount.</p> <div style="border: 1px solid orange; padding: 5px;"> <p>Note: The services.webdisk.homedir parameter determines the Subaccount's Web Disk home directory.</p> </div> <p>This parameter defaults to <i>rw</i>.</p>	<ul style="list-style-type: none"> • <i>ro</i> — Read-only permissions. • <i>rw</i> — Read and write permissions. 	<i>rw</i>
<i>type</i>	<i>string</i>	<p>The type of account.</p> <p>This parameter defaults to <i>sub</i>.</p>	<i>sub</i> — A Subaccount.	<i>sub</i>

username	<i>string</i>	<p>Required</p> <p>The Subaccount's username.</p>	<p>A username that meets the Subaccount name limitations.</p> <ul style="list-style-type: none"> • Length — 64 characters. • Characters — a-z, A-Z, 0-9, dot(.), hyphen(-), underscore (_). <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : This value does not include the domain name.</p> </div>	example
----------	---------------	--	--	---------

Returns

Return	Type	Description	Possible values	Example
alternate_email	<i>string</i>	An alternate email address for the subaccount's user.	A valid email address.	user@example.com
avatar_url	<i>string</i>	The user's subaccount profile photo.	A valid HTTPS URL that points to an image file.	Click to view... https://img.example.com/avatars/example.jpg
can_delete	<i>Boolean</i>	Whether the cPanel account user can delete the subaccount.	<ul style="list-style-type: none"> • 1 — Can delete. • 0 — Cannot delete. 	0

can_set_password	<i>Boolean</i>	Whether the cPanel account user can change the subaccount's password.	<ul style="list-style-type: none"> • 1 — Can change. • 0 — Cannot change. <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : The function returns a 0 value for subaccounts that inherit their password from the cPanel account.</p> </div>	1
can_set_quota	<i>Boolean</i>	Whether the cPanel account user can change the subaccount's disk usage quota.	<ul style="list-style-type: none"> • 1 — Can change. • 0 — Cannot change. 	0
dismissed	<i>Boolean</i>	Whether the cPanel account user dismissed the merge prompt for the service account.	<ul style="list-style-type: none"> • 1 — Dismissed. • 0 — Did not dismiss. <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : Only service accounts return this value.</p> </div>	1
domain	<i>string</i>	The subaccount user's associated domain.	A domain that the cPanel account owns.	example.com
full_username	<i>string</i>	The subaccount's username and domain name.	A valid username, the @ character, and the associated domain.	user@example.com

guid	string	The subaccount unique identifier.	The system assigned unique value.	Click to view... N4641:EXAMPLE.COM:564CC8A7:A82EA007D8348AC631C0170F9418EC1DEB0D164CC5A722A87C55EF5DD2AD98D4
issues	array	Information about any issues or problems with the subaccount.	This array contains the type, area, service, message, used, and limit returns.	
type	string	The type of issue. The function returns this value in the issues array.	<ul style="list-style-type: none"> error warning info 	info
area	string	The affected section of cPanel & WHM. The function returns this value in the issues array.	A valid section name.	quota
service	string	The affected service. The function returns this value in the issues array.	<ul style="list-style-type: none"> email ftp webdisk 	email
message	string	The description of the issue. The function returns this value in the issues array.	A valid string.	Your account is over quota.
used	integer	The number of Megabytes (MB) that the account currently uses. The function returns this value in the issues array.	A positive integer.	2000
limit	integer	The set quota Megabyte (MB) limit for the affected subaccount. The function returns this value in the issues array.	A positive integer.	1500

merge_candidates	<i>array</i>	An array of hashes that represents the service accounts that the system could merge for this subaccount.	This array contains the alternate_email, avatar_url, can_delete, can_set_password, can_set_quota, dismissed, domain, full_username, guid, has_siblings, issues, merge_candidates, parent_type, phone_number, real_name, services, special, sub_account_exists, synced_password, type, and user name returns.	
has_siblings	<i>Boolean</i>	Whether the service account shares a full_username value with another service account.	<ul style="list-style-type: none"> • 1 — Shares. • 0 — Does not share. 	0
parent_type	<i>string</i>	The type of account that could own the service account.	<ul style="list-style-type: none"> • sub — A subaccount. • hypothetical — A hypothetical subaccount that does not yet exist, but the user could create as part of a merge. • null — Not a merge candidate. 	hypothetical
phone_number	<i>string</i>	The subaccount user's phone number.	A valid phone number that conforms to ITU-T's E.164-recommended standard for the representation of telephone numbers.	+15551234567
real_name	<i>string</i>	The name of the subaccount's user.	<ul style="list-style-type: none"> • A first name, a last name, or a first name and last name. • An empty string. 	John Doe

services	hash	This hash contains information about the subaccount's access to email, FTP, and Web Disk.	This hash contains the email, ftp, and webdisk returns.	
email	hash	This hash contains the information that indicates the subaccount's email status. The function returns this hash in the services hash.	This hash contains the enabled and quota returns.	
enabled	Boolean	Whether the subaccount can access Webmail, POP, and IMAP services. The function returns this value in the email hash.	<ul style="list-style-type: none"> • 1 — Can access. • 0 — Cannot access. 	1
quota	integer	The maximum amount of disk space allocated to subaccount's email account. The function returns this value in the email hash.	A positive integer that represents the maximum disk space that the subaccount may use, in Megabytes (MB). <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : In cPanel & WHM version 70 and later, this function will not return 0 as a value.</p> </div>	100
ftp	hash	This hash contains the information that indicates the subaccount's FTP status. The function returns this hash in the services hash.	This hash contains the enabled, quota, and homedir returns.	

enabled	<i>Boolean</i>	Whether the subaccount can access FTP. The function returns this value in the <code>ftp</code> hash.	<ul style="list-style-type: none"> • 1 — Can access. • 0 — Cannot access. 	0
quota	<i>integer</i>	The subaccount's FTP disk space quota. The function returns this value in the <code>ftp</code> hash.	<ul style="list-style-type: none"> • A positive integer between 1 and 999999 that represents the maximum disk space that the subaccount may use, in Megabytes (MB). • 0 — Unlimited. 	100
home_dir	<i>string</i>	The subaccount's FTP home directory. The function returns this value in the <code>ftp</code> hash.	A valid path, relative to the cPanel account's home directory.	/subaccount
webdisk	<i>hash</i>	This hash contains information that indicates the subaccount's Web Disk status. The function returns this hash in the <code>services</code> hash.	This hash contains the <code>enabled</code> , <code>home_dir</code> , <code>perms</code> , and <code>private</code> returns.	
enabled	<i>Boolean</i>	Whether the subaccount can access Web Disk. The function returns this value in the <code>webdisk</code> hash.	<ul style="list-style-type: none"> • 1 — Can access. • 0 — Cannot access. 	0
home_dir	<i>string</i>	The subaccount's Web Disk home directory. The function returns this value in the <code>webdisk</code> hash.	A valid path, relative to the cPanel account's home directory.	/bob
perms	<i>string</i>	Whether to grant write permissions to the subaccount. The function returns this value in the <code>webdisk</code> hash.	<ul style="list-style-type: none"> • <code>ro</code> — Read-only permissions. • <code>rw</code> — Read and write permissions. 	<code>rw</code>

private	<i>Boolean</i>	<p>Whether to set the Web Disk directory's permissions to public or private.</p> <p>The function returns this value in the web disk hash.</p>	<ul style="list-style-type: none"> • 1 — Private (0700). • 0 — Public (0755). 	0
special	<i>Boolean</i>	<p>Whether the account is a system-created special account that the user cannot remove.</p>	<ul style="list-style-type: none"> • 1 — A special account. • 0 — Not a special account. 	1
sub_account_exists	<i>Boolean</i>	<p>Whether a subaccount exists with the same username.</p>	<ul style="list-style-type: none"> • 1 — Exists. • 0 — Does not exist. <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : The function returns a null value if the account is not a service account.</p> </div>	0
synced_password	<i>Boolean</i>	<p>Whether the user has synchronized the passwords for each of the subaccount's service accounts.</p>	<ul style="list-style-type: none"> • 1 — Synchronized. • 0 — Not synchronized. <div style="border: 1px solid black; padding: 5px; margin-top: 10px;"> <p>Note : The function returns a null value if the account is not a subaccount.</p> </div>	0

type	<i>string</i>	The type of account.	<ul style="list-style-type: none"> • <code>sub</code> — A subaccount. • <code>hypothetical</code> — A hypothetical subaccount that does not exist, but that the user could create as part of a merge. • <code>service</code> — A service account. • <code>cpanel</code> — The cPanel account. 	sub
username	<i>string</i>	The username for the subaccount.	<p>A username that meets the subaccount name limitations.</p> <ul style="list-style-type: none"> • Length — 64 characters. • Characters — a-z, A-Z, 0-9, dot (.), hyphen (-), underscore (_). <div style="border: 1px solid orange; padding: 5px; margin-top: 10px;"> <p>Note : This value does not include the domain name.</p> </div>	example