

# cPanel API 2 Functions - SSH::importkey

## Guide to cPanel API 2

- Return Data
- Filter and Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- cPanel Tags **(deprecated)**

## Description

This function imports an SSH key.

### Important:

This function **will** overwrite any existing keys that use the same name as the imported key.

### Warning:

We **strongly** recommend that you use [UAPI](#) instead of cPanel API 2. However, no equivalent UAPI function exists.

## Function information

AddonDomain:  
main:: add  
daddond

omain

AddonDomain:: del  
addondomain

AddonDomain:: list  
addondomains

### Backups

Backups:: listfullba  
ckups

### Bandwidth

Bandwidth:: addhtt  
pbandwidth

Bandwidth:: getbw  
data

Bandwidth:: getho  
urlyaveragebwover  
year

### BoxTrapper

BoxTrapper:: acco  
untmanagelist

### Branding

Branding:: addbra  
ndingobj

Branding:: applist

Branding:: brandin  
geditor

Branding:: createp  
kg

Branding:: cssmer  
ge

Branding:: delbran  
dingobj

Branding:: delpkg

## Examples

AddonDomain

### WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_apiversion=2&cpanel_jsonapi_module=SSH&cpanel_jsonapi_func=importkey&key=-----BEGIN%20RSA%20PRIVATE%20KEY-----%5CnProc-Type%3A%204%2CENCRYPTED%5CnDEK-Info%3A%20DES-EDE3-CBC%2C8B36FD4196F9015D%5Cn%5CnRttykPEmZu4jTfPzIZkSsfkZaTTXOt3Ho%2BJCqG6Hp1aCm%2FKibiEBkVUXkC4QLrUL%5CnB%2B%2FifvjN%2BiXYwiYvXLSB5EnVyEuPIjFnnugSIN1Cp84mU1RSyO4DfhPTdWLwr5tP%5CnIYqzpB0cxL2zqX%2BGB8BCx%2F52NDQ%2FnQWmepKZrod3kasza%2FH580F5103fJ1U%2B3WQb%5Cn1YqgOMKeDcatCDgrlc%2F5%2Fqz6xjk%2BHrivnZL%2BEQTS0av8ZtWEjsjCwvn9N0Gb1TOW%5Cni8uv%2FhPpu6SVZkLUb7RUSIEXW44%2B%2FSa6PsSjTq5SLu8C%2FDV8K6x63R%2F
```

## About this module

The SSH module manages SSH keys.

Branding:: gensprites  
 Branding:: getbrandingpkg  
 Branding:: getbrandingpkgstatus  
 Branding:: getdefaultbrandingpkg  
 Branding:: installbrandingpkgs  
 Branding:: installimages  
 Branding:: killimages  
 Branding:: listingtypes  
 Branding:: listobjecttypes  
 Branding:: preloadconf  
 Branding:: resetall  
 Branding:: resetscripts  
 Branding:: resethtml  
 Branding:: resolvefile  
 Branding:: resolvelocalcss  
 Branding:: savelocalcss  
 Branding:: setbrandingpkgstatus  
 Branding:: showpkgs  
 Branding:: spritelist

▼ CSVImport  
 CSVImport:: columnschoices  
 CSVImport:: configimport  
 CSVImport:: data  
 CSVImport:: fetchimportdata  
 CSVImport:: isenabled  
 CSVImport:: loaddata  
 CSVImport:: processdata  
 CSVImport:: sendcontact

RszlES%2BXi%5CnDb1%2BIGPY2JGPjBnje3X4D8QwzEFzFMx24VuwglT21IbYmhYrc5h0oye1mVLGwbV9%5Cn%2Fxo1X9iQEjRMzB67zHTU%2F6WfVPnYFSiSoBSCwcgtO14R4ZLMby5sdXycKME4wCyJ%5Cn3UFkrI6NH4H0FGte%2BMFjZ0SwUy18IO%2Fpxs%2FhScg0ZUk4Lbpia9feB%2FImkxrdW19t%5Cn9b26RWHI%2FK4tT4NUDSB%2BT08UM0Hb%2BQ2%2BMbYLDrANTvb4NxqazlJsa%2BrwYD3X8%2BHj%5CneTxxwSZSrVHJkog4fUfbZavYHiXgkSws1TXP9JfQOwn3D4elTscOS%2B%2BTvATTgo3Qr%5CnXpAmCQ8mfeZJzVDPiWP7XO3EBg3uDqfVe9gPh%2FQlmTwYOBYHmk3dWNbx1cuovXvC%5CnCFwjJHD8FGhBsC%2BEJhscRYW9YfVyuIcb3arZn%2BNk6a8p%2B%2BnLu8yojh5P6iGJviMq%5Cn2Pkk2tgu6Cshy66tFJy0joDo5jsXh5d4WEB1aKojrLI%3D%5Cn-----EN

## About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

### Notes:

- [Thumbnail users or 20 or 20\).](#)
- [Thumbnail users or 20 or 20\).](#)

## Find a function

- CSVImport:: uploadimport
- ▼ Contactus
  - Contactus:: isenabled
  - Contactus:: sendcontact
- ▼ Cron
  - Cron:: add\_line
  - Cron:: edit\_line
  - Cron:: fetchcron
  - Cron:: get\_email
  - Cron:: listcron
  - Cron:: remove\_line
  - Cron:: set\_email
- ▼ CustInfo
  - CustInfo:: contactemails
  - CustInfo:: contactrefs
  - CustInfo:: displaycontactinfo
  - CustInfo:: savecontactinfo
- ▼ DBmap
  - DBmap:: status
  - DBmap:: version
- ▼ DKIMUI
  - DKIMUI:: available
  - DKIMUI:: getrecords
  - DKIMUI:: install
  - DKIMUI:: installed
  - DKIMUI:: uninstall
- ▼ DenyIp
  - DenyIp:: listdenyp
- ▼ DiskCounter
  - DiskCounter:: disk\_counter
- ▼ DiskUsage
  - DiskUsage:: buildcache
  - DiskUsage:: clearcache
  - DiskUsage:: fetch\_raw\_disk\_usage
  - DiskUsage:: fetchdiskusage

```
D%20RSA%20PRIVATE%20KEY-----&name=user&password=12345luggage
```

**Note:**  
For more information, read our [Calls from the WHM API documentation](#).

▼ LiveAPI PHP Class

```
$cpanel = new CPANEL(); // Connect to cPanel - only do this once.

// Import an SSH key
$import_key = $cpanel->api2(
    'SSH',
    'importkey',
    array(
        'key' =>
        '-----BEGIN RSA
PRIVATE
KEY-----\nProc-Type:
4, ENCRYPTED\nDEK-Info:
DES-EDE3-CBC, 8B36FD41
96F9015D\n\rTtykPEmZ
u4jTfPzIZkSsfkZaTTXOt
3Ho+JCqG6HpLaCm/KibiE
BkVUXkC4QLrUL\nB+/ifv
jN+iXYwiYvXLSB5EnVyEu
PIjFnnugSIN1Cp84mU1RS
yO4DfhPTdWLwr5tP\nIYq
zpB0cxL2zqX+GB8BCx/S2
NDQ/nQWMepKZrod3kasza
/H580F5103fJ1U+3WQb\n
lYqqOMKeDcatCDgrlc/S/
qz6xjk+HrivnZL+EQTS0a
v8ZtWEjsjCwvn9N0Gb1TO
W\ni8uv/hPpu6SVZkLUb7
RUsIEXW44+/Sa6PsSjTq5
SLu8C/DV8K6x63R/RszlE
S+Xi\nDb1+IGPY2JGPjBn
je3X4D8QwzEFzFMx24Vuw
glT21IbYmhyc5h0oye1m
VLGwbV9\n/xo1X9iQEjRM
zB67zHTU/6WfVPnYFSiSo
```

- cPanel API 2 Functions - SSH: :fetchkey — This function retrieves an SSH key.
- cPanel API 2 Functions - SSH: :deletekey — This function deletes an SSH key.
- cPanel API 2 Functions - SSH: :authorizekey — This function authorizes an SSH key.

```

DiskUsage:: fetchdiskusagewithextras
  DnsLookup
    DnsLookup:: name2ip
  DomainLookup
    DomainLookup:: countbaseddomains
    DomainLookup:: getbaseddomains
    DomainLookup:: getdocroot
    DomainLookup:: getdocroots
    DomainLookup:: getmaindomain
  Email
    Email:: accountname
    Email:: adddomainforward
    Email:: addforward
    Email:: addmx
    Email:: addpop
    Email:: browseboxes
    Email:: changemx
    Email:: checkmaindiscard
    Email:: clearpopcache
    Email:: deletefilter
    Email:: delforward
    Email:: delmx
    Email:: delpop
    Email:: disablefilter
    Email:: editquota
    Email:: enablefilter
    Email:: fetchautosponder
    Email:: fetchcharmaps
    Email:: filteractions
    Email:: filterlist
    Email:: filtername
    Email:: filterrules
    Email:: get_archiving_configuration

```

```

BSCwCgtO14R4ZLMby5sdX
ycKME4wCyJ\n3UFkrI6NH
4H0FGte+MFjZ0SwUy18IO
/pxs/hScg0ZUk4LbpiA9f
eB/ImkxrdW19t\n9b26RW
HI/K4tT4NUDSB+T08UM0H
b+Q2+MbYLDrANTvb4Nxqa
z1Jsa+rwyD3X8+Hj\neTx
wSZSrVHJkog4fUfbZavYH
iXgkSws1TXP9JfqOwn3D4
eltscOS++TvATTgo3Qr\n
XpAmCQ8mfeZJzVDPiWP7X
O3EBg3uDqfVe9gPh/Q1mT
wYOBYHMk3dWNbx1cuovXv
C\nCFwjJHD8FGhBsC+EJh
scRYW9YfVyuIcb3arZn+N
k6a8p++nLu8y0jh5P6iGJ
viMq\n2Pkk2tgu6Cshy66
tFJy0joDo5jsXh5d4WEB1
aKojrLI=\n-----END
RSA PRIVATE
KEY-----',
      'name' =>
'user',
      'pass' =>

```

- cPanel API 2 Functions - SSH: :listkeys - This function lists SSH keys.

Email: get\_archiving\_default\_configuration

Email: get\_archiving\_types

Email: get\_default\_email\_quota

Email: get\_email\_signing

Email: get\_max\_email\_quota

Email: get\_tabs\_browser\_dir

Email: get\_always\_accept

Email: get\_disk\_usage

Email: get\_mx\_check

Email: has\_delegated\_mailman\_lists

Email: list\_system\_filter\_info

Email: list\_aliases\_backups

Email: list\_autoresponders

Email: list\_default\_addresses

Email: list\_domain\_forwards

Email: list\_filter\_backups

Email: list\_filters

Email: list\_forwards

Email: list\_lists

Email: list\_mail\_domains

Email: list\_mx

Email: list\_mx\_s

Email: list\_pops

Email: list\_pop\_single

Email: list\_pop\_switch\_disk

Email: list\_pop\_switch\_image

Email: load\_filter

Email: password\_pop

```
'12345luggage'  
)  
);
```

**Note:**

For more information, read our [Guide to the LiveAPI System](#).

#### LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Import an SSH key  
my $import_key =  
$cpliveapi->api2(  
    'SSH',  
    'importkey'  
    {  
        'key' =>  
        '-----BEGIN RSA  
PRIVATE  
KEY-----\nProc-Type:  
4, ENCRYPTED\nDEK-Info  
:  
DES-EDE3-CBC, 8B36FD41  
96F9015D\n\nRttykPEmZ  
u4jTfPzIZkSsfkZaTTXOt  
3Ho+JCqG6HpIaCm/KibiE  
BkVUXkC4QLrUL\nB+/ifv  
jN+iXYwiYvXLSB5EnVyEu  
PIjFnnugSIN1Cp84mU1RS  
yO4DfhPTdWLwr5tP\n\nIYq  
zpB0cxL2zqX+GB8BCx/S2  
NDQ/nQWMepKZrod3kasza  
/H580F5103fJ1U+3WQb\n\nlYqgOMKeDcatCDgrlc/S/  
qz6xjk+HrivnZL+EQTS0a  
v8ZtWEjsjCwvn9N0Gb1TO  
W\n\ni8uv/hPpu6SVzkLUB7  
RUsIEXW44+/Sa6PsSjTq5  
SLu8C/DV8K6x63R/RszlE  
S+Xi\n\nDb1+IGPY2JGPjBn  
je3X4D8QwzEFzFMx24Vuw  
g1T21IbYmhYrc5h0oye1m  
VLGwbV9\n\n/xo1X9iQEjRM
```

Email:: reorderfilter  
s

Email:: set\_archiving\_configuration

Email:: set\_archiving\_default\_configuration

Email:: set\_email\_signing

Email:: setalwaysaccept

Email:: setdefaultaddress

Email:: setmxcheck

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: search

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get\_encodings

Encoding:: guess\_file

Encoding:: guess\_file\_opts

▼ FSTest

FSTest:: dirisempty

▼ Fileman

Fileman:: autocompletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiractions

Fileman:: getdiskinfo

Fileman:: geteditty

Fileman:: geteditty

Fileman:: getfileactions

Fileman:: getpath

Fileman:: listfiles

Fileman:: mkdir

Fileman:: mkfile

```
zB67zHTU/6WfVPnYFSiSo
BSCwCgtO14R4ZLMby5sdX
ycKME4wCyJ\n3UFkrI6NH
4H0FGte+MFjZ0SwUy18IO
/pxs/hScg0ZUk4LbpiA9F
eB/ImkxrdW19t\n9b26RW
HI/K4tT4NUDSB+T08UM0H
b+Q2+MbYLDvANTvb4Nxqa
z1Jsa+rwYD3X8+Hj\neTx
wSZSrVHJkog4fUfbZavYH
iXgkSws1TXP9JfQOwn3D4
eltscOS++TvATTgo3Qr\n
XpAmCQ8mfeZJzVDPiWp7X
O3EBg3uDqfVe9gPh/Q1mT
wYOBYHMk3dWNbx1cuovXv
C\nCFwjJHD8FGhBsC+EJh
scRYW9YfVyuIcb3arZn+N
k6a8p++nLu8y0jh5P6iGJ
viMq\n2Pkk2tgu6Cshy66
tFJy0joDo5jsXh5d4WEB1
aKojrLI=\n-----END
RSA PRIVATE
KEY-----',
        'name' =>
'user',
        'pass' =>
```

Fileman:: savefile  
Fileman:: search  
Fileman:: statfiles  
Fileman:: uploadfiles  
Fileman:: viewfile

ForcePassword  
ForcePassword:: get\_force\_password\_flags

ForcePassword:: update\_force\_password\_flags

Frontpage  
Frontpage:: fpenabled

Frontpage:: list

Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: listftp

Ftp:: listftpsessions

Ftp:: listftpwithdisk

Ftp:: passwd

Ftp:: setquota

Gpg

Gpg:: listgpgkeys

Gpg:: listsecretgpgkeys

Gpg:: number\_of\_private\_keys

Gpg:: number\_of\_public\_keys

Htaccess

Htaccess:: listuser

Htaccess:: listusers

HttpUtils

HttpUtils:: getdirindices

ImageManager

ImageManager:: thumbnail

LVEInfo

LVEInfo:: getUsage

LangMods

LangMods:: getarchname

```
'12345luggage '  
    }  
);
```

**Note:**

For more information, read our [Guide to the LiveAPI System](#).

### ▼ cPanel Tag System (deprecated)

**Warnings:**

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Deprecated cPanel Tag Usage](#) documentation.

### ▼ Command Line

```
cpapi2  
--user=username SSH  
importkey  
key-----BEGIN RSA  
PRIVATE  
KEY-----\nProc-Type:  
4, ENCRYPTED\nDEK-Info:  
DES-EDE3-CBC, 8B36FD41  
96F9015D\n\nRttykPE  
mZu4jTfPzIZkSsfkZaTTX  
Ot3Ho+JCqG6HplaCm/Kib  
iEBkVUXkC4QLrUL\n\nB+/  
ifvjN+iXYwiYvXLSB5EnV  
yEuPIjFnnugSIN1Cp84mU  
lRSyO4DfhPTdWLwr5tP\n\nIYqzpb0cxL2zqX+GB8BCx  
/S2NDQ/nQWmepKZrod3ka  
sza/H580F5103fJ1U+3WQ  
b\n\nlYqgOMKeDcatCDgrlc  
/S/qz6xjk+HrivnZL+EQT  
S0av8ZtWEjsjCwvn9NOGb  
1TOW\n\ni8uv/hPpu6SVZkL
```

LangMods:: getkey  
LangMods:: getpre  
fix  
LangMods:: install  
LangMods:: langlis  
t  
LangMods:: list\_av  
ailable  
LangMods:: list\_in  
stalled  
LangMods:: magic  
\_status  
LangMods:: pre\_ru  
n  
LangMods:: search  
LangMods:: setup  
LangMods:: uninst  
all  
LangMods:: updat  
e  
▼ LeechProtect  
LeechProtect:: set  
up  
▼ Locale  
Locale:: get\_encod  
ing  
Locale:: get\_html\_  
dir\_attr  
Locale:: get\_locale  
\_name  
Locale:: get\_user\_  
ocale  
Locale:: get\_user\_  
ocale\_name  
Locale:: numf  
▼ Logaholic  
Logaholic:: adduse  
r  
Logaholic:: adduse  
rprofile  
Logaholic:: deleteu  
ser  
Logaholic:: deleteu  
serprofile  
Logaholic:: edituse  
r  
Logaholic:: fetchus  
er  
Logaholic:: listuser  
profiles  
Logaholic:: logahol

Ub7RUslEXW44+/Sa6PsSj  
Tq5SLu8C/DV8K6x63R/Rs  
zLES+Xi\nDb1+IGPY2JGP  
jBnje3X4D8QwzEFzFMx24  
Vuwg1T21IbYmhyc5h0oy  
e1mVLGwbV9\n/xo1X9iQE  
jRMzB67zHTU/6WfVPnYFS  
iSoBSCwCgtO14R4ZLMby5  
sdXycKME4wCyJ\n3UFkrI  
6NH4H0FGte+MFjz0SwUy1  
8IO/pxs/hScg0ZUk4Lbpi  
A9feB/ImkxrdW19t\n9b2  
6RWHI/K4tT4NUDSB+T08U  
M0Hb+Q2+MbYLDrANTvb4N  
xqaz1Jsa+rwYD3X8+Hj\n  
eTxwSZSrVHJkog4fUfbZa  
vYHiXgkSws1TXP9JfQOwn  
3D4e1tscOS++TvATTgo3Q  
r\nXpAmCQ8mfeZJzVDPiw  
P7XO3EBg3uDqfVe9gPh/Q  
lmTwYOBVHMk3dWNbx1cuo  
vXvC\nCFwjJHD8FGhBsC+  
EJhscRYW9YfVyuIcb3arZ  
n+Nk6a8p++nLu8yojh5P6  
iGJviMq\n2Pkk2tgu6Csh  
y66tFJy0joDo5jsXh5d4W  
EB1aKojrLI=\n-----END



iclink

Logaholic:: proces  
sstats

▼ Mime

Mime:: list\_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectna  
me

Mime:: redirecturln  
ame

▼ MysqlFE

MysqlFE:: authoriz  
ehost

MysqlFE:: change  
dbuserpassword

MysqlFE:: created  
b

MysqlFE:: created  
buser

MysqlFE:: dbusere  
xists

MysqlFE:: deautho  
rizehost

MysqlFE:: deleted  
b

MysqlFE:: deleted  
buser

MysqlFE:: getalldb  
sinfo

MysqlFE:: getalldb  
usersanddbs

MysqlFE:: getdbus  
erprivileges

MysqlFE:: getdbus  
ers

MysqlFE:: gethosts

MysqlFE:: getmys  
qlprivileges

MysqlFE:: getmys  
qlserverprivileges

MysqlFE:: has\_my  
cnf\_for\_cpuser

MysqlFE:: listdbs

MysqlFE:: listdbsb  
ackup

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers

```
RSA PRIVATE KEY-----  
name=user  
pass=12345luggage
```

**Notes:**

- You **must** URI-encode values.
- username represents your account-level username.
- You **must** run the `--user=username` command.
- For more information and additional output options, read our [Guide to cPanel API 2](#) documentation or run the `cpapi2 --help` command.
- If you run CloudLinux™, you **must** use the full path of the `cpapi2` command:

```
/usr/local  
/cpanel/bin/  
cpapi2
```

▼ Output (JSON)

```
{  
  "cpanelresult": {  
    "apiversion": 2,  
    "func":  
    "importkey",  
    "data": [  
      {  
        "name":  
        "bob",  
      }  
    ],  
    "event": {  
      "result": 1  
    },  
    "module": "SSH"  
  }  
}
```

**Note:**

Use cPanel's *API Shell* interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

indb

MysqlFE:: revoked  
buserprivileges

MysqlFE:: setdbu  
erprivileges

MysqlFE:: userdbp  
rivs

▼ MySQLOptimizer

MysqlOptimizer:: f  
etch\_slow\_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does\_news  
\_exist

News:: does\_news  
\_type\_exist

News:: get\_news

▼ PHPINI

PHPINI:: getallopti  
ons

PHPINI:: getoptio  
ns

▼ Park

Park:: listaddondo  
mains

Park:: listparkeddo  
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change\_  
password

Passwd:: set\_dige  
st\_auth

▼ PasswdStrength

PasswdStrength::  
appstrengths

PasswdStrength::  
get\_password\_stre  
ngth

PasswdStrength::  
get\_required\_stren  
gth

▼ Postgres

Postgres:: listdbs

## Parameters

Parameter	Type	Description	Possible values	Example
key	string	<b>Required</b>  The contents of the key file.	A valid SSH key file.	▼ <a href="#">Click to view...</a> <pre> -----BEGIN RSA PRIVATE KEY-----\n Proc-Type: 4, ENCRYPTED D\nDEK-Info: DES-EDE3-C BC, 8B36FD4 196F9015D\ n\nRttykPE mZu4jTfPzI ZkSsfkZaTT XOt3Ho+JCq G6HplaCm/K ibiEBkVUXk C4QLrUL\nB +/ifvjN+iX YwiYvXLSB5 EnVyEuPIjF nnugSIN1Cp 84mULRSyO4 DfhPTdWLwr 5tP\nIYqzp B0cxL2zqX+ GB8BCx/S2N DQ/nQWMePK Zrod3kasza /H580F5103 fJlU+3WQb\ nlyggOMKeD catCDgrlc/ S/qz6xjk+H rivnZL+EQT S0av8ZtWEj sjCwvn9N0G blTOW\ni8u v/hPpu6SVZ kLUB7RUsIE XW44+/Sa6P sSjTq5SLu8 C/DV8K6x63 R/RszLES+X i\nDb1+IGP Y2JGPjBnje 3X4D8QzEF zFMx24Vuwg lT21IbYmhy rc5h0oyelM VLGwbV9\n/ xo1X9iQEjR MzB67zHTU/ 6WFVpnyFSi SoBSCwctO 14R4ZLMby5 sdXycKME4w CyJ\n3UFkr I6NH4H0FGt e+MFjZ0SwU y18IO/pxs/ hScg0Zuk4L bpiA9feB/I mkxrdW19t\ </pre>

Postgres:: listusers  
Postgres:: listusers  
indb  
Postgres:: userexi  
sts  
▼ Rand  
Rand:: getranddat  
a  
▼ Resellers  
Resellers:: get\_su  
b\_accounts  
▼ RoR  
RoR:: addapp  
RoR:: changeapp  
RoR:: importrails  
RoR:: listapps  
RoR:: listrewrites  
RoR:: needsimport  
RoR:: removeapp  
RoR:: removerewri  
te  
RoR:: restartapp  
RoR:: setuprewrite  
RoR:: softrestartap  
p  
RoR:: startapp  
RoR:: stopapp  
▼ SetLang  
SetLang:: setlocale  
▼ SourceIPCheck  
SourceIPCheck:: a  
ddip  
SourceIPCheck:: d  
elip  
SourceIPCheck:: g  
etaccount  
SourceIPCheck:: li  
stips  
SourceIPCheck:: l  
oadsecquestions  
SourceIPCheck:: r  
esetsecquestions  
SourceIPCheck:: s  
amplequestions  
SourceIPCheck:: s  
avesecquestions  
▼ SPFUI  
SPFUI:: available

n9b26RWHI/  
K4tT4NUDSB  
+T08UM0Hb+  
Q2+MbYLDra  
NTvb4Nxqaz  
lJsa+rwyD3  
X8+Hj\neTx  
wSZSrVHJko  
g4fUfbZavY  
HiXgkSws1T  
XP9JfqOwn3  
D4e1tscOS+  
+TvATTgo3Q  
r\nXpAmCQ8  
mfeZJzVDPI  
wP7XO3EBg3  
uDqfVe9gPh  
/Q1mTwYOBY  
HMk3dWNbx1  
cuovXvC\nC  
FwjJHD8FGh  
BsC+EJhscR  
YW9YfVyuIc  
b3arZn+Nk6  
a8p++nLu8y  
ojh5P6iGJv  
iMq\n2Pkk2  
tgu6Cshy66  
tFJy0 joDo5  
jsXh5d4WEB  
laKojrLI=\n  
n-----END

SPFUI:: count\_settings

SPFUI:: entries\_complete

SPFUI:: get\_raw\_record

SPFUI:: getmainserverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list\_settings

SPFUI:: load\_current\_values

SPFUI:: uninstall

▼ SSH

SSH:: authkey

SSH:: converttopk

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey\_legacy

SSH:: importkey

SSH:: listkeys

▼ SSL

SSL:: fetchcertificate

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcname

SSL:: installssl

SSL:: listcrt

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

▼ SSLInfo

SSLInfo:: fetchinfo

▼ StatCache

StatCache:: clearcache

				RSA PRIVATE KEY-----
name	string	The SSH key's filename.  If you do not use either the <code>name</code> or <code>pass</code> parameters, the function returns <b>all</b> of the account's keys.	A valid string.  <b>Note:</b> You cannot use the following values: <ul style="list-style-type: none"><li>• <code>configng</code></li><li>• <code>known_hosts</code></li><li>• <code>authorized_hosts</code></li><li>• <code>environment</code></li><li>• <code>rc</code></li><li>• <code>identities</code></li></ul>	user

- Stats:: getmonthly bandwidth
  - Stats:: getmonthly domainbandwidth
  - Stats:: getthismonth hsbwusage
  - Stats:: lastapache hits
  - Stats:: lastvisitors
  - Stats:: listanalog
  - Stats:: listawstats
  - Stats:: listlastvisitors
  - Stats:: listrawlogs
  - Stats:: listurchin
  - Stats:: listwealizer
- StatsBar:: rowcounter
  - StatsBar:: setrowcounter
  - StatsBar:: stat
- SubDomain:: adds ubdomain
  - SubDomain:: changedocroot
  - SubDomain:: delsubdomain
  - SubDomain:: getresubdomains
  - SubDomain:: listsubdomains
  - SubDomain:: validategex
- Themes:: apply\_new\_theme
  - Themes:: does\_panel\_theme\_exist
  - Themes:: get\_available\_themes
  - Themes:: get\_themes\_list
  - Themes:: restore\_saved\_theme

			<p><b>Remember:</b> This function will overwrite any existing keys that use the same name as the imported key.</p>	
pass	string	<p>The SSH key's password.</p> <p>If you do not use either the name or pass parameters, the function returns all of the account's keys.</p>	A secure password.	12345luggage

## Returns

Return	Type	Description	Possible values	Example
name	string	The SSH key's name.	A valid filename.	user
reason	string	<p>A reason for failure.</p> <div style="border: 1px solid #ffcdd2; padding: 5px; margin-top: 10px;"> <p><b>Note</b> : This function only returns a reason value if it failed.</p> </div>	A string that describes the error.	This is an error message.
result	Boolean	Whether the function succeeded.	<ul style="list-style-type: none"> <li>• 1 — The function succeeded.</li> <li>• 0 — The function failed.</li> </ul>	1

▼ UI

- UI:: dynamicincludelist
- UI:: includelist
- UI:: listform
- UI:: paginate
- UI:: paginate\_list

▼ UserHttpUtils

- UserHttpUtils:: getdirindices

▼ WebDisk

- WebDisk:: addwebdisk
- WebDisk:: delwebdisk
- WebDisk:: hasdigest
- WebDisk:: listwebdisks
- WebDisk:: passwdwebdisk
- WebDisk:: set\_digest\_auth
- WebDisk:: set\_home\_dir
- WebDisk:: set\_perms
- WebDisk:: setstatus

▼ WebmailApps

- WebmailApps:: listwebmailapps

▼ ZoneEdit

- ZoneEdit:: add\_zone\_record
- ZoneEdit:: edit\_zone\_record
- ZoneEdit:: fetch\_cpanel\_generated\_domains
- ZoneEdit:: fetchzone
- ZoneEdit:: fetchzone\_records
- ZoneEdit:: fetchzones
- ZoneEdit:: get\_zone\_record
- ZoneEdit:: remove\_zone\_record
- ZoneEdit:: resetzone

