

UAPI Functions - Mysql::create_user

Guide to UAPI

- Return Data
- Filter Output
- Sort Output
- Paginate Output
- Output Columns
- Calls from the WHM API
- Custom UAPI Modules

Backup
Backup::
fullbacku

p_to_ftp

Backup:: fullbacku
p_to_homedir

Backup:: fullbacku
p_to_scp_with_key

Backup:: fullbacku
p_to_scp_with_password

Backup:: list_backups

Bandwidth

Bandwidth:: get_enabled_protocols

Bandwidth:: get_retention_periods

Bandwidth:: query

Batch

Batch:: strict

Brand

Brand:: read

Branding

Branding:: file

Branding:: get_applications

Branding:: get_application_information

Branding:: get_available_applications

Branding:: get_information_for_applications

Description

This function creates a MySQL® database user.

Important:

In cPanel & WHM version 76 and later, when you disable the MySQL role, the system **disables** this function. For more information, read our [How to Use Server Profiles](#) documentation.

Examples

▼ cPanel or Webmail Session URL

```
https://hostname.example.com:2083/cpsess##  
▼ #####/execute/Mysql/create_user?name=db  
user&password=12345lu  
ggage
```

Note:

This example calls the UAPI function via a cPanel session. For more information, read our [Guide to UAPI](#) documentation.

Function information

About this module

The MySQL module manages MySQL users, databases, and services.

About UAPI

DAV:: is_horde_enabled

▼ DCV

DCV:: check_domains_via_dns

DCV:: check_domains_via_http

DCV:: ensure_domains_can_pass_dcv

▼ DomainInfo

DomainInfo:: domains_data

DomainInfo:: list_domains

DomainInfo:: main_domain_builtin_subdomain_aliases

DomainInfo:: single_domain_data

▼ DNS

DNS:: ensure_domains_reside_only_locally

DNS:: has_local_authority

▼ DNSSEC

DNSSEC:: disable_dnssec

DNSSEC:: enable_dnssec

DNSSEC:: fetch_dns_records

DNSSEC:: set_nsec3

DNSSEC:: unset_nsec3

▼ Email

Email:: account_name

Email:: add_auto_responder

Email:: add_domain_forwarder

Email:: add_forwarder

Email:: add_list

Email:: add_mailman_delegates

Email:: add_mx

Email:: add_pop

Email:: add_spam_filter

▼ LiveAPI Perl Module

```
my $cpliveapi =  
Cpanel::LiveAPI->new(  
); # Connect to  
cPanel - only do this  
once.
```

```
# Create a new  
database user.  
my $create_db_user =  
$cpliveapi->uapi(  
  'Mysql',  
  'create_user',  
  {  
    'name'  
=> 'dbuser',  
    'password'  
=> '12345luggage',  
  }  
);
```

Note:

For more information, read our [Guide to the LiveAPI System](#).

▼ cPanel Template Toolkit

```
<!-- Create a new  
user. -->  
[% execute( 'Mysql',  
  'create_user', { name  
=> 'dbuser', password  
=> '12345luggage' } )  
%]
```

Note:

For more information, read our [Guide to Template Toolkit documentation](#).

- UAPI Modules - PostgreSQL - The PostgreSQL module manages PostgreSQL databases and users.
- UAPI Functions - PostgreSQL::create_database - This function creates a PostgreSQL database.
- UAPI Functions - PostgreSQL::create_user - This function creates a PostgreSQL database user.

Email: browse_mailbox

Email: change_mx

Email: check_fastmail

Email: check_pipe_forwarder

Email: delete_auto_responder

Email: delete_domain_forwarder

Email: delete_filter

Email: delete_forwarder

Email: delete_help_messages

Email: delete_list

Email: delete_mx

Email: delete_pop

Email: disable_filter

Email: disable_mailbox_autocreate

Email: disable_spam_assassin

Email: disable_spam_autodelete

Email: disable_spam_box

Email: dispatch_client_settings

Email: edit_pop_quota

Email: enable_filter

Email: enable_mailbox_autocreate

Email: enable_spam_assassin

Email: enable_spam_box

Email: fetch_charmaps

Email: fts_rescan_mailbox

Email: generate_mailman_otp

Email: get_auto_responder

Email: get_chase

Command Line

```
uapi --user=username
Mysql create_user
name=dbuser
password=12345luggage
```

Notes:

- You **must** URI-encode values.
- username represents your account-level username.
- For more information and additional output options, read our [Guide to UAPI](#) documentation or run the `uapi --help` command.
- If you run CloudLinux™, you **must** use the full path of the `uapi` command:

```
/usr/local
/cpanel/bin/uapi
```

Output (JSON)

```
{
  "messages": null,
  "errors": null,
  "status": 1,
  "metadata": {
  },
  "data": null
}
```

Note:
Use cPanel's *API Shell* interface (`cPanel >> Home >> Advanced >> API Shell`) to directly test cPanel API calls.

- UAPI Functions - PostgreSQL: delete database — This function deletes a PostgreSQL database.

Parameters

Parameter	Type	Description	Possible values	Example
name	string	Required		dbuser

ts

Email: get_client_settings

Email: get_default_email_quota

Email: get_default_email_quota_mib

Email: get_disk_usage

Email: get_filter

Email: get_held_message_count

Email: get_mailbox_autocreate

Email: get_mailman_delegates

Email: get_main_account_disk_usage

Email: get_main_account_disk_usage_bytes

Email: get_max_email_quota

Email: get_max_email_quota_mib

Email: get_pop_quota

Email: get_spam_settings

Email: get_webmail_settings

Email: has_delegated_mailman_lists

Email: has_plaintext_authentication

Email: hold_outgoing

Email: is_integer

Email: list_autoresponders

Email: list_default_address

Email: list_domain_forwarders

Email: list_filters

Email: list_filters_backups

Email: list_forwarders

Email: list_forward

The new user's name.

A valid database username.

Important:

To learn more about database usernames and limits, click your database username type:

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

MySQL

ers_backups
Email:: list_lists
Email:: list_mail_domains
Email:: list_mx
Email:: list_pops
Email:: list_pops_with_disk
Email:: list_system_filter_info
Email:: passwd_list
Email:: passwd_pop
Email:: release_outgoing
Email:: remove_mailman_delegates
Email:: reorder_filters
Email:: set_always_accept
Email:: set_default_address
Email:: set_list_privacy_options
Email:: stats_db_status
Email:: store_filter
Email:: suspend_incoming
Email:: suspend_login
Email:: suspend_outgoing
Email:: trace_filter
Email:: unsuspend_incoming
Email:: unsuspend_login
Email:: unsuspend_outgoing
Email:: verify_password
▼ EmailAuth
EmailAuth:: disable_dkim
EmailAuth:: enable_dkim
EmailAuth:: ensure_dkim_keys_exist

b
a
s
e
p
r
e
f
i
x
(
t
h
e
f
i
r
s
t
e
i
g
h
t
c
h
a
r
a
c
t
e
r
s
o
f
t
h
e
c
P
a
n
e
l
a
c
c
o
u
n
t
,
s
u
s
e
r
n
a
m
e
a
n
d
a
n
u
n
d
e
r
s
c
o
r
e
c
h
a
r
a
c
t
e
r
)
i
n
t

EmailAuth:: fetch_
dkim_private_keys

EmailAuth:: install
_dkim_private_key
s

EmailAuth:: install
_spf_records

EmailAuth:: validat
e_current_dkims

EmailAuth:: validat
e_current_ptrs

EmailAuth:: validat
e_current_spfs

ExternalAuthenticat
ion

ExternalAuthenticat
ion:: add_auth_li
nk

ExternalAuthenticat
ion:: configured_
modules

ExternalAuthenticat
ion:: get_authn_lin
ks

ExternalAuthenticat
ion:: has_external
_auth_modules_co
nfigured

ExternalAuthenticat
ion:: remove_auth
n_link

Features

Features:: get_feat
ure_metadata

Features:: has_fea
ture

Features:: list_feat
ures

Fileman

Fileman:: autocom
pletedir

Fileman:: empty_tr
ash

Fileman:: get_file_
content

Fileman:: get_file_i
nformation

Fileman:: list_files

Fileman:: save_file
_content

Fileman:: transcod
e

Fileman:: upload_fi
les

h
e
c
h
a
r
a
c
t
e
r
c
o
u
n
t
f
o
r
t
h
e
u
s
e
r
n
a

- Ftp:: add_ftp
 - Ftp:: allows_anonymous_ftp
 - Ftp:: allows_anonymous_ftp_incoming
 - Ftp:: delete_ftp
 - Ftp:: ftp_exists
 - Ftp:: get_ftp_daemon_info
 - Ftp:: get_port
 - Ftp:: get_quota
 - Ftp:: get_welcome_message
 - Ftp:: kill_session
 - Ftp:: list_ftp
 - Ftp:: list_ftp_with_disk
 - Ftp:: list_sessions
 - Ftp:: passwd
 - Ftp:: server_name
 - Ftp:: set_anonymous_ftp
 - Ftp:: set_anonymous_ftp_incoming
 - Ftp:: set_homedir
 - Ftp:: set_quota
 - Ftp:: set_welcome_message
- Integration
 - Integration:: fetch_url
- KnownHosts
 - KnownHosts:: create
 - KnownHosts:: delete
 - KnownHosts:: update
 - KnownHosts:: verify
- LangPHP
 - LangPHP:: php_get_domain_handler
 - LangPHP:: php_get_impacted_domains
 - LangPHP:: php_get_installed_version

me . For example :

- A MySQL database with the db_ prefix allows usernames that contain up to 13 characters.
- A MySQL database with the example_ prefix allows usernames that contain up to eight characters.

▼ MariaDB

MariaDB limit the size of the database user name to 47 characters.

The system file includes

s

LangPHP:: php_get_system_default_version

LangPHP:: php_get_vhost_versions

LangPHP:: php_ini_get_user_basic_directives

LangPHP:: php_ini_get_user_content

LangPHP:: php_ini_get_user_paths

LangPHP:: php_ini_set_user_basic_directives

LangPHP:: php_ini_set_user_content

LangPHP:: php_set_vhost_versions

▼ LastLogin

LastLogin:: get_last_or_current_logged_in_ip

▼ Locale

Locale:: get_attributes

▼ Mailboxes

Mailboxes:: expunge_mailbox_messages

Mailboxes:: expunge_messages_for_mailbox_guid

Mailboxes:: get_mailbox_status

Mailboxes:: has_utf8_mailbox_names

Mailboxes:: set_utf8_mailbox_names

▼ Market

Market:: cancel_pending_ssl_certificate

Market:: create_shopping_cart

Market:: get_all_products

Market:: get_certificate_status_details

Market:: get_login_url

Market:: get_pending_ssl_certificates

e
s
t
h
e
d
a
t
a
b
a
s
e
p
r
e
f
i
x
(
a
l
l
o
f
t
h
e
c
P
a
n
e
l
a
c
c
o
u
n
t
,
s
u
s
e
r
n
a
m
e
a
n
d
a
n
u
n
d
e
r
s
c
o
r
e
c
h
a
r
a
c
t
e
r
)
i
n
t
h
e
c
h
a
r
a
c
t
e
r
c

Market:: get_provi
der_specific_dcv_
constraints

Market:: get_provi
ders_list

Market:: get_ssl_c
ertificate_if_availa
ble

Market:: process_s
sl_pending_queue

Market:: request_s
sl_certificates

Market:: set_status
_of_pending_queu
e_items

Market:: set_url_af
ter_checkout

Market:: validate_l
ogin_token

▼ Mime

Mime:: add_handl
er

Mime:: add_hotlink

Mime:: add_mime

Mime:: add_redire
ct

Mime:: delete_han
dler

Mime:: delete_hotli
nk

Mime:: delete_mim
e

Mime:: delete_redi
rect

Mime:: list_handler
s

Mime:: list_hotlinks

Mime:: list_mime

Mime:: list_redirect
s

Mime:: redirect_inf
o

▼ ModSecurity

ModSecurity:: disa
ble_all_domains

ModSecurity:: disa
ble_domains

ModSecurity:: ena
ble_all_domains

ModSecurity:: ena
ble_domains

- ModSecurity:: has_modsecurity_installed
- ModSecurity:: list_domains
- ▼ Mysql
 - Mysql:: add_host
 - Mysql:: add_host_note
 - Mysql:: check_database
 - Mysql:: create_database
 - Mysql:: create_user
 - Mysql:: delete_database
 - Mysql:: delete_host
 - Mysql:: delete_user
 - Mysql:: get_host_notes
 - Mysql:: get_privileges_on_database
 - Mysql:: get_restrictions
 - Mysql:: get_server_information
 - Mysql:: locate_server
 - Mysql:: rename_database
 - Mysql:: rename_user
 - Mysql:: repair_database
 - Mysql:: revoke_access_to_database
 - Mysql:: set_password
 - Mysql:: set_privileges_on_database
- ▼ Notifications
 - Notifications:: get_notifications_count
- ▼ NVData
 - NVData:: get
 - NVData:: set
- ▼ Parser
 - Parser:: firstfile_relative_uri

			e . F o r e x a m p l e :	
password	string	Required The new user's password.	A secure password that meets the server's minimum MySQL password strength requirements.	<ul style="list-style-type: none"> • A MariaDB database with the db_ prefix allows usernames that contain up to 44 characters. • A MariaDB database with the example_ prefix allows usernames that contain up to 39 characters.
				12345luggage

Returns

This function only returns metadata.

- ▼ PassengerApps
 - PassengerApps:: disable_application
 - PassengerApps:: edit_application
 - PassengerApps:: enable_application
 - PassengerApps:: ensure_deps
 - PassengerApps:: list_applications
 - PassengerApps:: register_application
 - PassengerApps:: unregister_application
- ▼ PasswdStrength
 - PasswdStrength:: get_required_strength
- ▼ Personalization
 - Personalization::set
 - Personalization::get
- ▼ Postgresql
 - Postgresql:: create_database
 - Postgresql:: create_user
 - Postgresql:: delete_database
 - Postgresql:: get_restrictions
 - Postgresql:: grant_all_privileges
 - Postgresql:: rename_database
 - Postgresql:: rename_user
 - Postgresql:: rename_user_no_password
 - Postgresql:: revoke_all_privileges
 - Postgresql:: set_password
- ▼ Pushbullet
 - Pushbullet:: send_test_message
- ▼ Quota
 - Quota:: get_quota_info

- ▼ Resellers
 - Resellers:: list_accounts
- ▼ ResourceUsage
 - ResourceUsage:: get_usages
- ▼ Restore
 - Restore:: directory_listing
 - Restore:: get_users
 - Restore:: query_file_info
 - Restore:: restore_file
- ▼ Session
 - Session:: create_temp_user
- ▼ SiteTemplates
 - SiteTemplates:: list_site_templates
 - SiteTemplates:: list_user_settings
 - SiteTemplates:: publish
- ▼ SpamAssassin
 - SpamAssassin :: clear_spam_box
 - SpamAssassin:: get_symbolic_test_names
 - SpamAssassin:: get_user_preferences
 - SpamAssassin:: update_user_preference
- ▼ SSH
 - SSH:: get_port
- ▼ SSL
 - SSL:: add_autossl_excluded_domains
 - SSL:: can_ssl_redirect
 - SSL:: check_shared_cert
 - SSL:: delete_cert
 - SSL:: delete_csr
 - SSL:: delete_key
 - SSL:: delete_ssl
 - SSL :: disable_mail_sni

SSL:: enable_mail
_sni

SSL:: fetch_best_f
or_domain

SSL:: fetch_cert_in
fo

SSL:: fetch_certific
ates_for_fqdns

SSL:: fetch_key_a
nd_cabundle_for_
certificate

SSL:: find_certifica
tes_for_key

SSL:: find_csrs_for
_key

SSL:: generate_ce
rt

SSL:: generate_cs
r

SSL:: generate_ke
y

SSL:: get_autossl_
excluded_domains

SSL:: get_autossl_
pending_queue

SSL:: get_autossl_
problems

SSL:: get_cabundl
e

SSL:: get_cn_nam
e

SSL:: install_ssl

SSL:: installed_ho
st

SSL:: installed_ho
sts

SSL:: is_autossl_c
heck_in_progress

SSL:: is_mail_sni_
supported

SSL:: is_sni_supp
orted

SSL:: list_certs

SSL:: list_csrs

SSL:: list_keys

SSL:: list_ssl_item
s

SSL:: mail_sni_sta
tus

SSL:: rebuild_mail
_sni_config

SSL:: rebuildssldb

SSL:: remove_aut
ossl_excluded_do
mains

SSL:: set_autossl_
excluded_domains

SSL:: set_cert_frie
ndly_name

SSL:: set_csr_frien
dly_name

SSL:: set_key_frie
ndly_name

SSL:: set_primary
_ssl

SSL:: set_ssl_shar
e

SSL:: show_cert

SSL:: show_csr

SSL:: show_key

SSL:: start_autossl_
_check

SSL:: toggle_ssl_r
edirects_for_doma
ins

SSL:: upload_cert

SSL:: upload_key

▼ StatsBar

StatsBar:: get_stat
s

▼ Styles

Styles:: current

Styles:: list

Styles:: set_default

Styles:: update

▼ SubDomain

SubDomain:: adds
ubdomain

▼ Themes

Themes:: get_the
me_base

Themes:: list

Themes:: update

▼ Tokens

Tokens:: create_fu
ll_access

Tokens:: list

Tokens:: rename

Tokens:: revoke

▼ TwoFactorAuth

TwoFactorAuth:: generate_user_configuration

TwoFactorAuth:: get_user_configuration

TwoFactorAuth:: remove_user_configuration

TwoFactorAuth:: set_user_configuration

▼ UserManager

UserManager:: check_account_conflicts

UserManager:: create_user

UserManager:: delete_user

UserManager:: dismiss_user

UserManager:: edit_user

UserManager:: list_users

UserManager:: lookup_service_account

UserManager:: lookup_user

UserManager:: merge_service_account

UserManager:: unlink_service_account

▼ UserTasks

UserTasks:: delete

UserTasks:: retrieve

▼ VersionControl

VersionControl:: create

VersionControl:: delete

VersionControl:: retrieve

VersionControl:: update

▼ VersionControlDeployment

VersionControlDeployment:: create

VersionControlDeployment:: delete

VersionControlDeployment:: retrieve

▼ WebDisk

WebDisk:: delete_user

WebDisk:: set_homedir

WebDisk:: set_password

WebDisk:: set_permissions

▼ WebmailApps

WebmailApps:: list_webmailapps

▼ WebVhosts

WebVhost:: list_domains

WebVhost:: list_ssl_capable_domains

▼ WordPressBackup

WordPressBackup:: any_running

WordPressBackup:: cancel

WordPressBackup:: cleanup

WordPressBackup:: get_available_backups

WordPressBackup:: is_running

WordPressBackup:: start

▼ WordPressInstance

Manager

WordPressInstanceManager:: cancel_scan

WordPressInstanceManager:: cleanup_scan

WordPressInstanceManager:: change_admin_password

WordPressInstanceManager:: configure_autoupdate

WordPressInstanceManager:: get_api_version

WordPressInstanceManager:: get_in

stance_by_id

WordPressInstanceManager::get_instances

WordPressInstanceManager::get_latest_wordpress_version_from_wordpress_org

WordPressInstanceManager::get_scan_results

WordPressInstanceManager::is_installable_addon_available

WordPressInstanceManager::start_scan

▼ WordPressRestore

WordPressRestore::any_running

WordPressRestore::cleanup

WordPressRestore::start