

# cPanel API 2 Functions - Logaholic::deleteuser

Guide to cPanel API 2

Return Data

Filter and Sort Output

Paginate Output

Output Columns

Calls from the WHM API

cPanel Tags (deprecated)

## Description

This function removes a user from the Logaholic statistics program.

### Warning:

We **strongly** recommend that you use [UAPI](#) instead of cPanel API 2. However, no equivalent UAPI function exists.

### Important:

As of cPanel & WHM version 11.48, Logaholic is no longer available. We removed Logaholic's API functions, and they will **not** produce any results.

## Examples

AddonDomain

### WHM API (JSON)

```
https://hostname.example.com:2087/cpsess#####/json-api/cpanel?cpanel_jsonapi_user=user&cpanel_jsonapi_api_version=2&cpanel_jsonapi_module=Logaholic&cpanel_jsonapi_function=deleteuser&username=example
```

### Note:

For more information, read our [Calls from the WHM API documentation](#).

## Function information

## About this module

The Logaholic module manages the Logaholic statistics program.

AddonDomain:: adddondomain

domain

AddonDomain:: listdondomains

AddonDomain:: listdondomains

### Backups

Backups:: listfullbackups

### Bandwidth

Bandwidth:: addhttpbandwidth

Bandwidth:: getbandwidthdata

Bandwidth:: gethourlyaveragebandwidthoveryear

### BoxTrapper

BoxTrapper:: accountmanagelist

### Branding

Branding:: addbrandingobj

Branding:: applybranding

Branding:: brandingeditor

Branding:: createpackage

Branding:: cssmerge

Branding:: delbrandingobj

Branding:: delpackage

Branding:: gensprites

Branding:: getbrandingpkg

Branding:: getbrandingpkgstatus

Branding:: getdefaultbrandingpkg

Branding:: installbrandingpkgs

Branding:: installimages

Branding:: killimages

Branding:: listingtypes

Branding:: listobjecttypes

Branding:: preloadconf

Branding:: resetall

Branding:: resetscss

Branding:: resethtml

Branding:: resolvefile

Branding:: resolveocalcss

Branding:: saveocalcss

Branding:: setbrandingpkgstatus

Branding:: showpkgs

Branding:: spritelist

#### ▼ CSVImport

CSVImport:: columnchoices

CSVImport:: configimport

CSVImport:: data

CSVImport:: fetchimportdata

CSVImport:: isenabled

CSVImport:: loaddata

CSVImport:: processdata

CSVImport:: sendcontact

#### ▼ LiveAPI PHP Class

```
$cpanel = new  
CPANEL(); // Connect  
to cPanel - only do  
this once.  
  
// Remove Logaholic  
user "example"  
$delete_logaholicuser  
= $cpanel->api2(  
    'Logaholic',  
    'deleteuser',  
    array(  
        'username'  
=> 'example',  
    )  
);
```

#### Note:

For more information, read our [Guide to the LiveAPI System](#).

## About cPanel API 2

cPanel API 2 accesses and modifies data for cPanel accounts.

#### Notes:

- The  
Fe  
  
int  
• Ur  
mi  
us  
20  
or  
20  
)'.  
20  
or  
20  
)

## Find a function

- CSVImport:: uploadimport
- Contactus:: isenabled
    - Contactus:: sendcontact
  - Cron
    - Cron:: add\_line
    - Cron:: edit\_line
    - Cron:: fetchcron
    - Cron:: get\_email
    - Cron:: listcron
    - Cron:: remove\_line
    - Cron:: set\_email
  - CustInfo
    - CustInfo:: contactemails
    - CustInfo:: contactrefs
    - CustInfo:: displaycontactinfo
    - CustInfo:: savecontactinfo
  - DBmap
    - DBmap:: status
    - DBmap:: version
  - DKIMUI
    - DKIMUI:: available
    - DKIMUI:: getrecords
    - DKIMUI:: install
    - DKIMUI:: installed
    - DKIMUI:: uninstall
  - DenyIp
    - DenyIp:: listdenyps
  - DiskCounter
    - DiskCounter:: disk\_counter
  - DiskUsage
    - DiskUsage:: buildcache
    - DiskUsage:: clearcache
    - DiskUsage:: fetch\_raw\_disk\_usage
    - DiskUsage:: fetchdiskusage

## LiveAPI Perl Module

```

my $cpliveapi =
Cpanel::LiveAPI->new(
); # Connect to
cPanel - only do this
once.

# Remove Logaholic
user "example"
my
$delete_logaholicuser
= $cpliveapi->api2(
  'Logaholic',
  'deleteuser',
  {
    'username'
=> 'example',
  }
);

```

**Note:**  
For more information, read our [Guide to the LiveAPI System](#).

## cPanel Tag System (deprecated)

**Warnings:**

- In cPanel & WHM version 11.30 and later, cPanel tags are **deprecated**. We **strongly** recommend that you **only** use the [LiveAPI](#) system to call the cPanel APIs. Examples are **only** present in order to help developers move from the old cPanel tag system to our [LiveAPI](#).
- cPanel API 2 calls that use cPanel tags vary in code syntax and in their output.
- For more information, read our [Deprecated cPanel Tag Usage](#) documentation.

## Command Line

**Important:**  
Because we removed this function before we introduced this functionality, you **cannot** call this function via the command line.

- cPanel API 2 Functions - Logaholic: adduserprofile — This function adds a profile to a Logaholic user.
- cPanel API 2 Functions - Logaholic: deleteuserprofile — This function removes a profile from a Logaholic user.

- DiskUsage:: fetchdiskusagewithextras
- ▼ DnsLookup
  - DnsLookup:: name2ip
- ▼ DomainLookup
  - DomainLookup:: countbaseddomains
  - DomainLookup:: getbaseddomains
  - DomainLookup:: getdocroot
  - DomainLookup:: getdocroots
  - DomainLookup:: getmaindomain
- ▼ Email
  - Email:: accountname
  - Email:: adddomainforward
  - Email:: addforward
  - Email:: addmx
  - Email:: addpop
  - Email:: browseboxes
  - Email:: changemx
  - Email:: checkmaindiscard
  - Email:: clearpopcache
  - Email:: deletefilter
  - Email:: delforward
  - Email:: delmx
  - Email:: delpop
  - Email:: disablefilter
  - Email:: editquota
  - Email:: enablefilter
  - Email:: fetchautoreponder
  - Email:: fetchcharmaps
  - Email:: filteractions
  - Email:: filterlist
  - Email:: filtername
  - Email:: filterrules
  - Email:: get\_archiving\_configuration

### ▼ Output (JSON)

```

{
  "cpanelresult": {
    "apiversion": 2,
    "func":
    "deleteuser",
    "data": [
      {
        "reason":
        "The Logaholic user
        "example" was
        successfully
        deleted.",
        "result": 1
      }
    ],
    "event": {
      "result": 1
    },
    "module":
    "Logaholic"
  }
}
```

**Note:**  
 Use cPanel's *API Shell* interface (*cPanel >> Home >> Advanced >> API Shell*) to directly test cPanel API calls.

- cPanel API 2 Functions - Logaholic: deleteuser — This function removes a user from the Logaholic statistics program.
- cPanel API 2 Functions - Logaholic: edituser — This function edits a Logaholic user.

## Parameters

Return	Type	Description	Possible values	Example
username	string	<b>Required</b> The Logaholic username.	A valid string.	example

## Returns

Return	Type	Description	Possible values	Example
--------	------	-------------	-----------------	---------

Email: `get_archiving_default_configuration`

Email: `get_archiving_types`

Email: `get_default_email_quota`

Email: `get_email_signing`

Email: `get_max_email_quota`

Email: `getabsbrowse_dir`

Email: `getalwaysaccept`

Email: `getdiskusage`

Email: `getmxcheck`

Email: `has_delegated_mailman_lists`

Email: `list_system_filter_info`

Email: `listaliasbackups`

Email: `listautoresponders`

Email: `listdefaultaddresses`

Email: `listdomainforwards`

Email: `listfilterbackups`

Email: `listfilters`

Email: `listforwards`

Email: `listlists`

Email: `listmaildomains`

Email: `listmx`

Email: `listmxs`

Email: `listpops`

Email: `listpopssingle`

Email: `listpopswithdisk`

Email: `listpopswithimage`

Email: `loadfilter`

Email: `passwdpop`

<code>reason</code>	<i>string</i>	The status message from the function.	<ul style="list-style-type: none"><li>• The Logaholic user "example" was successfully deleted.</li><li>• "example" does not own the user "user".</li></ul>	The Logaholic user "example" was successfully deleted.
<code>result</code>	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none"><li>• 1 — The function succeeded.</li><li>• 0 — The function failed.</li></ul>	1
<code>reason</code>	<i>string</i>	A reason for failure. <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"><b>Note</b> : This function only returns a reason value if it failed.</div>	A string that describes the error.	This is an error message.
<code>result</code>	<i>Boolean</i>	Whether the function succeeded.	<ul style="list-style-type: none"><li>• 1 — The function succeeded.</li><li>• 0 — The function failed.</li></ul>	1

Email:: reorderfilter  
s

Email:: set\_archivi  
ng\_configuration

Email:: set\_archivi  
ng\_default\_configu  
ration

Email:: set\_email\_  
signing

Email:: setalwaysa  
ccept

Email:: setdefaulta  
ddress

Email:: setmxchec  
k

Email:: storefilter

Email:: tracefilter

▼ EmailTrack

EmailTrack:: searc  
h

EmailTrack:: stats

EmailTrack:: trace

▼ Encoding

Encoding:: get\_en  
codings

Encoding:: guess\_  
file

Encoding:: guess\_  
file\_opts

▼ FSTest

FSTest:: dirisempt  
y

▼ Fileman

Fileman:: autocom  
pletedir

Fileman:: fileop

Fileman:: getabsdir

Fileman:: getdir

Fileman:: getdiracti  
ons

Fileman:: getdiskin  
fo

Fileman:: geteditty  
pe

Fileman:: getfileact  
ions

Fileman:: getpath

Fileman:: listfiles

Fileman:: mkdir

Fileman:: mkfile

Fileman:: savefile

Fileman:: search

Fileman:: statfiles

Fileman:: uploadfiles

Fileman:: viewfile

▼ ForcePassword

ForcePassword:: get\_force\_password\_flags

ForcePassword:: update\_force\_password\_flags

▼ Frontpage

Frontpage:: fpenabled

Frontpage:: list

▼ Ftp

Ftp:: addftp

Ftp:: delftp

Ftp:: listftp

Ftp:: listftpsessions

Ftp:: listftpwithdisk

Ftp:: passwd

Ftp:: setquota

▼ Gpg

Gpg:: listgpgkeys

Gpg:: listsecretgpgkeys

Gpg:: number\_of\_private\_keys

Gpg:: number\_of\_public\_keys

▼ Htaccess

Htaccess:: listuser

Htaccess:: listusers

▼ HttpUtils

HttpUtils:: getdirindices

▼ ImageManager

ImageManager:: thumbnail

▼ LVEInfo

LVEInfo:: getUsage

▼ LangMods

LangMods:: getarchname

LangMods:: getkey

LangMods:: getpre  
fix

LangMods:: install

LangMods:: langlis  
t

LangMods:: list\_av  
ailable

LangMods:: list\_in  
stalled

LangMods:: magic  
\_status

LangMods:: pre\_ru  
n

LangMods:: search

LangMods:: setup

LangMods:: uninst  
all

LangMods:: updat  
e

▼ LeechProtect

LeechProtect:: set  
up

▼ Locale

Locale:: get\_encod  
ing

Locale:: get\_html\_  
dir\_attr

Locale:: get\_locale  
\_name

Locale:: get\_user\_  
ocale

Locale:: get\_user\_  
ocale\_name

Locale:: numf

▼ Logaholic

Logaholic:: adduse  
r

Logaholic:: adduse  
rprofile

Logaholic:: deleteu  
ser

Logaholic:: deleteu  
serprofile

Logaholic:: edituse  
r

Logaholic:: fetchus  
er

Logaholic:: listuser  
profiles

Logaholic:: logahol



iclink

Logaholic:: proces  
sstats

▼ Mime

Mime:: list\_hotlinks

Mime:: listhandlers

Mime:: listmime

Mime:: listredirects

Mime:: redirectna  
me

Mime:: redirecturln  
ame

▼ MysqlFE

MysqlFE:: authoriz  
ehost

MysqlFE:: change  
dbuserpassword

MysqlFE:: created  
b

MysqlFE:: created  
buser

MysqlFE:: dbusere  
xists

MysqlFE:: deautho  
rizehost

MysqlFE:: deleted  
b

MysqlFE:: deleted  
buser

MysqlFE:: getalldb  
sinfo

MysqlFE:: getalldb  
usersanddbs

MysqlFE:: getdbus  
erprivileges

MysqlFE:: getdbus  
ers

MysqlFE:: gethosts

MysqlFE:: getmys  
qlprivileges

MysqlFE:: getmys  
qlserverprivileges

MysqlFE:: has\_my  
cnf\_for\_cpuser

MysqlFE:: listdbs

MysqlFE:: listdbsb  
ackup

MysqlFE:: listhosts

MysqlFE:: listusers

MysqlFE:: listusers

indb

MysqlFE:: revoked  
buserprivileges

MysqlFE:: setdbu  
erprivileges

MysqlFE:: userdbp  
rivs

▼ MysqlOptimizer

MysqlOptimizer:: f  
etch\_slow\_queries

▼ NVData

NVData:: get

NVData:: set

NVData:: setall

▼ Net

Net:: dnszone

Net:: traceroute

▼ News

News:: does\_news  
\_exist

News:: does\_news  
\_type\_exist

News:: get\_news

▼ PHPINI

PHPINI:: getallopti  
ons

PHPINI:: getoption  
s

▼ Park

Park:: listaddondo  
mains

Park:: listparkeddo  
mains

Park:: park

Park:: unpark

▼ Passwd

Passwd:: change\_  
password

Passwd:: set\_dige  
st\_auth

▼ PasswdStrength

PasswdStrength::  
appstrengths

PasswdStrength::  
get\_password\_stre  
ngth

PasswdStrength::  
get\_required\_stren  
gth

▼ Postgres

Postgres:: listdbs

Postgres:: listusers

Postgres:: listusers  
indb

Postgres:: userexists

▼ Rand

Rand:: getranddata

▼ Resellers

Resellers:: get\_sub\_accounts

▼ RoR

RoR:: addapp

RoR:: changeapp

RoR:: importrails

RoR:: listapps

RoR:: listrewrites

RoR:: needsimport

RoR:: removeapp

RoR:: removerewrite

RoR:: restartapp

RoR:: setuprewrite

RoR:: softrestartapp

RoR:: startapp

RoR:: stopapp

▼ SetLang

SetLang:: setlocale

▼ SourceIPCheck

SourceIPCheck:: addip

SourceIPCheck:: delip

SourceIPCheck:: getaccount

SourceIPCheck:: listips

SourceIPCheck:: loadsecquestions

SourceIPCheck:: resetsecquestions

SourceIPCheck:: samplequestions

SourceIPCheck:: savequestions

▼ SPFUI

SPFUI:: available

SPFUI:: count\_settings

SPFUI:: entries\_complete

SPFUI:: get\_raw\_record

SPFUI:: getmainserverip

SPFUI:: install

SPFUI:: installed

SPFUI:: list\_settings

SPFUI:: load\_current\_values

SPFUI:: uninstall

#### ▼ SSH

SSH:: authkey

SSH:: converttopk

SSH:: delkey

SSH:: fetchkey

SSH:: genkey

SSH:: genkey\_legacy

SSH:: importkey

SSH:: listkeys

#### ▼ SSL

SSL:: fetchcertificate

SSL:: fetchinfo

SSL:: genctr

SSL:: gencsr

SSL:: genkey

SSL:: getcnname

SSL:: installssl

SSL:: listcrts

SSL:: listcsrs

SSL:: listkeys

SSL:: listsslitems

SSL:: uploadcrt

SSL:: uploadkey

#### ▼ SSLInfo

SSLInfo:: fetchinfo

#### ▼ StatCache

StatCache:: clearcache

▼ Stats

- Stats:: getmonthly bandwidth
- Stats:: getmonthly domainbandwidth
- Stats:: getthismont hsbwusage
- Stats:: lastapache hits
- Stats:: lastvisitors
- Stats:: listanalog
- Stats:: listawstats
- Stats:: listlastvisitors
- Stats:: listrawlogs
- Stats:: listurchin
- Stats:: listwebalizer

▼ StatsBar

- StatsBar:: getrowcounter
- StatsBar:: rowcounter
- StatsBar:: setrowcounter
- StatsBar:: stat

▼ SubDomain

- SubDomain:: adds ubdomain
- SubDomain:: changedocroot
- SubDomain:: delsubdomain
- SubDomain:: getservedsubdomains
- SubDomain:: listsubdomains
- SubDomain:: validregex

▼ Themes

- Themes:: apply\_new\_theme
- Themes:: does\_cpanel\_theme\_exist
- Themes:: get\_available\_themes
- Themes:: get\_themes\_list
- Themes:: restore\_saved\_theme

▼ UI

- UI:: dynamicincludelist
- UI:: includelist
- UI:: listform
- UI:: paginate
- UI:: paginate\_list

▼ UserHttpUtils

- UserHttpUtils:: getdirindices

▼ WebDisk

- WebDisk:: addwebdisk
- WebDisk:: delwebdisk
- WebDisk:: hasdigest
- WebDisk:: listwebdisks
- WebDisk:: passwdwebdisk
- WebDisk:: set\_digest\_auth
- WebDisk:: set\_homedir
- WebDisk:: set\_perms
- WebDisk:: setstatus

▼ WebmailApps

- WebmailApps:: listwebmailapps

▼ ZoneEdit

- ZoneEdit:: add\_zone\_record
- ZoneEdit:: edit\_zone\_record
- ZoneEdit:: fetch\_panel\_generated\_domains
- ZoneEdit:: fetchzone
- ZoneEdit:: fetchzone\_records
- ZoneEdit:: fetchzones
- ZoneEdit:: get\_zone\_record
- ZoneEdit:: remove\_zone\_record
- ZoneEdit:: resetzone

