

WHM API 1 Functions - get_all_contact_importances

Guide to WHM API 1

[Return Data](#)

[Filter Output](#)

[Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Call cPanel API 2 and UAPI](#)

[restore_modules_summary](#)

[restore_queue_activate](#)

[restore_queue_add_task](#)

[restore_queue_clear_all_completed_tasks](#)

[restore_queue_clear_all_failed_tasks](#)

[restore_queue_clear_all_pending_tasks](#)

[restore_queue_clear_all_tasks](#)

[restore_queue_clear_completed_task](#)

[restore_queue_clear_pending_task](#)

[restore_queue_is_active](#)

[restore_queue_list_active](#)

[restore_queue_list_completed](#)

[restore_queue_list_pending](#)

[restore_queue_state](#)

[restoreaccount](#)

[verify_new_username_for_restore](#)

[accountsummary](#)

Description

This function lists the importance of all application events in WHM's *Contact Manager* interface (*WHM >> Home >> Server Contacts >> Contact Manager*).

Examples

```
https://hostname.example.com:2087/cpsess#####/json-api/get_all_contact_importances?api.version=1
```

```
https://hostname.example.com:2087/cpsess#####/xml-api/get_all_contact_importances?api.version=1
```

```
whmapil get_all_contact_importances
```



Notes:

- Unless otherwise noted, you **must** [URI-encode](#) values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local/cpanel/bin/whmapil
```

```
{
  "data": {
    "importances": [
      {
        "app": "Accounts",
        "event": "*",
        "importance": "1",
        "name": "High"
      },
      {
        "event": "*",
        "app": "AdminBin",
        "name": "High",
        "importance": "1"
      },
      {
        "importance": "1",
        "name": "High",
        "event": "*",
        "app": "Application"
      },
      {
        "importance": "1",
        "name": "High",
        "event": "*",
        "app": "Backup"
      },
      {
        "importance": "1",

```

Function information

API Version: [WHM API 1](#)
Available in: WHM 58+
Methods: GET, POST
Required Parameters: (none)
Return Format: JSON, XML



Important:

cPanel & WHM version 66 **deprecated** XML output.

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.



Notes:

applist
createacct
domainuserdata
editquota
forcepasswordchange
get_disk_usage
get_domain_info
getdomainowner
has_digest_auth
has_myconf_or_cpuser
limitbw
list_users
listaccts
listlockedaccounts
listsuspended
modifyacct
myprivs
passwd
quota_enabled
removeacct
set_digest_auth
showbw
suspendacct
unsuspendacct
untrack_acct_id
verify_new_username
convert_addon_fetch_conversion_details
convert_addon_fetch_domain_details
convert_addon_get_conversion_status
convert_addon_initiate_conversion

```
"name": "High",  
"app": "Backup",  
"event": "Delayed"  
},  
{  
  "importance": "1",  
  "name": "High",  
  "event": "Disabled",  
  "app": "Backup"  
},  
{  
  "importance": "1",  
  "name": "High",  
  "app": "Backup",  
  "event": "Failure"  
},  
{  
  "app": "Backup",  
  "event": "PreBackupNotice",  
  "name": "High",  
  "importance": "1"  
},  
{  
  "name": "High",  
  "importance": "1",  
  "event": "Success",  
  "app": "Backup"  
},  
{  
  "app": "Backup",  
  "event": "Transport",  
  "name": "High",  
  "importance": "1"  
},  
{  
  "importance": "1",  
  "name": "High",  
  "event": "*",  
  "app": "BandwidthUsageExceeded"  
},  
{  
  "app": "ChangePassword",  
  "event": "*",  
  "name": "High",  
  "importance": "1"  
},  
{  
  "event": "ResetRequest",  
  "app": "ChangePassword",  
  "importance": "1",  
  "name": "High"  
},  
{  
  "app": "Check",  
  "event": "*",  
  "importance": "3",  
  "name": "Low"  
},  
{  
  "app": "Check",  
  "event": "Biglog",  
  "importance": "1",  
  "name": "High"  
},  
{  
  "name": "High",  
  "importance": "1",  
  "app": "Check",  
  "event": "CpanelRPMs"  
},  
{
```

- Some functions and parameters may require that you authenticate the router.

convert_addon_list_addon_domains
convert_addon_list_conversions
api_token_create
api_token_list
api_token_revoke
api_token_update
disable_authentication_provider
disable_failing_authentication_providers
enable_authentication_provider
get_available_authentication_providers
get_login_url
get_provider_client_configurations
get_provider_configuration_fields
get_provider_display_configurations
get_users_authn_linked_accounts
link_user_authn_provider
set_provider_client_configurations
set_provider_display_configurations
twofactorauth_disable_policy
twofactorauth_enable_policy
twofactorauth_generate_tfa_config
twofactorauth_get_issuer

```
"name": "High",  
"importance": "1",  
"event": "EximConfig",  
"app": "Check"  
},  
{  
"importance": "1",  
"name": "High",  
"app": "Check",  
"event": "Hack"  
},  
{  
"name": "High",  
"importance": "1",  
"event": "HostnameOwnedByUser",  
"app": "Check"  
},  
{  
"event": "IP",  
"app": "Check",  
"importance": "1",  
"name": "High"  
},  
{  
"importance": "1",  
"name": "High",  
"app": "Check",  
"event": "ImmutableFiles"  
},  
{  
"importance": "1",  
"name": "High",  
"event": "InvalidDomains",  
"app": "Check"  
},  
{  
"app": "Check",  
"event": "MySQL",  
"importance": "1",  
"name": "High"  
},  
{  
"event": "MysqlConnection",  
"app": "Check",  
"name": "High",  
"importance": "1"  
},  
{  
"event": "Oops",  
"app": "Check",  
"name": "High",  
"importance": "1"  
},  
{  
"importance": "1",  
"name": "High",  
"event": "PopBeforeSMTPEnabled",  
"app": "Check"  
},  
{  
"name": "High",  
"importance": "1",  
"event": "Resolvers",  
"app": "Check"  
},  
{  
"app": "Check",  
"event": "SSLCertExpired",  
"importance": "1",  
"name": "High"  
},  
},
```

• You must use the appropriate WHM ports (2086 or 2087) to call WHM API functions.

Find a function

Related functions

[twofactorauth_get_user_configs](#)
[twofactorauth_policy_status](#)
[twofactorauth_remove_user_config](#)
[twofactorauth_set_issuer](#)
[twofactorauth_set_tfa_config](#)
[unlink_user_authn_provider](#)
[validate_login_token](#)
[backup_config_get](#)
[backup_config_set](#)
[backup_date_list](#)
[backup_destination_add](#)
[backup_destination_delete](#)
[backup_destination_get](#)
[backup_destination_list](#)
[backup_destination_set](#)
[backup_destination_validate](#)
[backup_get_transport_status](#)
[backup_list_transported](#)
[backup_set_list](#)
[backup_set_list_combined](#)
[backup_skip_users_all](#)
[backup_skip_users_all_status](#)
[backup_user_list](#)

```

{
  "name": "High",
  "importance": "1",
  "app": "Check",
  "event": "SSLCertExpiresSoon"
},
{
  "name": "High",
  "importance": "1",
  "app": "Check",
  "event": "SecurityAdvisorStateChange"
},
{
  "app": "Check",
  "event": "Smart",
  "name": "High",
  "importance": "1"
},
{
  "importance": "1",
  "name": "High",
  "app": "Check",
  "event": "UnmonitoredEnabledServices"
},
{
  "name": "High",
  "importance": "1",
  "app": "Check",
  "event": "ValidServerHostname"
},
{
  "event": "*",
  "app": "CloudLinux",
  "importance": "1",
  "name": "High"
},
{
  "name": "High",
  "importance": "1",
  "app": "Config",
  "event": "*"
},
{
  "importance": "1",
  "name": "High",
  "event": "*",
  "app": "ConvertAddon"
},
{
  "name": "High",
  "importance": "1",
  "app": "DAV",
  "event": "ChangeHostname"
},
{
  "name": "High",
  "importance": "1",
  "event": "*",
  "app": "DigestAuth"
},
{
  "event": "*",
  "app": "DnsAdmin",
  "name": "Medium",
  "importance": "2"
},
{
  "name": "High",
  "importance": "1",
  "app": "DnsAdmin",
  "event": "ClusterError"
}

```

- [WHM API 1 Functions - get_tweaksetting](#) — This function retrieves a value from the `/var/cpanel/cpanel.config` file.
- [WHM API 1 Functions - getdiskusage](#) — This function retrieves the server's drive partition information.
- [WHM API 1 Functions - systemloadavg](#) — This function retrieves the system's load average.
- [WHM API 1 Functions - loadavg](#) — This function retrieves the server's load average.
- [WHM API 1 Functions - gethostname](#) — This function retrieves the server's hostname.

convert_and_migrate_from_legacy_config

get_users_with_backup_metadata

list_cparchive_files

start_background_pkgacct

toggle_user_backup_state

cphulk_status

create_cphulk_record

delete_cphulk_record

disable_cphulk

enable_cphulk

flush_cphulk_login_history

flush_cphulk_login_history_for_ips

get_countries_with_known_ip_ranges

get_cphulk_brutes

get_cphulk_excessive_brutes

get_cphulk_failed_logins

get_cphulk_user_brutes

load_cphulk_config

read_cphulk_records

save_cphulk_config

set_cphulk_config_key

background_mysql_upgrade_status

current_mysql_version

installable_mysql_versions

latest_available_mysql_version

```
},
{
  "name": "High",
  "importance": "1",
  "event": "UnreachablePeer",
  "app": "DnsAdmin"
},
{
  "name": "High",
  "importance": "1",
  "event": "*",
  "app": "EasyApache"
},
{
  "importance": "1",
  "name": "High",
  "event": "*",
  "app": "Greylist"
},
{
  "app": "Horde",
  "event": "*",
  "importance": "1",
  "name": "High"
},
{
  "name": "Low",
  "importance": "3",
  "app": "ImportMyDNSdb",
  "event": "*"
},
{
  "event": "Failure",
  "app": "ImportMyDNSdb",
  "name": "High",
  "importance": "1"
},
{
  "app": "ImportMyDNSdb",
  "event": "InProgress",
  "name": "High",
  "importance": "1"
},
{
  "app": "ImportMyDNSdb",
  "event": "Success",
  "name": "High",
  "importance": "1"
},
{
  "app": "Install",
  "event": "*",
  "name": "Low",
  "importance": "3"
},
{
  "app": "Install",
  "event": "ClamavConnector",
  "importance": "1",
  "name": "High"
},
{
  "app": "Install",
  "event": "Horde",
  "name": "High",
  "importance": "1"
},
{
  "name": "High",
  "importance": "1",
  "app": "Install",
```

list_database_users	}, { "event": "PackageExtension"
list_databases	{ "event": "*", "app": "Logd", "name": "High", "importance": "1"
list_mysql_databases_and_users	}, { "name": "High", "importance": "1", "event": "*", "app": "Logger"
remote_mysql_create_profile	}, { "event": "*", "app": "Market", "importance": "1", "name": "High"
remote_mysql_create_profile_via_ssh	}, { "app": "NSD", "event": "*", "name": "High", "importance": "1"
remote_mysql_delete_profile	}, { "name": "High", "importance": "1", "app": "NSD", "event": "BadZones"
remote_mysql_initiate_profile_activation	}, { "event": "*", "app": "Notice", "importance": "1", "name": "High"
remote_mysql_monitor_profile_activation	}, { "name": "High", "importance": "1", "app": "OutdatedSoftware", "event": "Notify"
remote_mysql_read_profile	}, { "importance": "1", "name": "High", "event": "CpuWatch", "app": "OverLoad"
remote_mysql_read_profiles	}, { "name": "High", "importance": "1", "app": "OverLoad", "event": "LogRunner"
remote_mysql_update_profile	}, { "name": "High", "importance": "1", "app": "PaperLantern", "event": "UpdateUsers"
remote_mysql_validate_profile	}, { "name": "Low", "importance": "3", "event": "*", "app": "Quota"
rename_mysql_database	}, { "app": "Quota", "event": "DiskWarning",
rename_mysql_user	
rename_postgresql_database	
rename_postgresql_user	
set_local_mysql_root_password	
set_mysql_password	
set_postgresql_password	
start_background_mysql_upgrade	
adddns	
addzonerecord	
addzonerecord (Reverse DNS)	

dumpzone	"importance": "1", "name": "High"
editzonerecord	}, {
get_nameser ver_config	"app": "Quota", "event": "RebootRequired", "importance": "1", "name": "High"
getzonerecord	}, {
has_local_au thority	"app": "Quota", "event": "SetupComplete", "importance": "1", "name": "High"
killdns	}, {
listmxs	"event": "*", "app": "RPMVersions", "importance": "1", "name": "High"
listzones	}, {
lookupnsip	"importance": "1", "name": "High"
lookupnspis	}, {
removezoner ecord	"importance": "1", "name": "High", "event": "*", "app": "Stats"
resetzone	}, {
resolvedomai nname	"importance": "1", "name": "High", "event": "*", "app": "StuckScript"
savemxs	}, {
setresolvers	"event": "UserDisable", "app": "TwoFactorAuth", "importance": "1", "name": "High"
update_nam eservers_con fig	}, {
ea4_get_curr ently_installe d_packages	"importance": "1", "name": "High", "event": "UserEnable", "app": "TwoFactorAuth"
ea4_get_ea_ pkgs_state	}, {
ea4_list_profi les	"app": "Update", "event": "*", "importance": "1", "name": "High"
ea4_metainfo	}, {
ea4_migration	"app": "Update", "event": "Blocker", "importance": "1", "name": "High"
ea4_pre_mig rate_check	}, {
ea4_recomm endations	"event": "Now", "app": "Update", "importance": "1", "name": "High"
ea4_save_pr ofile	}, {
ea4_tomcat8 5_add	"name": "High", "importance": "1", "app": "Update", "event": "ServiceDeprecated"
ea4_tomcat8 5_list	}, {
ea4_tomcat8 5_rem	"name": "High",
cpgreylist_is_ server_netblo ck_trusted	
cpgreylist_list _entries_for_ common_mai l_provider	

cpgreylist_lo
ad_common_
mail_provider
s_config

cpgreylist_sa
ve_common_
mail_provider
s_config

cpgreylist_st
atus

cpgreylist_tru
st_entries_for
_common_m
ail_provider

cpgreylist_un
trust_entries_
for_common_
_mail_provid
er

create_cpgre
ylist_trusted_
host

delete_cpgre
ylist_trusted_
host

disable_cpgr
eylist

enable_cpgre
ylist

load_cpgreyli
st_config

read_cpgreyli
st_deferred_
entries

read_cpgreyli
st_trusted_ho
st

save_cpgreyli
st_config

batch

cpanel

create_integr
ation_group

create_integr
ation_link

get_integratio
n_link_user_
config

list_integratio
n_groups

list_integratio
n_links

remove_integ
ration_group

remove_integ
ration_link

```
"importance": "1",  
"event": "UpgradeRequired",  
"app": "Update"  
},  
{  
  "app": "appconfig",  
  "event": "*",  
  "name": "High",  
  "importance": "1"  
},  
{  
  "importance": "1",  
  "name": "High",  
  "app": "biglogcheck",  
  "event": "*"   
},  
{  
  "name": "High",  
  "importance": "1",  
  "app": "cPHulk",  
  "event": "*"   
},  
{  
  "event": "BruteForce",  
  "app": "cPHulk",  
  "importance": "1",  
  "name": "High"  
},  
{  
  "app": "cPHulk",  
  "event": "Login",  
  "name": "High",  
  "importance": "1"  
},  
{  
  "event": "*",  
  "app": "checkperlmodules",  
  "importance": "0",  
  "name": "Disabled"  
},  
{  
  "event": "*",  
  "app": "chkserverd",  
  "importance": "1",  
  "name": "High"  
},  
{  
  "app": "chkserverd",  
  "event": "DiskUsage",  
  "importance": "1",  
  "name": "High"  
},  
{  
  "name": "High",  
  "importance": "1",  
  "event": "Hang",  
  "app": "chkserverd"  
},  
{  
  "importance": "1",  
  "name": "High",  
  "event": "OOM",  
  "app": "chkserverd"  
},  
{  
  "app": "clamd",  
  "event": "*",  
  "importance": "1",  
  "name": "High"  
},  
{
```



```

update_integ
ration_link_to
ken
    "name": "Disabled",
    "importance": "0",
    "app": "cpanel.config",
    "event": "*"
},
addips
{
    "event": "*",
    "app": "cpbackup",
    "name": "High",
    "importance": "1"
},
delip
{
    "importance": "1",
    "name": "High",
    "app": "cpbackupdisabled",
    "event": "*"
},
get_public_ip
{
    "name": "High",
    "importance": "1",
    "app": "dbindex",
    "event": "Warn"
},
get_shared_ip
{
    "importance": "0",
    "name": "Disabled",
    "app": "disabledigest",
    "event": "*"
},
ipv6_disable
_account
{
    "app": "formmaillog",
    "event": "*",
    "name": "High",
    "importance": "1"
},
ipv6_enable_
account
{
    "importance": "0",
    "name": "Disabled",
    "app": "hackcheck",
    "event": "*"
},
ipv6_range_a
dd
{
    "importance": "1",
    "name": "High",
    "app": "iContact",
    "event": "*"
},
ipv6_range_e
dit
{
    "event": "*",
    "app": "icontact_sendim",
    "name": "High",
    "importance": "1"
},
ipv6_range_li
st
{
    "app": "installbandwidth",
    "event": "*",
    "name": "High",
    "importance": "1"
},
ipv6_range_r
emove
{
    "app": "ipcheck",
    "event": "*",
    "importance": "0",
    "name": "Disabled"
},
ipv6_range_u
sage
{
    "name": "Disabled",
    "importance": "0",
    "event": "*",
    "app": "kernelcheck"
},
listips
{
    "app": "kernelcheck"
},
nat_checkip
{
    "app": "kernelcheck"
},
nat_set_publi
c_ip
{
    "app": "kernelcheck"
},
setsiteip
{
    "app": "kernelcheck"
},
disable_dkim
{
    "app": "kernelcheck"
},
disable_mail
_sni
{
    "app": "kernelcheck"
},
emailtrack_s
earch
{
    "app": "kernelcheck"
},
emailtrack_st
ats
{
    "app": "kernelcheck"
},
emailtrack_u
ser_stats
{
    "app": "kernelcheck"
},
enable_dkim
{
    "app": "kernelcheck"
},
enable_mail_
sni
{
    "app": "kernelcheck"
},
ensure_dkim
_keys_exist
{
    "app": "kernelcheck"
},
exim_configu
ration_check
{
    "app": "kernelcheck"
},
expunge_mai
lbox_messag
es
{
    "app": "kernelcheck"
},
expunge_me
ssages_for_
mailbox_guid
{
    "app": "kernelcheck"
},
fetch_dkim_p
rivate_keys
{
    "app": "kernelcheck"
},
fetch_mail_q
ueue
{
    "app": "kernelcheck"
}

```

generate_mailconfig
get_mailbox_status
get_mailbox_status_list
get_unique_recipient_count_per_sender_for_user
get_unique_sender_recipient_count_per_user
get_user_email_forward_destination
hold_outgoing_email
install_dkim_private_keys
install_spf_records
is_sni_supported
list_pops_for
mail_sni_status
rebuild_mail_sni_config
release_outgoing_email
save_spamd_config
set_user_email_forward_destination
suspend_outgoing_email
unsuspend_outgoing_email
validate_current_installed_exim_config
validate_current_dkims
validate_current_ptrs
validate_current_spfs
validate_exim_configuration_syntax
disable_market_provider

```
{
  "importance": "1",
  "name": "High",
  "event": "*",
  "app": "killacct"
},
{
  "app": "mailconfigupdate",
  "event": "*",
  "name": "High",
  "importance": "1"
},
{
  "event": "*",
  "app": "maildirupdate",
  "name": "High",
  "importance": "1"
},
{
  "event": "*",
  "app": "migrate_branding",
  "name": "High",
  "importance": "1"
},
{
  "event": "*",
  "app": "newmailcgi",
  "importance": "1",
  "name": "High"
},
{
  "event": "*",
  "app": "oopscheck",
  "name": "Disabled",
  "importance": "0"
},
{
  "name": "High",
  "importance": "1",
  "app": "parkadmin",
  "event": "*"
},
{
  "app": "queueprocd",
  "event": "*",
  "name": "High",
  "importance": "1"
},
{
  "app": "quotaadmin",
  "event": "*",
  "importance": "0",
  "name": "Disabled"
},
{
  "importance": "0",
  "name": "Disabled",
  "app": "quotacheck",
  "event": "*"
},
{
  "app": "rpm.versions",
  "event": "*",
  "name": "High",
  "importance": "1"
},
{
  "event": "*",
  "app": "rpmcheck",
  "importance": "0",
  "name": "Disabled"
}
```

enable_market_provider

get_adjusted_market_providers_products

get_market_providers_commission_config

get_market_providers_list

get_market_providers_product_metadata

get_market_providers_products

set_market_product_attribute

set_market_provider_commission_id

modsec_add_rule

modsec_add_vendor

modsec_assemble_config_text

modsec_batch_settings

modsec_check_rule

modsec_clone_rule

modsec_deploy_all_rule_changes

modsec_deploy_rule_changes

modsec_deploy_settings_changes

modsec_disable_rule

modsec_disable_vendor

modsec_disable_vendor_configs

modsec_disable_vendor_updates

```
    },
    {
      "name": "Disabled",
      "importance": "0",
      "event": "*",
      "app": "smartcheck"
    },
    {
      "app": "suspendacct",
      "event": "*",
      "importance": "1",
      "name": "High"
    },
    {
      "importance": "1",
      "name": "High",
      "app": "sysup",
      "event": "*"
    },
    {
      "event": "*",
      "app": "unsuspendacct",
      "importance": "1",
      "name": "High"
    },
    {
      "event": "*",
      "app": "upacct",
      "importance": "1",
      "name": "High"
    },
    {
      "app": "upcp",
      "event": "*",
      "importance": "1",
      "name": "High"
    },
    {
      "app": "wwwacct",
      "event": "*",
      "name": "High",
      "importance": "1"
    }
  ]
},
"metadata": {
  "reason": "OK",
  "command": "get_all_contact_importances",
  "version": 1,
  "result": 1
}
}
```

```
<result>
  <data>
    <importances>
      <name>High</name>
      <importance>1</importance>
      <event>*</event>
      <app>Accounts</app>
    </importances>
    <importances>
      <importance>1</importance>
      <app>AdminBin</app>
      <event>*</event>
      <name>High</name>
    </importances>
  </importances>
</result>
```

modsec_discard_all_rule_changes
modsec_discard_rule_changes
modsec_edit_rule
modsec_enable_vendor
modsec_enable_vendor_configs
modsec_enable_vendor_updates
modsec_get_config_text
modsec_get_configs
modsec_get_configs_with_changes_pending
modsec_get_log
modsec_get_rules
modsec_get_settings
modsec_get_vendors
modsec_is_installed
modsec_make_config_active
modsec_make_config_inactive
modsec_preview_vendor
modsec_remove_rule
modsec_remove_setting
modsec_remove_vendor
modsec_report_rule
modsec_set_config_text
modsec_set_setting
modsec_undisable_rule

```
<name>High</name>
<importance>1</importance>
<app>Application</app>
<event>*</event>
</importances>
<importances>
  <importance>1</importance>
  <app>Backup</app>
  <event>*</event>
  <name>High</name>
</importances>
<importances>
  <importance>1</importance>
  <event>Delayed</event>
  <app>Backup</app>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <app>Backup</app>
  <event>Disabled</event>
  <importance>1</importance>
</importances>
<importances>
  <name>High</name>
  <app>Backup</app>
  <event>Failure</event>
  <importance>1</importance>
</importances>
<importances>
  <name>High</name>
  <app>Backup</app>
  <event>PreBackupNotice</event>
  <importance>1</importance>
</importances>
<importances>
  <name>High</name>
  <event>Success</event>
  <app>Backup</app>
  <importance>1</importance>
</importances>
<importances>
  <app>Backup</app>
  <event>Transport</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <importance>1</importance>
  <app>BandwidthUsageExceeded</app>
  <event>*</event>
  <name>High</name>
</importances>
<importances>
  <importance>1</importance>
  <app>ChangePassword</app>
  <event>*</event>
  <name>High</name>
</importances>
<importances>
  <app>ChangePassword</app>
  <event>ResetRequest</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>Low</name>
  <importance>3</importance>
  <app>Check</app>
  <event>*</event>
</importances>
```

modsec_update_vendor
_getpkgextensionform
add_override_features_for_user
addpkg
addpkgext
changepackage
create_featurelist
delete_featurelist
delpkgext
editpkg
get_available_applications
get_available_featurelists
get_feature_metadata
get_feature_names
get_featurelist_data
get_featurelists
get_users_features_settings
getfeaturelist
getpkginfo
killpkg
listpkgs
manage_features
matchpkgs
read_featurelist
remove_override_features_for_user
update_featurelist
verify_user_has_feature
convert_all_domains_to_fpm

```
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>Biglog</event>
  <app>Check</app>
</importances>
<importances>
  <importance>1</importance>
  <app>Check</app>
  <event>CpanelRPMs</event>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>EximConfig</event>
  <app>Check</app>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <app>Check</app>
  <event>Hack</event>
</importances>
<importances>
  <app>Check</app>
  <event>HostnameOwnedByUser</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <importance>1</importance>
  <event>IP</event>
  <app>Check</app>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <event>ImmutableFiles</event>
  <app>Check</app>
  <importance>1</importance>
</importances>
<importances>
  <importance>1</importance>
  <event>InvalidDomains</event>
  <app>Check</app>
  <name>High</name>
</importances>
<importances>
  <importance>1</importance>
  <event>MySQL</event>
  <app>Check</app>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>MysqlConnection</event>
  <app>Check</app>
</importances>
<importances>
  <name>High</name>
  <app>Check</app>
  <event>Oops</event>
  <importance>1</importance>
</importances>
<importances>
  <importance>1</importance>
  <event>PopBeforeSMTPEnabled</event>
  <app>Check</app>
  <name>High</name>
```

get_fpm_configuration
is_conversion_in_progress
php_get_default_account_s_to_fpm
php_get_handlers
php_get_important_domains
php_get_installed_versions
php_get_old_fpm_flag
php_get_system_default_version
php_get_who_sts_by_version
php_get_who_st_versions
php_ini_get_content
php_ini_get_directives
php_ini_set_content
php_ini_set_directives
php_set_default_accounts_to_fpm
php_set_handler
php_set_old_fpm_flag
php_set_session_save_path
php_set_system_default_version
php_set_who_st_versions
acctcounts
get_public_contact
getresellerips
listaccls
listresellers

```
</importances>  
<importances>  
  <importance>1</importance>  
  <app>Check</app>  
  <event>Resolvers</event>  
  <name>High</name>  
</importances>  
<importances>  
  <importance>1</importance>  
  <app>Check</app>  
  <event>SSLCertExpired</event>  
  <name>High</name>  
</importances>  
<importances>  
  <name>High</name>  
  <app>Check</app>  
  <event>SSLCertExpiresSoon</event>  
  <importance>1</importance>  
</importances>  
<importances>  
  <importance>1</importance>  
  <event>SecurityAdvisorStateChange</event>  
  <app>Check</app>  
  <name>High</name>  
</importances>  
<importances>  
  <app>Check</app>  
  <event>Smart</event>  
  <importance>1</importance>  
  <name>High</name>  
</importances>  
<importances>  
  <importance>1</importance>  
  <app>Check</app>  
  <event>UnmonitoredEnabledServices</event>  
  <name>High</name>  
</importances>  
<importances>  
  <name>High</name>  
  <event>ValidServerHostname</event>  
  <app>Check</app>  
  <importance>1</importance>  
</importances>  
<importances>  
  <importance>1</importance>  
  <event>*</event>  
  <app>CloudLinux</app>  
  <name>High</name>  
</importances>  
<importances>  
  <event>*</event>  
  <app>Config</app>  
  <importance>1</importance>  
  <name>High</name>  
</importances>  
<importances>  
  <name>High</name>  
  <app>ConvertAddon</app>  
  <event>*</event>  
  <importance>1</importance>  
</importances>  
<importances>  
  <app>DAV</app>  
  <event>ChangeHostname</event>  
  <importance>1</importance>  
  <name>High</name>  
</importances>  
<importances>  
  <name>High</name>  
  <app>DigestAuth</app>  
  <event>*</event>
```

resellerstats
saveacllist
set_public_contact
setacis
setresellerips
setresellerlimits
setresellermainip
setresellername_servers
setresellerpackage_limit
setupreseller
suspendreseller
terminatereseller
unsetupreseller
unsuspendreseller
delete_rpm_version
edit_rpm_version
get_rpm_version_data
install_rpm_plugin
list_rpms
package_manager_fixcache
package_manager_get_build_log
package_manager_get_package_info
package_manager_is_performing_actions
package_manager_list_packages
package_manager_resolve_actions
package_manager_submit_actions

```
<importance>1</importance>
</importances>
<importances>
  <name>Medium</name>
  <importance>2</importance>
  <event>*</event>
  <app>DnsAdmin</app>
</importances>
<importances>
  <name>High</name>
  <app>DnsAdmin</app>
  <event>ClusterError</event>
  <importance>1</importance>
</importances>
<importances>
  <event>UnreachablePeer</event>
  <app>DnsAdmin</app>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>*</event>
  <app>EasyApache</app>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <app>Greylist</app>
  <event>*</event>
</importances>
<importances>
  <name>High</name>
  <event>*</event>
  <app>Horde</app>
  <importance>1</importance>
</importances>
<importances>
  <app>ImportMyDNSdb</app>
  <event>*</event>
  <importance>3</importance>
  <name>Low</name>
</importances>
<importances>
  <importance>1</importance>
  <app>ImportMyDNSdb</app>
  <event>Failure</event>
  <name>High</name>
</importances>
<importances>
  <app>ImportMyDNSdb</app>
  <event>InProgress</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <app>ImportMyDNSdb</app>
  <event>Success</event>
</importances>
<importances>
  <importance>3</importance>
  <app>Install</app>
  <event>*</event>
  <name>Low</name>
</importances>
<importances>
  <importance>1</importance>
  <event>ClamavConnector</event>
```

package_m
anager_upgra
de

uninstall_rpm
_plugin

delete_hook

edit_hook

list_hooks

reorder_hooks

accessshash

authorizessh
key

check_remot
e_ssh_conne
ction

convertopens
shtoputty

deletesshkey

fetch_securit
y_advice

generatesshk
eypair

importsshkey

listsshkeys

add_configcl
usterserver

configurebac
kgroundproc
esskiller

configureserv
ice

cors_proxy_g
et

create_user_
session

delete_config
clusterserver

enable_monit
or_all_enable
d_services

get_all_conta
ct_importanc
es

get_appconfi
g_application
_list

get_applicati
on_contact_e
vent_importa
nce

get_applicati
on_contact_i
mpportance

```
<app>Install</app>
  <name>High</name>
</importances>
<importances>
  <importance>1</importance>
  <event>Horde</event>
  <app>Install</app>
  <name>High</name>
</importances>
<importances>
  <event>PackageExtension</event>
  <app>Install</app>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <event>*</event>
  <app>Logd</app>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <event>*</event>
  <app>Logger</app>
  <importance>1</importance>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>*</event>
  <app>Market</app>
</importances>
<importances>
  <name>High</name>
  <app>NSD</app>
  <event>*</event>
  <importance>1</importance>
</importances>
<importances>
  <app>NSD</app>
  <event>BadZones</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <app>Notice</app>
  <event>*</event>
</importances>
<importances>
  <name>High</name>
  <app>OutdatedSoftware</app>
  <event>Notify</event>
  <importance>1</importance>
</importances>
<importances>
  <app>OverLoad</app>
  <event>CpuWatch</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <event>LogRunner</event>
  <app>OverLoad</app>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
```


get_available_profiles
get_current_profile
get_password_strength
get_remote_access_hash
get_service_config
get_service_config_key
get_tcp4_sockets
get_tcp6_sockets
get_tweaksetting
get_udp4_sockets
get_udp6_sockets
get_update_availability
get_users_links
getdiskusage
gethostname
is_role_enabled
list_configclusterservers
loadavg
nvget
nvset
personalization_get
personalization_set
purchase_app_license
reboot
remove_in_progress_exim_config_edit
restartservice
restore_config_from_file
restore_config_from_upload

```
<importance>1</importance>  
<app>PaperLantern</app>  
<event>UpdateUsers</event>  
</importances>  
<importances>  
<importance>3</importance>  
<app>Quota</app>  
<event>*</event>  
<name>Low</name>  
</importances>  
<importances>  
<app>Quota</app>  
<event>DiskWarning</event>  
<importance>1</importance>  
<name>High</name>  
</importances>  
<importances>  
<importance>1</importance>  
<event>RebootRequired</event>  
<app>Quota</app>  
<name>High</name>  
</importances>  
<importances>  
<name>High</name>  
<importance>1</importance>  
<event>SetupComplete</event>  
<app>Quota</app>  
</importances>  
<importances>  
<importance>1</importance>  
<event>*</event>  
<app>RPMVersions</app>  
<name>High</name>  
</importances>  
<importances>  
<importance>1</importance>  
<event>*</event>  
<app>Stats</app>  
<name>High</name>  
</importances>  
<importances>  
<app>StuckScript</app>  
<event>*</event>  
<importance>1</importance>  
<name>High</name>  
</importances>  
<importances>  
<name>High</name>  
<importance>1</importance>  
<app>TwoFactorAuth</app>  
<event>UserDisable</event>  
</importances>  
<importances>  
<name>High</name>  
<importance>1</importance>  
<app>TwoFactorAuth</app>  
<event>UserEnable</event>  
</importances>  
<importances>  
<name>High</name>  
<event>*</event>  
<app>Update</app>  
<importance>1</importance>  
</importances>  
<importances>  
<app>Update</app>  
<event>Blocker</event>  
<importance>1</importance>  
<name>High</name>  
</importances>  
<importances>
```

run_cpkeyctl
send_test_posturl
send_test_pushbullet_note
servicestatus
set_application_contact_event_importance
set_application_contact_importance
set_primary_servername
set_service_config_key
set_tweaking
sethostname
setminimumpasswordstrengths
start_profile_activation
system_needs_reboot
systemloadavg
update_config_clusterserver
update_contact_email
verify_aim_access
verify_icq_access
verify_oscar_access
verify_posturl_access
verify_pushbullet_access
disable_auto_ssl
fetch_service_ssl_components
fetch_ssl_certificates_forfqdns
fetch_ssl_vhosts

```
<event>Now</event>
<app>Update</app>
<importance>1</importance>
<name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>ServiceDeprecated</event>
  <app>Update</app>
</importances>
<importances>
  <app>Update</app>
  <event>UpgradeRequired</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <app>appconfig</app>
  <event>*</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>*</event>
  <app>biglogcheck</app>
</importances>
<importances>
  <app>cPHulk</app>
  <event>*</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>BruteForce</event>
  <app>cPHulk</app>
</importances>
<importances>
  <importance>1</importance>
  <app>cPHulk</app>
  <event>Login</event>
  <name>High</name>
</importances>
<importances>
  <name>Disabled</name>
  <app>checkperlmodules</app>
  <event>*</event>
  <importance>0</importance>
</importances>
<importances>
  <event>*</event>
  <app>chksservd</app>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <app>chksservd</app>
  <event>DiskUsage</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <app>chksservd</app>
  <event>Hang</event>
</importances>
```

fetch_vhost_ssl_components
fetchcrtinfo
fetchsslinfo
generatessl
get_autossl_check_schedule
get_autossl_log
get_autossl_logs_catalog
get_autossl_metadata
get_autossl_pending_queue
get_autossl_pending_queue_for_domain
get_autossl_pending_queue_for_user
get_autossl_problems_for_domain
get_autossl_problems_for_user
get_autossl_providers
get_best_ssl_domain_for_service
install_service_ssl_certificate
installssl
listcrts
rebuildinstall_edssldb
rebuildusersldb
reset_autossl_provider
reset_service_ssl_certificate
set_autossl_metadata
set_autossl_metadata_key
set_autossl_provider

```
<importances>
  <importance>1</importance>
  <app>chkserve</app>
  <event>OOM</event>
  <name>High</name>
</importances>
<importances>
  <importance>1</importance>
  <event>*</event>
  <app>clamd</app>
  <name>High</name>
</importances>
<importances>
  <importance>0</importance>
  <app>cpanel.config</app>
  <event>*</event>
  <name>Disabled</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>*</event>
  <app>cpbackup</app>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>*</event>
  <app>cpbackupdisabled</app>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>Warn</event>
  <app>dbindex</app>
</importances>
<importances>
  <importance>0</importance>
  <event>*</event>
  <app>disabledigest</app>
  <name>Disabled</name>
</importances>
<importances>
  <importance>1</importance>
  <app>formmaillog</app>
  <event>*</event>
  <name>High</name>
</importances>
<importances>
  <event>*</event>
  <app>hackcheck</app>
  <importance>0</importance>
  <name>Disabled</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <app>iContact</app>
  <event>*</event>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <event>*</event>
  <app>icontact_sendim</app>
</importances>
<importances>
  <name>High</name>
  <app>installbandwidth</app>
  <event>*</event>
  <importance>1</importance>
```

start_autossl
_check_for_all_users

start_autossl
_check_for_online_user

generate_cpanel_plugin

list_styles

load_style

remove_logo

remove_style

save_style

set_default

ticket_create_stub_ticket

ticket_get_support_agreement

ticket_get_support_info

ticket_grant

ticket_list

ticket_remove_closed

ticket_revoke

ticket_ssh_test

ticket_ssh_test_start

ticket_update_service_agreement_approval

ticket_validate_oauth2_code

ticket_whitelist_check

ticket_whitelist_setup

ticket_whitelist_unsetup

abort_transfer_session

analyze_transfer_session_remote

available_transfer_modules

create_remote_root_transfer_session

```
</importances>
<importances>
  <importance>0</importance>
  <app>ipcheck</app>
  <event>*</event>
  <name>Disabled</name>
</importances>
<importances>
  <name>Disabled</name>
  <event>*</event>
  <app>kernelcheck</app>
  <importance>0</importance>
</importances>
<importances>
  <event>*</event>
  <app>killacct</app>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <event>*</event>
  <app>mailconfigupdate</app>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <event>*</event>
  <app>maildirupdate</app>
  <importance>1</importance>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <app>migrate_branding</app>
  <event>*</event>
</importances>
<importances>
  <importance>1</importance>
  <app>newmailcgi</app>
  <event>*</event>
  <name>High</name>
</importances>
<importances>
  <importance>0</importance>
  <app>oopscheck</app>
  <event>*</event>
  <name>Disabled</name>
</importances>
<importances>
  <name>High</name>
  <event>*</event>
  <app>parkadmin</app>
  <importance>1</importance>
</importances>
<importances>
  <importance>1</importance>
  <app>queueprocd</app>
  <event>*</event>
  <name>High</name>
</importances>
<importances>
  <importance>0</importance>
  <event>*</event>
  <app>quotaadmin</app>
  <name>Disabled</name>
</importances>
<importances>
  <importance>0</importance>
  <app>quotacheck</app>
  <event>*</event>
```

create_remote_user_transfer_session
delete_account_archives
enqueue_transfer_item
fetch_transfer_session_log
get_transfer_session_state
pause_transfer_session
remote_basic_credential_check
retrieve_transfer_session_remote_analysis
start_transfer_session
transfer_module_schema
validate_system_user
accept_eula
get_available_tiers
get_current_lts_expiration_status
get_lts_wexpire
getlongtermsupport
installed_versions
set_cpanel_updates
set_tier
update_updateconf
version

```
<name>Disabled</name>
</importances>
<importances>
  <importance>1</importance>
  <app>rpm.versions</app>
  <event>*</event>
  <name>High</name>
</importances>
<importances>
  <name>Disabled</name>
  <importance>0</importance>
  <event>*</event>
  <app>rpmcheck</app>
</importances>
<importances>
  <app>smartcheck</app>
  <event>*</event>
  <importance>0</importance>
  <name>Disabled</name>
</importances>
<importances>
  <name>High</name>
  <app>suspendacct</app>
  <event>*</event>
  <importance>1</importance>
</importances>
<importances>
  <name>High</name>
  <app>sysup</app>
  <event>*</event>
  <importance>1</importance>
</importances>
<importances>
  <name>High</name>
  <app>unsuspendacct</app>
  <event>*</event>
  <importance>1</importance>
</importances>
<importances>
  <app>upacct</app>
  <event>*</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <app>upcp</app>
  <event>*</event>
  <importance>1</importance>
  <name>High</name>
</importances>
<importances>
  <name>High</name>
  <importance>1</importance>
  <app>wwwacct</app>
  <event>*</event>
</importances>
</data>
<metadata>
  <result>1</result>
  <command>get_all_contact_importances</command>
  <reason>OK</reason>
  <version>1</version>
</metadata>
</result>
```

**Note:**

Use WHM's [API Shell](#) interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

This function does not accept parameters.

Returns

Return	Type	Description	Possible values	Example
importance	array of hashes	An array of hashes with event importance information.	This array of hashes includes the <code>app</code> , <code>event</code> , <code>name</code> , and <code>importance</code> returns.	
app	string	The application's name. <div data-bbox="602 894 948 1163" style="border: 1px solid red; padding: 5px;"> <p> Warning:</p> <p>We deprecated the MyDNS and NSD nameservers in cPanel & WHM version 78 and plan to remove them a future release. We strongly recommend that you migrate to PowerDNS. For more information, read our cPanel Deprecation Plan.</p> </div> <p>The function returns this value in the <code>importance</code> hash.</p>	A valid cPanel & WHM module name.	wwwacct
event	string	The event's name. The function returns this value in the <code>importance</code> hash.	A valid event name in the module. <div data-bbox="967 1329 1089 1871" style="border: 1px solid yellow; padding: 5px;"> <p> Note:</p> <p>An asterisk character (<code>*</code>) represents all events in the module.</p> </div>	*

name	<i>string</i>	<p>The text name of the contact event.</p> <p>The function returns this value in the importance hash.</p>	<ul style="list-style-type: none"> • High • Medium • Low • Disabled 	High
importance	<i>integer</i>	<p>The importance of the contact event.</p> <p>The function returns this value in the importance hash.</p>	<ul style="list-style-type: none"> • 1 — High. • 2 — Medium. • 3 — Low. • 0 — Disabled. 	0