

[verify_new_username_for_restore](#)
[accountsummary](#)
[applist](#)
[createacct](#)
[domainuserdata](#)
[editquota](#)
[forcepasswordchange](#)
[get_current_users_count](#)
[get_disk_usage](#)
[get_domain_info](#)
[getdomainowner](#)
[get_maximum_users](#)
[getminimumpasswordstrengths](#)
[has_digest_auth](#)
[has_myconf_or_cpuser](#)
[limitbw](#)
[list_users](#)
[listaccts](#)
[listlockedaccounts](#)
[listsuspended](#)
[modifyacct](#)
[myprivs](#)
[passwd](#)
[quota_enabled](#)
[removeacct](#)
[set_digest_auth](#)
[showbw](#)
[suspendacct](#)
[unsuspendacct](#)
[untrack_acct_id](#)
[verify_new_username](#)

```

YuNzItMi44NCA2LjcyLTYuODQgMC0uNDYtLjA1LS44MS0uMTBtMS4xNkg3
ek0yMiA2aC0yVjRoLTJ2MmgtMnYyaDJ2MmgyVjhoMiIvPjwvZz48L3N2Zz
4=" ,
    "icon_type": "image/svg+xml" ,
    "display_name": "Gooble" ,
    "color": "dd4b39" ,
    "textcolor": "FF0000" ,
    "link": "https://hostname.example.com:2083
/openid_connect/google" ,
    "label": "Log in via Google"
  } ,
  {
    "color": "dd4b39" ,
    "link": "https://hostname.example.com:2096
/openid_connect/google" ,
    "textcolor": "FFFFFF" ,
    "label": "Log in via Google" ,
    "display_name": "Gooble" ,
    "icon_type": "image/svg+xml" ,
    "icon": "
PHN2ZyB4bWxucz0iaHR0cDovL3d3dy53My5vcmcvMjAwMC9zdmciIHdpZH
RoPSIyMiIgaGVpZ2h0PSIxNCIgdmlld0JveD0iMCAwIDYyIDE0Ij48ZyBm
aWxsPSIjZmZmIiBmaWxsLXJlbGU9ImV2ZW5vZGQiPjxwYXRoIGQ9Ik03ID
Z2Mi40aDMuOTdjLS4xNiAxLjAzLTFEUiAzLjAyLTMuOTcgMy4wMi0yLjM5
IDAtNC4zNC0xLjk4LTQuMzQtNC40MlM0LjYxIDIuNTggNyAyLjU4YzEuMz
YgMCAyLjI3LjU4IDIuNzkgMS4wOGwxLjktMS44MOMxMC40Ny42OSA4Ljg5
IDAgNyAwIDMuMTMgMCAwIDMuMTMgMCA3czMuMTMgNyA3IDdjNC4wNCAwID
YuNzItMi44NCA2LjcyLTYuODQgMC0uNDYtLjA1LS44MS0uMTBtMS4xNkg3
ek0yMiA2aC0yVjRoLTJ2MmgtMnYyaDJ2MmgyVjhoMiIvPjwvZz48L3N2Zz
4=" ,
    "documentation_url": "https://developers.
google.com/identity/protocols/OpenIDConnect" ,
    "service": "webmaild" ,
    "provider_name": "google"
  } ,
  {
    "documentation_url": "https://developers.
google.com/identity/protocols/OpenIDConnect" ,
    "provider_name": "google" ,
    "service": "whostmgrd" ,
    "icon": "
PHN2ZyB4bWxucz0iaHR0cDovL3d3dy53My5vcmcvMjAwMC9zdmciIHdpZH
RoPSIyMiIgaGVpZ2h0PSIxNCIgdmlld0JveD0iMCAwIDYyIDE0Ij48ZyBm
aWxsPSIjZmZmIiBmaWxsLXJlbGU9ImV2ZW5vZGQiPjxwYXRoIGQ9Ik03ID
Z2Mi40aDMuOTdjLS4xNiAxLjAzLTFEUiAzLjAyLTMuOTcgMy4wMi0yLjM5
IDAtNC4zNC0xLjk4LTQuMzQtNC40MlM0LjYxIDIuNTggNyAyLjU4YzEuMz
YgMCAyLjI3LjU4IDIuNzkgMS4wOGwxLjktMS44MOMxMC40Ny42OSA4Ljg5
IDAgNyAwIDMuMTMgMCAwIDMuMTMgMCA3czMuMTMgNyA3IDdjNC4wNCAwID
YuNzItMi44NCA2LjcyLTYuODQgMC0uNDYtLjA1LS44MS0uMTBtMS4xNkg3
ek0yMiA2aC0yVjRoLTJ2MmgtMnYyaDJ2MmgyVjhoMiIvPjwvZz48L3N2Zz
4=" ,
    "icon_type": "image/svg+xml" ,
    "display_name": "Gooble" ,
    "color": "dd4b39" ,
    "link": "https://hostname.example.com:2087
/openid_connect/google" ,
    "label": "Log in via Google" ,
    "textcolor": "FFFFFF"
  }
]
}
}

```

```

<result>
  <data>
    <configurations>
      <color>dd4b39</color>
      <display_name>gooble</display_name>

```

- [Manage External Authentications](#) — The *Manage External Authentications* interface allows you to manage your server's OpenID Connect-compliant identity providers.
- [WHM API 1 Functions - list_configcluster servers](#) — This function lists the servers in the server's configuration cluster.
- [WHM API 1 Functions - update_configcluster server](#) — This function updates the username or remote access key for a cluster server.
- [WHM API 1 Functions - delete_configcluster server](#) — This function removes a server from a configuration cluster.
- [WHM API 1 Functions - add_configcluster server](#) — This function adds a server to a configuration cluster.

convert_addo_n_fetch_conversion_details
convert_addo_n_fetch_domain_details
convert_addo_n_get_conversion_status
convert_addo_n_initiate_conversion
convert_addo_n_list_addon_domains
convert_addo_n_list_conversions
api_token_create
api_token_list
api_token_revoke
api_token_update
disable_authentication_provider
disable_failing_authentication_providers
enable_authentication_provider
get_available_authentication_providers
get_login_url
get_provider_client_configurations
get_provider_configuration_fields
get_provider_display_configurations
get_users_authn_linked_accounts
link_user_authn_provider
set_provider_client_configurations
set_provider_display_configurations

```
<documentation_url>https://developers.google.com/identity/protocols/OpenIDConnect</documentation_url>

<icon>PHN2ZyB4bWxucz0iaHR0cDovL3d3dy53My5vcmcvMjAwMC9zdmciIHdpZHRoPSIyMiIgaGVpZ2h0PSIxNCIgdmlld0JveD0iMCAwIDIyIDE0Ij48ZyBmaWxsPSIjZmZmIiBmaWxsLXJlbGU9ImV2ZW5vZGQipjxwYXRoIGQ9Ik03IDZ2Mi40aDMuOTdjLS4xNiAxLjAzLzE0LjYxLjU4YzEuMzYgMCAyLjI3LjU4IDIuNzkgMS4wOGwxLjktMS44M0MxMC40Ny42OSAA4Ljg5IDAgNyAwIDMuMTMgMCAwIDMuMTMgMCA3czMuMTMgNyA3IDdjNC4wNCAwIDYuNzItMi44NCA2LjcyLTYuODQgMCA0uNDYtLjAlLS44MS0uMTETMS4xNkg3ek0yMiA2aC0yVjRoLTJ2MmgtMnYyYyDJ2MmgyVjhoMiIvPjwvZz48L3N2Zz4=</icon>

<icon_type>image/svg+xml</icon_type>
<label>Log in via Google</label>
<link>https://hostname.example.com:2083/openid_connect/google</link>
<provider_name>google</provider_name>
<textcolor>FF0000</textcolor>
</configurations>
<configurations>
<color>dd4b39</color>
<display_name>Google</display_name>
<documentation_url>https://developers.google.com/identity/protocols/OpenIDConnect</documentation_url>

<icon>PHN2ZyB4bWxucz0iaHR0cDovL3d3dy53My5vcmcvMjAwMC9zdmciIHdpZHRoPSIyMiIgaGVpZ2h0PSIxNCIgdmlld0JveD0iMCAwIDIyIDE0Ij48ZyBmaWxsPSIjZmZmIiBmaWxsLXJlbGU9ImV2ZW5vZGQipjxwYXRoIGQ9Ik03IDZ2Mi40aDMuOTdjLS4xNiAxLjAzLzE0LjYxLjU4YzEuMzYgMCAyLjI3LjU4IDIuNzkgMS4wOGwxLjktMS44M0MxMC40Ny42OSAA4Ljg5IDAgNyAwIDMuMTMgMCAwIDMuMTMgMCA3czMuMTMgNyA3IDdjNC4wNCAwIDYuNzItMi44NCA2LjcyLTYuODQgMCA0uNDYtLjAlLS44MS0uMTETMS4xNkg3ek0yMiA2aC0yVjRoLTJ2MmgtMnYyYyDJ2MmgyVjhoMiIvPjwvZz48L3N2Zz4=</icon>

<icon_type>image/svg+xml</icon_type>
<label>Log in via Google</label>
<link>https://hostname.example.com:2096/openid_connect/google</link>
<provider_name>google</provider_name>
<textcolor>FFFFFF</textcolor>
</configurations>
<configurations>
<color>dd4b39</color>
<display_name>Google</display_name>
<documentation_url>https://developers.google.com/identity/protocols/OpenIDConnect</documentation_url>

<icon>PHN2ZyB4bWxucz0iaHR0cDovL3d3dy53My5vcmcvMjAwMC9zdmciIHdpZHRoPSIyMiIgaGVpZ2h0PSIxNCIgdmlld0JveD0iMCAwIDIyIDE0Ij48ZyBmaWxsPSIjZmZmIiBmaWxsLXJlbGU9ImV2ZW5vZGQipjxwYXRoIGQ9Ik03IDZ2Mi40aDMuOTdjLS4xNiAxLjAzLzE0LjYxLjU4YzEuMzYgMCAyLjI3LjU4IDIuNzkgMS4wOGwxLjktMS44M0MxMC40Ny42OSAA4Ljg5IDAgNyAwIDMuMTMgMCAwIDMuMTMgMCA3czMuMTMgNyA3IDdjNC4wNCAwIDYuNzItMi44NCA2LjcyLTYuODQgMCA0uNDYtLjAlLS44MS0uMTETMS4xNkg3ek0yMiA2aC0yVjRoLTJ2MmgtMnYyYyDJ2MmgyVjhoMiIvPjwvZz48L3N2Zz4=</icon>

<icon_type>image/svg+xml</icon_type>
<label>Log in via Google</label>
<link>https://hostname.example.com:2087/openid_connect/google</link>
<provider_name>google</provider_name>
<textcolor>FFFFFF</textcolor>
</configurations>
</data>
<metadata>
<command>get_provider_display_configurations</command>
</command>
<reason>OK</reason>
```

twofactorauth
_disable_policy

twofactorauth
_enable_policy

twofactorauth
_generate_tfa_config

twofactorauth
_get_issuer

twofactorauth
_get_user_configs

twofactorauth
_policy_status

twofactorauth
_remove_user_config

twofactorauth
_set_issuer

twofactorauth
_set_tfa_config

unlink_user_authn_provider

validate_login_token

backup_config_get

backup_config_set

backup_date_list

backup_destination_add

backup_destination_delete

backup_destination_get

backup_destination_list

backup_destination_set

backup_destination_validate

backup_get_transport_status

backup_list_transported

backup_set_list

```
<result>1</result>
  <version>1</version>
  </metadata>
</result>
```



Note:

Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

Parameter	Type	Description	Possible values	Example
provider_id	string	Required The identity provider's key.	A valid identity provider's key.	google

Returns

Return	Type	Description	Possible values	Example
configurations	array of hashes	This array of hashes contains information about each service's external authentication display information.	This array of hashes includes the link, label, document_url, icon, provider_name, color, display_name, service, icon_type, and textcolor returns.	
icon_type	string	The icon file's MIME type. The function returns this value in the configurations name hash.	A valid image format's MIME type.	image/svg+xml
label	string	The text label in the button that the cPanel login interface displays. The function returns this value in the configurations name hash.	A valid string.	Log in via Google

<p>backup_set_list_combined</p> <p>backup_skip_users_all</p> <p>backup_skip_users_all_status</p> <p>backup_user_list</p> <p>convert_and_migrate_from_legacy_config</p> <p>get_users_with_backup_metadata</p> <p>list_cparchive_files</p> <p>start_background_pkgacct</p> <p>toggle_user_backup_state</p> <p>participate_in_analytics</p> <p>cpbulk_status</p> <p>create_cpbulk_record</p> <p>delete_cpbulk_record</p> <p>disable_cpbulk</p> <p>enable_cpbulk</p> <p>flush_cpbulk_login_history</p> <p>flush_cpbulk_login_history_for_ips</p> <p>get_countries_with_known_ip_ranges</p> <p>get_cpbulk_brutes</p> <p>get_cpbulk_excessive_brutes</p> <p>get_cpbulk_failed_logins</p> <p>get_cpbulk_user_brutes</p> <p>load_cpbulk_config</p> <p>read_cpbulk_records</p> <p>save_cpbulk_config</p>	<p>icon</p> <p>color</p> <p>provider_name</p> <p>display_name</p> <p>service</p> <p>text_color</p>	<p>string</p> <p>string</p> <p>string</p> <p>string</p> <p>string</p> <p>string</p>	<p>The icon file in the button that the cPanel login interface displays.</p> <p>The function returns this value in the configurations name hash.</p> <p>The background color of the button in the cPanel interface.</p> <p>The function returns this value in the configurations name hash.</p> <p>The name of the identity provider.</p> <p>The function returns this value in the configurations name hash.</p> <p>The display name of the identity provider.</p> <p>The function returns this value in the configurations name hash.</p> <p>The service's name.</p> <p>The function returns this value in the configurations name hash.</p> <p>The color of the text label in the button that the cPanel login interface displays.</p> <p>The function returns this value in the configurations name hash.</p>	<p>A valid Base64-encoded, JPG or PNG-formatted image file.</p> <p>A valid RGB hexadecimal color value.</p> <p>A valid string.</p> <p>A valid string.</p> <p>A valid service name:</p> <ul style="list-style-type: none"> • cpanel • whostmgrd • webmail <p>A valid RGB hexadecimal color value.</p>	<pre>iVBORw0KGgoAAAANSUheUgAAACEAAAhCAYAAABX5MJvAAAAAGRFWHRTb2Z0d2FyZQBBZG9iZSBBZWFnZVJlYWR5ccllPAAAAV1JREFUeNrsVtGNwJAMJegGYIRucBmhtwEjdAMYQjYoG2SEG6HcBGUDugFskHOqglzTlFaN\\/\n/KkqMh2yYvt53S3KygomIzAE+y9P8BDJ9xXpdSDxT9jwX7dxDJSdMvCuV133GF1sBwS508GX7eVgCabGyRkGJF25v0sJHrcyDH7iMhWE19zWSD1\\xs1klJn8J\\n/gZ4WxNdgu8KyidXGIfmJ7L06R8CI5rJnwO+Kv0Wb9Z7x1Zr+wMt8f\\n/ANmyCoCMF3CUMp8rOmHip1AM\\n/8tdbLcJfnL5NigYmIp+ilp5iYRJNkmaJtLIBuJiUZ1S+aDKGDjI8tGk+N\\n/9yuy00DcGIjL8UEmcXKLDelRDQ5tHcuIkSLQE1WYhIRfMRiEmiV1Z7NES5Rh9nIisRGVWGoyyflC5fSkDsTmk1KnVMBForqQw+IVtUCP3KEpdOjffHnRGKcq3LZ3pBgST+BRgANXt+WPKE7tYAAAAASUVORK5CYII=</pre> <p>dd4b39</p> <p>google</p> <p>Google</p> <p>cpanel</p> <p>FF9999</p>
---	--	---	---	---	---

[set_cphulk_config_key](#)
[background_mysql_upgrade_status](#)
[current_mysql_version](#)
[installable_mysql_versions](#)
[latest_available_mysql_version](#)
[list_database_users](#)
[list_databases](#)
[list_mysql_databases_and_users](#)
[remote_mysql_create_profile](#)
[remote_mysql_create_profile_via_ssh](#)
[remote_mysql_delete_profile](#)
[remote_mysql_initiate_profile_activation](#)
[remote_mysql_monitor_profile_activation](#)
[remote_mysql_read_profile](#)
[remote_mysql_read_profiles](#)
[remote_mysql_update_profile](#)
[remote_mysql_validate_profile](#)
[rename_mysql_database](#)
[rename_mysql_user](#)
[rename_postgresql_database](#)
[rename_postgresql_user](#)
[set_local_mysql_root_password](#)

document_ation_url	<i>string</i>	The URL to the identity provider's documentation. The function returns this value in the configuration name hash.	A valid URL.	https://developers.google.com/identity/protocols/OpenIDConnect
link	<i>string</i>	A link to the identity provider's configuration for the system. The function returns this value in the configuration name hash.	A valid URL.	https://hostname.example.com:2083/openid_connect/google

set_mysql_password

set_postgresql_password

start_background_mysql_upgrade

addns

addzonerecord

addzonerecord (Reverse DNS)

create_parser_domain_for_user

dumpzone

editzonerecord

get_nameserver_config

getzonerecord

has_local_authority

killdns

listmxs

listzones

lookupnsip

lookupnsips

removezonerecord

resetzone

resolvedomainname

savemxs

setresolvers

update_nameservers_config

ea4_get_currently_installed_packages

ea4_get_ea_pkgs_state

ea4_list_profiles

ea4_metainfo

ea4_migration

ea4_pre_migrate_check

ea4_recommendations

ea4_save_profile

ea4_tomcat85_add

ea4_tomcat85_list

ea4_tomcat85_remove

cpgreylist_is_server_netblock_trusted

cpgreylist_list_entries_for_common_mail_provider

cpgreylist_load_common_mail_providers_config

cpgreylist_save_common_mail_providers_config

cpgreylist_status

cpgreylist_trusted_entries_for_common_mail_provider

cpgreylist_untrust_entries_for_common_mail_provider

create_cpgreylist_trusted_host

delete_cpgreylist_trusted_host

disable_cpgreylist

enable_cpgreylist

load_cpgreylist_config

read_cpgreylist_deferred_entries

read_cpgreylist_trusted_hosts

save_cpgreylist_config

batch

cpanel

create_integration_group

create_integration_link

get_integration_link_user_config

list_integration_groups

list_integration_links

remove_integration_group

remove_integration_link

update_integration_link_to_ken

addips

delip

get_public_ip

get_shared_ip

ipv6_disable_account

ipv6_enable_account

ipv6_range_add

ipv6_range_delete

ipv6_range_list

ipv6_range_remove

ipv6_range_usage

listips

nat_checkip

nat_set_public_ip

setsiteip

disable_dkim

disable_mail_sni

emailtrack_search

emailtrack_stats

emailtrack_user_stats

enable_dkim

enable_mail_sni

ensure_dkim
_keys_exist

exim_configu
ration_check

expunge_mai
lbox_messag
es

expunge_me
ssages_for_
mailbox_guid

fetch_dkim_p
rivate_keys

fetch_mail_q
ueue

generate_mo
bileconfig

get_mailbox_
status

get_mailbox_
status_list

get_unique_r
ecipient_cou
nt_per_send
er_for_user

get_unique_s
ender_recipie
nt_count_per
_user

get_user_em
ail_forward_d
estination

hold_outgoi
ng_email

install_dkim_
private_keys

install_spf_re
cords

is_sni_suppo
rted

list_pops_for

mail_sni_stat
us

rebuild_mail_
sni_config

release_outg
oing_email

save_spamd_
_config

set_user_em
ail_forward_d
estination

suspend_out
going_email

unsuspend_o
utgoing_email

validate_curr
ent_installed
_exim_config

validate_curr
ent_dkims

validate_curr
ent_ptrs

validate_curr
ent_spfs

validate_exi
m_configurati
on_syntax

disable_mark
et_provider

enable_mark
et_provider

get_adjusted
_market_pro
viders_produ
cts

get_market_
providers_co
mmission_co
nfig

get_market_
providers_list

get_market_
providers_pr
oduct_metad
ata

get_market_
providers_pr
oducts

set_market_p
roduct_attri
bute

set_market_p
rovider_com
mission_id

modsec_add
_rule

modsec_add
_vendor

modsec_ass
emble_config
_text

modsec_batc
h_settings

modsec_che
ck_rule

modsec_clon
e_rule

modsec_depl
oy_all_rule_c
hanges

modsec_depl
oy_rule_chan
ges

modsec_depl
oy_settings_
changes

modsec_disa
ble_rule

modsec_disa
ble_vendor

modsec_disa
ble_vendor_c
onfigs

modsec_disa
ble_vendor_u
pdates

modsec_disc
ard_all_rule_
changes

modsec_disc
ard_rule_cha
nges

modsec_edit
_rule

modsec_ena
ble_vendor

modsec_ena
ble_vendor_c
onfigs

modsec_ena
ble_vendor_u
pdates

modsec_get_
config_text

modsec_get_
configs

modsec_get_
configs_with_
changes_pen
ding

modsec_get_
log

modsec_get_
rules

modsec_get_
settings

modsec_get_
vendors

modsec_is_i
nstalled

modsec_mak
e_config_acti
ve

modsec_mak
e_config_ina
ctive

modsec_prev
iew_vendor

modsec_rem
ove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_undisable_rule

modsec_update_vendor

_getpkgextensionform

add_override_features_for_user

addpkg

addpkgext

changepackage

create_featurelist

delete_featurelist

delpkgext

editpkg

get_available_applications

get_available_featurelists

get_feature_metadata

get_feature_names

get_featurelist_data

get_featurelists

get_users_features_settings

getfeaturelist

getpkginfo

killpkg

listpkgs

manage_features

matchpkgs

read_featurelist

remove_override_features_for_user

update_featurelist

verify_user_has_feature

convert_all_domains_to_fpm

get_fpm_count_and_utilization

is_conversion_in_progress

php_get_default_accounts_to_fpm

php_get_handlers

php_get_impacted_domains

php_get_installed_versions

php_get_old_fpm_flag

php_get_system_default_version

php_get_hosts_by_version

php_get_host_versions

php_ini_get_content

php_ini_get_directives

php_ini_set_content

php_ini_set_directives

php_fpm_config_get

php_fpm_config_set

php_set_default_accounts_to_fpm

php_set_handler

php_set_old_fpm_flag

php_set_session_save_path

php_set_system_default_version

php_set_vhost_versions

acctcounts

get_public_contact

getresellerips

listacts

listresellers

resellerstats

saveacllist

set_public_contact

setacts

setresellerips

setresellerlimits

setresellermainip

setresellernameservers

setresellerpackage_limit

setupreseller

suspendreseller

terminatereseller

unsetupreseller

unsuspendreseller

delete_rpm_version

edit_rpm_version

get_rpm_version_data

install_rpm_plugin

list_rpms

package_manager_fixcache

package_manager_get_build_log

package_ma
nager_get_p
ackage_info

package_ma
nager_is_per
forming_actio
ns

package_ma
nager_list_pa
ckages

package_ma
nager_resolv
e_actions

package_ma
nager_submit
_actions

package_ma
nager_upgra
de

uninstall_rpm
_plugin

delete_hook

edit_hook

list_hooks

reorder_hooks

accessssh

authorizessh
key

check_remot
e_ssh_conne
ction

convertopens
shputty

deletesshkey

fetch_securit
y_advice

generatesshk
eypair

importsshkey

listsshkeys

add_configcl
usterserver

configurebac
kgroundproc
esskiller

configureserv
ice

cors_proxy_g
et

create_user_
session

delete_config
clusterserver

enable_monit
or_all_enable
d_services

get_all_conta
ct_importanc
es

get_appconfi
g_application
_list

get_applicati
on_contact_e
vent_importa
nce

get_applicati
on_contact_i
mportance

get_available
_profiles

get_current_
profile

get_passwor
d_strength

get_remote_
access_hash

get_service_
config

get_service_
config_key

get_tcp4_soc
kets

get_tcp6_soc
kets

get_tweakset
ting

get_udp4_so
ckets

get_udp6_so
ckets

get_update_
availability

get_users_lin
ks

getdiskusage

gethostname

is_role_enabl
ed

list_configclu
sterservers

loadavg

nvget

nvset

personalizati
on_get

personalizati
on_set

purchase_a_l
icense

reboot

remove_in_p
rogress_exim
_config_edit

restartservice

restore_conf
g_from_file

restore_conf
g_from_uplo
ad

run_cpkeyclt

send_test_po
sturl

send_test_pu
shbullet_note

servicestatus

set_applicati
on_contact_e
vent_importa
nce

set_applicati
on_contact_i
mportance

set_primary_
servername

set_service_
config_key

set_tweakset
ting

sethostname

setminimump
asswordstren
gths

start_profile_
activation

system_need
s_reboot

systemloada
vg

update_conf
gclusterserver

update_conta
ct_email

verify_aim_a
ccess

verify_icq_ac
cess

verify_oscar_
access

verify_posturl
_access

verify_pushbullet_access

delete_ssl_vhost

disable_auto
ssl

fetch_service
_ssl_components

fetch_ssl_certificates_for_fqdns

fetch_ssl_vhosts

fetch_vhost_ssl_components

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl_check_schedule

get_autossl_log

get_autossl_logs_catalog

get_autossl_metadata

get_autossl_pending_queue

get_autossl_pending_queue_for_domain

get_autossl_pending_queue_for_user

get_autossl_problems_for_domain

get_autossl_problems_for_user

get_autossl_providers

get_best_ssl_domain_for_service

install_service_ssl_certificate

installssl

listcrts
rebuildinstall
edssldb
rebuilduserss
ldb
reset_autossl
_provider
reset_service
_ssl_certificate
set_autossl_
metadata
set_autossl_
metadata_key
set_autossl_
provider
start_autossl
_check_for_a
ll_users
start_autossl
_check_for_o
ne_user
generate_cp
anel_plugin
list_styles
load_style
remove_logo
remove_style
save_style
set_default
ticket_create
_stub_ticket
ticket_get_su
pport_agree
ment
ticket_get_su
pport_info
ticket_grant
ticket_list
ticket_remov
e_closed
ticket_revoke
ticket_ssh_te
st
ticket_ssh_te
st_start
ticket_update
_service_agr
eement_appr
oval
ticket_validat
e_oauth2_co
de

ticket_whiteli
st_check

ticket_whiteli
st_setup

ticket_whiteli
st_unsetup

abort_transfe
r_session

analyze_tran
sfer_session
_remote

available_tra
nsfer_modules

create_remot
e_root_transf
er_session

create_remot
e_user_trans
fer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transfe
r_session_log

get_transfer_
session_state

pause_transf
er_session

remote_basic
_credential_c
heck

retrieve_tran
sfer_session
_remote_ana
lysis

start_transfer
_session

transfer_mod
ule_schema

validate_syst
em_user

accept_eula

get_available
_tiers

get_current_l
ts_expiration
_status

get_lts_wexpi
re

getlongterms
upport

installed_ver
sions

set_cpanel_u
pdates

set_tier

update_upda
teconf

version