

Advanced Apache Configuration - The paths.conf File

Overview

To improve future compatibility within the cPanel & WHM codebase, we eliminated the use of hardcoded paths to refer to Apache files and directories.



Warning:

We **strongly** recommend that you do **not** change Apache configuration file locations. EasyApache 4 controls the `/etc/cpanel/ea4/paths.conf` file with the `ea-apache24-config-runtime` package, and you can **only** change these values if you create a custom webstack.

Default file paths

EasyApache 4 configures the following file paths by default:

Alias	File Path
<i>dir_domlogs</i>	<code>/etc/apache2/logs/domlogs</code>
<i>bin_httpd</i>	<code>/usr/sbin/httpd</code>
<i>bin_apachectl</i>	<code>/usr/sbin/apachectl</code>
<i>bin_suexec</i>	<code>/usr/sbin/suexec</code>
<i>dir_docroot</i>	<code>/var/www/html</code>
<i>file_conf_php_conf</i>	<code>/etc/apache2/conf.d/php.conf</code>
<i>dir_modules</i>	<code>/etc/apache2/modules</code>
<i>dir_conf_userdata</i>	<code>/etc/apache2/conf.d/userdata</code>
<i>file_conf</i>	<code>/etc/apache2/conf/httpd.conf</code>
<i>dir_base</i>	<code>/etc/apache2</code>
<i>dir_conf</i>	<code>/etc/apache2/conf.d</code>
<i>file_access_log</i>	<code>/etc/apache2/logs/access_log</code>
<i>file_error_log</i>	<code>/etc/apache2/logs/error_log</code>
<i>dir_conf_includes</i>	<code>/etc/apache2/conf.d/includes</code>
<i>dir_run</i>	<ul style="list-style-type: none">CentOS 6: <code>/var/run/apache2</code>CentOS 7: <code>/run/apache2</code>
<i>file_conf_mime_types</i>	<code>/etc/mime.type</code>
<i>dir_logs</i>	<code>/etc/apache2/logs</code>
<i>file_conf_srm_conf</i>	<code>/etc/apache2/conf.d/srm.conf</code>

For more information about EasyApache 4 and Apache, read our [Apache](#) documentation.

Additional documentation

- [EasyApache 4 Home](#)
- [Apache](#)
- [EasyApache 4 File System Layout](#)
- [Advanced Apache Configuration](#)

- [Apache Module: Brotli](#)