

WHM API 1 Functions - saveacllist

Guide to WHM API 1

[Return Data](#)

[Filter Output](#)

[Sort Output](#)

[Paginate Output](#)

[Output Columns](#)

[Call cPanel API 2 and UAPI](#)

Description

This function creates or modifies an [Access Control List \(ACL\)](#).



Warning:

We **strongly** recommend that WHM users create and edit ACLs and ACL privileges through WHM's *Edit Reseller Nameservers and Privileges* interface (*WHM >> Home >> Resellers >> Edit Reseller Nameservers and Privileges*).

[restore_modules_summary](#)

[restore_queue_activate](#)

[restore_queue_add_task](#)

[restore_queue_clear_all_completed_tasks](#)

[restore_queue_clear_all_failed_tasks](#)

[restore_queue_clear_all_pending_tasks](#)

[restore_queue_clear_all_tasks](#)

[restore_queue_clear_completed_task](#)

[restore_queue_clear_pending_task](#)

[restore_queue_is_active](#)

[restore_queue_list_active](#)

[restore_queue_list_completed](#)

[restore_queue_list_pending](#)

[restore_queue_state](#)

[restoreaccount](#)

[verify_new_username_for_restore](#)

[accountsummary](#)

Function information

API Version:
[WHM API 1](#)
Available in:
WHM 11+
Methods:
GET, POST
Required Parameters:
acllist
Return Format:
JSON, XML



Important:

cPanel & WHM version 66 **deprecated** XML output.

About WHM API 1

WHM API 1 performs functions and accesses data in WHM.



Notes:

[applist](#)
[createacct](#)
[domainuserdata](#)
[editquota](#)
[forcepasswordchange](#)
[get_current_users_count](#)
[get_disk_usage](#)
[get_domain_info](#)
[getdomainowner](#)
[get_maximum_users](#)
[getminimumpasswordstrengths](#)
[has_digest_auth](#)
[has_mycnf_for_cpuser](#)
[limitbw](#)
[list_users](#)
[listaccts](#)
[listlockedaccounts](#)
[listsuspended](#)
[modifyacct](#)
[myprivs](#)
[passwd](#)
[quota_enabled](#)
[removeacct](#)
[set_digest_auth](#)
[showbw](#)
[suspendacct](#)
[unsuspendacct](#)
[untrack_acct_id](#)
[verify_new_username](#)
[convert_addon_fetch_conversion_details](#)

Examples

```
https://hostname.example.com:2087/cpsess#####/json-api/saveacllist?api.version=1&acllist=my_acl_list&acl-all=1
```

```
https://hostname.example.com:2087/cpsess#####/xml-api/saveacllist?api.version=1&acllist=my_acl_list&acl-all=1
```

```
whmapil saveacllist acllist=my_acl_list acl-all=1
```

Notes:

- Unless otherwise noted, you **must** [URI-encode](#) values.
- For more information and additional output options, read our [Guide to WHM API 1](#) documentation or run the `whmapil --help` command.
- If you run CloudLinux™, you **must** use the full path of the `whmapil` command:

```
/usr/local/cpanel/bin/whmapil
```

```
{
  "metadata": {
    "version": 1,
    "reason": "ACL List my_acl_list saved.",
    "result": 1,
    "command": "saveacllist"
  }
}
```

```
<result>
  <metadata>
    <version>1</version>
    <reason>ACL List my_acl_list saved.</reason>
    <result>1</result>
    <command>saveacllist</command>
  </metadata>
</result>
```

Note:

Use WHM's *API Shell* interface (*WHM >> Home >> Development >> API Shell*) to directly test WHM API calls.

Parameters

• Some functions and parameters may require that you authenticate as the root user.

[convert_addon_fetch_domain_details](#)

[convert_addon_get_conversion_status](#)

[convert_addon_initiate_conversion](#)

[convert_addon_list_addon_domains](#)

[convert_addon_list_conversions](#)

[api_token_create](#)

[api_token_list](#)

[api_token_revoke](#)

[api_token_update](#)

[disable_authentication_provider](#)

[disable_failing_authentication_providers](#)

[enable_authentication_provider](#)

[get_available_authentication_providers](#)

[get_login_url](#)

[get_provider_client_configurations](#)

[get_provider_configuration_fields](#)

[get_provider_display_configurations](#)

[get_users_authn_linked_accounts](#)

[link_user_authn_provider](#)

[set_provider_client_configurations](#)

[set_provider_display_configurations](#)

[twofactorauth_disable_policy](#)

| Parameter | Type | Description | Possible values | Example |
|---------------------------|----------------|---|--|-------------|
| acllist | <i>string</i> | Required The ACL to assign to the reseller. <div style="border: 1px solid #ffc107; padding: 5px; margin-top: 10px;">Note: To modify an existing ACL, set this value to that ACL's name.</div> | A valid ACL name. | my_acl_list |
| acl-edit-pkg | <i>Boolean</i> | Whether to allow the reseller to edit hosting plans (packages). This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-add-pkg | <i>Boolean</i> | Whether to allow the reseller to add and remove hosting plans (packages). This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-list-pkgs | <i>Boolean</i> | Whether to allow the reseller to view existing hosting plans (packages). This parameter defaults to 0. <div style="border: 1px solid #ffc107; padding: 5px; margin-top: 10px;">Note: We added this parameter in cPanel & WHM version 68.</div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-mailcheck | <i>Boolean</i> | Whether to allow the reseller to troubleshoot mail delivery. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-generate-email-config | <i>Boolean</i> | Whether to allow the reseller to generate a mobile configuration profile for an email account. This parameter defaults to 0. <div style="border: 1px solid #ffc107; padding: 5px; margin-top: 10px;">Note: We added this parameter in cPanel & WHM version 68.</div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-show-bandwidth | <i>Boolean</i> | Whether to allow the reseller to view account bandwidth usage. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-list-accts | <i>Boolean</i> | Whether to allow the reseller to view the list of accounts. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |

• You must use the appropriate WHM ports (2086 or 2087) to call WHM API functions.

Find a function

Related functions

[twofactorauth_enable_policy](#)

[twofactorauth_generate_tfa_config](#)

[twofactorauth_get_issuer](#)

[twofactorauth_get_user_configs](#)

[twofactorauth_policy_status](#)

[twofactorauth_remove_user_config](#)

[twofactorauth_set_issuer](#)

[twofactorauth_set_tfa_config](#)

[unlink_user_auth_provider](#)

[validate_login_token](#)

[backup_config_get](#)

[backup_config_set](#)

[backup_date_list](#)

[backup_destination_add](#)

[backup_destination_delete](#)

[backup_destination_get](#)

[backup_destination_list](#)

[backup_destination_set](#)

[backup_destination_validate](#)

[backup_get_transport_status](#)

[backup_list_transported](#)

[backup_set_list](#)

[backup_set_list_combined](#)

[backup_skip_users_all](#)

| | | | | | |
|---|-------------------------------|----------------|---|--|---|
| twofactorauth_enable_policy | <code>acl-acct-summary</code> | <i>Boolean</i> | Whether to allow the reseller to view an account summary. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px; background-color: #fff9c4;">Note: We added this parameter in cPanel & WHM version 68.</div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| twofactorauth_generate_tfa_config | <code>acl-clustering</code> | <i>Boolean</i> | Whether to allow the reseller to use DNS clusters. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| twofactorauth_get_issuer | <code>acl-news</code> | <i>Boolean</i> | Whether to allow the reseller to modify the server's news. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| twofactorauth_get_user_configs | <code>acl-thirdparty</code> | <i>Boolean</i> | Whether to allow the reseller to manage third-party services. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| twofactorauth_policy_status | <code>acl-kill-dns</code> | <i>Boolean</i> | Whether to allow the reseller to remove DNS zones. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| twofactorauth_remove_user_config | <code>acl-cpanel-api</code> | <i>Boolean</i> | Whether to allow the reseller to execute cPanel API 1 , cPanel API 2 and UAPI functions via WHM. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px; background-color: #fff9c4;">Note: We added this parameter in cPanel & WHM version 68.</div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| twofactorauth_set_issuer | <code>acl-edit-dns</code> | <i>Boolean</i> | Whether to allow the reseller to edit DNS zones. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| twofactorauth_set_tfa_config | <code>acl-park-dns</code> | <i>Boolean</i> | Whether to allow the reseller to park DNS zones. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| unlink_user_auth_provider | <code>acl-create-dns</code> | <i>Boolean</i> | Whether to allow the reseller to add DNS zones. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |

- [WHM API 1 Functions - acctcounts](#) — This function lists a reseller's total accounts, suspended accounts, and account creation limit.
- [WHM API 1 Functions - getresellerips](#) — This function lists a reseller's available IP addresses.
- [WHM API 1 Functions - listresellers](#) — This function lists the reseller accounts on the server.
- [WHM API 1 Functions - setresellerips](#) — This function adds IP addresses to a reseller's account.
- [WHM API 0 Functions - setresellermainip](#) — This function assigns a main IP address to a reseller's account.

backup_skip_users_all_status

backup_user_list

convert_and_migrate_from_legacy_config

get_users_with_backup_metadata

list_cparchive_files

start_background_pkgacct

toggle_user_backup_state

participate_in_analytics

cphulk_status

create_cphulk_record

delete_cphulk_record

disable_cphulk

enable_cphulk

flush_cphulk_login_history

flush_cphulk_login_history_for_ips

get_countries_with_known_ip_ranges

get_cphulk_brules

get_cphulk_excessive_brutes

get_cphulk_failed_logins

get_cphulk_server_brutes

load_cphulk_config

read_cphulk_records

save_cphulk_config

set_cphulk_config_key

background_mysql_upgrade_status

| | | | | |
|------------------------|---------|---|--|---|
| acl-manage-api-tokens | Boolean | Whether to allow the reseller to manage API tokens. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">Notes:<ul style="list-style-type: none">This privilege allows an API token user to bypass any restrictions that you set on the API token. For more information, read our Manage API Tokens documentation.We added this parameter in cPanel & WHM version 68.</div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-manage-oidc | Boolean | Whether to allow the reseller to manage external authentication for their accounts. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">Note:<p>We added this parameter in cPanel & WHM version 68.</p></div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-manage-dns-records | Boolean | Whether to allow the reseller to manage DNS records. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">Note:<p>We added this parameter in cPanel & WHM version 68.</p></div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-manage-styles | Boolean | Whether to allow the reseller to manage their server's cPanel styles. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">Note:<p>We added this parameter in cPanel & WHM version 68.</p></div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-nameserver-config | Boolean | Whether to allow the reseller to manage nameservers. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">Note:<p>We added this parameter in cPanel & WHM version 68.</p></div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-ssl | Boolean | Whether to allow the reseller to perform SSL site management. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |

current_mysql_version

installable_mysql_versions

latest_available_mysql_version

list_database_users

list_databases

list_mysql_databases_and_users

remote_mysql_create_profile

remote_mysql_create_profile_via_ssh

remote_mysql_delete_profile

remote_mysql_initiate_profile_activation

remote_mysql_monitor_profile_activation

remote_mysql_read_profile

remote_mysql_read_profiles

remote_mysql_update_profile

remote_mysql_validate_profile

rename_mysql_database

rename_mysql_user






rename_postgresql_database

rename_postgresql_user





set_local_mysql_root_password

set_mysql_password

set_postgresql_password

| | | | | |
|-------------------------|----------------|--|---|---|
| acl-ssl-info | <i>Boolean</i> | <p>Whether to allow the reseller to view their server's SSL information.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">  Note: We added this parameter in cPanel & WHM version 68. </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-mysql-info | <i>Boolean</i> | <p>Whether to allow the reseller to retrieve MySQL® database and user data.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">  Note: We added this parameter in cPanel & WHM version 68. </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-create-acct | <i>Boolean</i> | <p>Whether to allow the reseller to create accounts.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-suspend-acct | <i>Boolean</i> | <p>Whether to allow the reseller to suspend or unsuspend accounts.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-basic-system-info | <i>Boolean</i> | <p>Whether to allow the reseller to retrieve basic system information.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">  Note: We added this parameter in cPanel & WHM version 68. </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-basic-whm-functions | <i>Boolean</i> | <p>Whether to allow the reseller to access basic cPanel & WHM options.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">  Note: We added this parameter in cPanel & WHM version 68. </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-res-cart | <i>Boolean</i> | <p>Whether to allow the reseller to reset the Interchange shopping cart.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;">  Important: <ul style="list-style-type: none"> • We removed this return in cPanel & WHM version 11.46. • Do not use this privilege in cPanel & WHM version 11.38 or later. </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |

start_background_mysql_upgrade
 adddns
 addzonerecord
 addzonerecord (Reverse DNS)
 create_parser_domain_for_user
 dumpzone
 editzonerecord
 get_nameserver_config
 getzonerecord
 has_local_authority
 killdns
 listmxs
 listzones
 lookupnsip
 lookupnsips
 removezonerecord
 resetzone
 resolvedomainname
 savemxs
 setresolvers
 update_nameservers_config
 ea4_get_currently_installed_packages
 ea4_get_ea_packages_state
 ea4_list_profiles
 ea4_metainfo
 ea4_migration
 ea4_pre_migration_check
 ea4_recommendations
 ea4_save_profile
 ea4_tomcat85_add

| | | | | |
|------------------------|----------------|---|---|---|
| acl-passwd | <i>Boolean</i> | <p>Whether to allow the reseller to change passwords.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <p> Note:</p> <p>This privilege allows an API token user to change account passwords and log in with a new password. For more information, read our Manage API Tokens documentation.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-ssl-buy | <i>Boolean</i> | <p>Whether to allow the reseller to purchase SSL certificates.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-cpanel-integration | <i>Boolean</i> | <p>Whether to allow the reseller to manage how their server and its services connect to other servers and services.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <p> Note:</p> <p>We added this parameter in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-frontpage | <i>Boolean</i> | <p>Whether to allow the reseller to manage Microsoft® FrontPage® Extensions.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <p> Notes:</p> <ul style="list-style-type: none"> • We removed this parameter in cPanel & WHM version 68. • cPanel & WHM will ignore all Microsoft® FrontPage settings and parameters if either of the following statements are true: <ul style="list-style-type: none"> • Your server runs cPanel & WHM version 11.44 and FrontPage extensions are not installed on your server. • Your server runs cPanel & WHM version 11.46 or later. </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| acl-cors-proxy-get | <i>Boolean</i> | <p>Whether to allow the reseller to perform Cross-Origin Resource Sharing (CORS) HTTP requests.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <p> Note:</p> <p>We added this parameter in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |

ea4_tomcat8
5_list

ea4_tomcat8
5_rem

cpgreylist_is_
server_netblo
ck_trusted

cpgreylist_list
_entries_for_
common_mai
l_provider

cpgreylist_lo
ad_common_
mail_provid
er_s_config

cpgreylist_sa
ve_common_
mail_provid
er_s_config

cpgreylist_st
atus

cpgreylist_tru
st_entries_for
_common_m
ail_provider

cpgreylist_un
trust_entries_
for_common_
mail_provid
er

create_cpgre
ylist_trusted_
host

delete_cpgre
ylist_trusted_
host

disable_cpgr
eylist

enable_cpgr
eylist

load_cpgreyli
st_config

read_cpgreyli
st_deferred_
entries

read_cpgreyli
st_trusted_ho
st




save_cpgreyli
st_config

batch


cpanel

create_integr
ation_group

create_integr
ation_link

| | | | | |
|-------------------------|---------|--|--|---|
| acl-upgrade-account | Boolean | Whether to allow the reseller to upgrade or downgrade accounts. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-ssl-gencrt | Boolean | Whether to allow the reseller to generate SSL certificates. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-create-user-session | Boolean | Whether to allow the reseller to create a temporary user session for a specified service. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px;"><p> Notes:</p><ul style="list-style-type: none">This privilege allows an API token user to bypass any restrictions that you set on the API token. For more information, read our Manage API Tokens documentation.We added this parameter in cPanel & WHM version 68.</div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-edit-mx | Boolean | Whether to allow the reseller to edit MX entries. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-digest-auth | Boolean | Whether to allow the reseller to manage Digest Authentication support. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px;"><p> Note:</p><p>We added this parameter in cPanel & WHM version 68.</p></div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-kill-acct | Boolean | Whether to allow the reseller to terminate accounts. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-viewglobalpackages | Boolean | Whether to allow the reseller to use all global packages. For more information, read our reseller packages documentation. This parameter defaults to 0. | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |
| acl-allow-shell | Boolean | Whether to allow the reseller to create accounts with shell access. This parameter defaults to 0. <div style="border: 1px solid #ccc; padding: 5px;"><p> Note:</p><p>We added this parameter in cPanel & WHM version 68.</p></div> | <ul style="list-style-type: none">1 — Allow.0 — Do not allow. | 1 |

[get_integration_link_user_config](#)
[list_integration_groups](#)
[list_integration_links](#)
[remove_integration_group](#)
[remove_integration_link](#)
[update_integration_link_to_ken](#)
[addips](#)
[delip](#)
[get_public_ip](#)
[get_shared_ip](#)
[ipv6_disable_account](#)
[ipv6_enable_account](#)
[ipv6_range_add](#)
[ipv6_range_edit](#)
[ipv6_range_list](#)
[ipv6_range_remove](#)
[ipv6_range_usage](#)
[listips](#)
[nat_checkip](#)
[nat_set_public_ip](#)
[setsiteip](#)
[disable_dkim](#)
[disable_mail_sni](#)
[emailtrack_search](#)
[emailtrack_stats](#)
[emailtrack_user_stats](#)
[enable_dkim](#)
[enable_mail_sni](#)
[ensure_dkim_keys_exist](#)

| | | | | |
|-------------------------------|----------------|--|---|---|
| acl-add-pkg-shell | <i>Boolean</i> | <p>Whether to allow the reseller to create packages with shell access.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-allow-addoncreate | <i>Boolean</i> | <p>Whether to allow the reseller to create packages with addon domains.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-disallow-shell | <i>Boolean</i> | <p>Whether to allow the reseller to create accounts that possess shell access.</p> <p>This parameter defaults to 0.</p> <div style="border: 1px solid #ccc; padding: 5px; margin-top: 10px;"> <p> Note: We removed this parameter in cPanel & WHM version 68.</p> </div> | <ul style="list-style-type: none"> 1 — Do not allow. 0 — Allow. | 1 |
| acl-allow-parkedcreate | <i>Boolean</i> | <p>Whether to allow the reseller to create packages with parked domains (aliases).</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-allow-unlimited-disk-pkgs | <i>Boolean</i> | <p>Whether to allow the reseller to create packages with unlimited disk space.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-allow-unlimited-pkgs | <i>Boolean</i> | <p>Whether to allow the reseller to create packages with unlimited features.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-allow-unlimited-bw-pkgs | <i>Boolean</i> | <p>Whether to allow the reseller to create packages with unlimited bandwidth.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-add-pkg-ip | <i>Boolean</i> | <p>Whether to allow the reseller to create packages with a dedicated IP address.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-locale-edit | <i>Boolean</i> | <p>Whether to allow the reseller to create and modify locales on the server.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-resftp | <i>Boolean</i> | <p>Whether to allow the reseller to resync FTP passwords.</p> <p>This parameter defaults to 0.</p> | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |

exim_configuration_check

expunge_mailbox_messages

expunge_messages_for_mailbox_guid

fetch_dkim_private_keys

fetch_mail_queue

generate_mobileconfig

get_mailbox_status

get_mailbox_status_list

get_unique_recipient_count_per_sender_for_user

get_unique_sender_recipient_count_per_user

get_user_email_forward_destination

hold_outgoing_email

install_dkim_private_keys

install_spf_records

is_sni_supported

list_pops_for

mail_sni_status

rebuild_mail_sni_config

release_outgoing_email

save_spamd_config

set_user_email_forward_destination

suspend_outgoing_email



unsuspend_outgoing_email

validate_current_installed_exim_config

| | | | | |
|---------------------|----------------|---|---|---|
| acl-restart | <i>Boolean</i> | Whether to allow the reseller to restart services. This parameter defaults to 0. | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-status | <i>Boolean</i> | Whether to allow the reseller to view the server's status. This parameter defaults to 0. | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-stats | <i>Boolean</i> | Whether to allow the reseller to view server information. This parameter defaults to 0. | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-quota | <i>Boolean</i> | Whether to allow the reseller to modify quotas. This parameter defaults to 0. | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-demo-setup | <i>Boolean</i> | Whether to allow the reseller to enable demo mode for accounts. This parameter defaults to 0. | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-edit-account | <i>Boolean</i> | Whether to allow the reseller to edit accounts. This parameter defaults to 0. | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-limit-bandwidth | <i>Boolean</i> | Whether to allow the reseller to modify bandwidth limits (quotas). This parameter defaults to 0. | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |
| acl-rearrange-accts | <i>Boolean</i> | Whether to allow the reseller to rearrange accounts. This parameter defaults to 0. | <ul style="list-style-type: none"> 1 — Allow. 0 — Do not allow. | 1 |

Warning:
If you do not use resource limits, this privilege allows resellers to circumvent package limits for disk space.

Warning:
If you do not use resource limits, a value of 1 allows resellers to circumvent package limits for disk space.

| | | | | |
|--|---------------------------------|---|---|---|
| validate_current_dkims validate_current_ptrs validate_current_spfs validate_email_configuration_syntax | acl-track-email | <i>Boolean</i> Whether to allow the reseller to view reports about email message delivery attempts from their account. This parameter defaults to 0. <div style="border: 1px solid #ffc107; padding: 5px; margin-top: 10px;">  Note: We added this parameter in cPanel & WHM version 68. </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |
| disable_market_provider enable_market_provider get_adjusted_market_providers_products get_market_providers_commission_config get_market_providers_list get_market_providers_product_metadata get_market_providers_products set_market_provider_attribute set_market_provider_commission_id modsec_add_rule modsec_add_vendor modsec_assemble_config_text modsec_batch_settings modsec_check_rule modsec_clone_rule modsec_deploy_all_rule_changes modsec_deploy_rule_changes modsec_deploy_settings_changes | acl-all | <i>Boolean</i> Whether to grant the reseller all privileges. This parameter defaults to 0. <div style="border: 1px solid #dc3545; padding: 5px; margin-top: 10px;">  Warning: A value of 1 grants <code>root</code>-level privileges to the reseller. </div> | <ul style="list-style-type: none"> • 1 — Allow. • 0 — Do not allow. | 1 |

Returns

This function only returns metadata.

modsec_disable_rule

modsec_disable_vendor

modsec_disable_vendor_configs

modsec_disable_vendor_updates

modsec_discard_all_rule_changes

modsec_discard_rule_changes

modsec_edit_rule

modsec_enable_vendor

modsec_enable_vendor_configs

modsec_enable_vendor_updates

modsec_get_config_text

modsec_get_configs

modsec_get_configs_with_changes_pending

modsec_get_log

modsec_get_rules

modsec_get_settings

modsec_get_vendors

modsec_is_installed

modsec_make_config_active

modsec_make_config_inactive

modsec_preview_vendor

modsec_remove_rule

modsec_remove_setting

modsec_remove_vendor

modsec_report_rule

modsec_set_config_text

modsec_set_setting

modsec_undisable_rule

modsec_update_vendor

_getpkgextensionform

add_override_features_for_user

addpkg

addpkgext

changepackage

create_featurelist

delete_featurelist

delpkgext

editpkg

get_available_applications

get_available_featurelists

get_feature_metadata

get_feature_names

get_featurelist_data

get_featurelists

get_users_features_settings

getfeaturelist

getpkginfo

killpkg

listpkgs

manage_features

matchpkgs

read_featurelist

remove_override_features_for_user

update_feature_relist

verify_user_has_feature

convert_all_domains_to_fpm

get_fpm_count_and_utilization

is_conversion_in_progress

php_get_defaults_to_fpm

php_get_handlers

php_get_affected_domains

php_get_installed_versions

php_get_old_fpm_flag

php_get_system_default_version

php_get_hosts_by_version

php_get_host_versions

php_ini_get_content

php_ini_get_directives

php_ini_set_content

php_ini_set_directives

php_fpm_config_get

php_fpm_config_set

php_set_defaults_to_fpm

php_set_handler

php_set_old_fpm_flag

php_set_session_save_path

php_set_sys
tem_default_v
ersion

php_set_vho
st_versions

acctcounts

get_public_c
ontact

getresellerips

listacfs

listresellers

resellerstats

saveacflist

set_public_c
ontact

setacfs

setresellerips

setresellerlim
its

setresellerma
inip

setresellerna
meservers

setresellerpa
ckagelimit

setupreseller

suspendresel
ler

terminateres
eller

unsetupresell
er

unsuspendre
seller

delete_rpm_v
ersion

edit_rpm_ver
sion

get_rpm_ver
sion_data

install_rpm_p
lugin

list_rpms

package_ma
nager_fixcac
he

package_ma
nager_get_b
uild_log

package_ma
nager_get_p
ackage_info

package_ma
nager_is_per
forming_actio
ns

package_ma
nager_list_pa
ckages

package_ma
nager_resolv
e_actions

package_ma
nager_submit
_actions

package_ma
nager_upgra
de

uninstall_rpm
_plugin

delete_hook

edit_hook

list_hooks

reorder_hooks

accesshash

authorizessh
key

check_remot
e_ssh_conne
ction

convertopens
shtoputty

deletesshkey

fetch_securit
y_advice

generatesshk
eypair

importsshkey

listsshkeys

add_configcl
usterserver

configurebac
kgroundproc
esskiller

configureserv
ice

cors_proxy_g
et

create_user_
session

delete_config
clusterserver

enable_monit
or_all_enable
d_services

get_all_contact_importances

get_application_list

get_application_contact_event_importance

get_application_contact_importance

get_available_profiles

get_current_profile

get_password_strength

get_remote_access_hash

get_service_config

get_service_config_key

get_tcp4_sockets

get_tcp6_sockets

get_tweaksetting

get_udp4_sockets

get_udp6_sockets

get_update_availability

get_users_links

getdiskusage

gethostname

is_role_enabled

list_configclusterservers

loadavg

nvget

nvset

personalization_get

personalization_set

purchase_a_l
icense

reboot

remove_in_p
rogress_exim
_config_edit

restartservice

restore_conf
g_from_file

restore_conf
g_from_uplo
ad

run_cpkeyclt

send_test_po
sturl

send_test_pu
shbullet_note

servicestatus

set_applicati
on_contact_e
vent_importa
nce

set_applicati
on_contact_i
mportance

set_primary_
servername

set_service_
config_key

set_tweakset
ting

sethostname

setminimump
asswordstren
gths

start_profile_
activation

system_need
s_reboot

systemloada
vg

update_conf
gclusterserver

update_conta
ct_email

verify_aim_a
ccess

verify_icq_ac
cess

verify_oscar_
access

verify_posturl
_access

verify_pushb
ullet_access

delete_ssl_v
host

disable_auto
ssl

fetch_service
_ssl_compon
ents

fetch_ssl_cer
tificates_for_f
qdns

fetch_ssl_vh
osts

fetch_vhost_
ssl_compone
nts

fetchcrtinfo

fetchsslinfo

generatessl

get_autossl_
check_sched
ule

get_autossl_
log

get_autossl_
ogs_catalog

get_autossl_
metadata

get_autossl_
pending_que
ue

get_autossl_
pending_que
ue_for_doma
in

get_autossl_
pending_que
ue_for_user

get_autossl_
problems_for
_domain

get_autossl_
problems_for
_user

get_autossl_
providers

get_best_ssl
domain_for_s
ervice

install_servic
e_ssl_certific
ate

installssl

listcrts

rebuildinstall
edssldb

rebuilduserss
ldb

reset_autossl
_provider

reset_service
_ssl_certificate

set_autossl_
metadata

set_autossl_
metadata_key

set_autossl_
provider

start_autossl
_check_for_a
ll_users

start_autossl
_check_for_o
ne_user

generate_cp
anel_plugin

list_styles

load_style

remove_logo

remove_style

save_style

set_default

ticket_create
_stub_ticket

ticket_get_su
pport_agree
ment

ticket_get_su
pport_info

ticket_grant

ticket_list

ticket_remov
e_closed

ticket_revoke

ticket_ssh_te
st

ticket_ssh_te
st_start

ticket_update
_service_agr
eement_appr
oval

ticket_validat
e_oauth2_co
de

ticket_whiteli
st_check

ticket_whiteli
st_setup

ticket_whiteli
st_unsetup

abort_transfe
r_session

analyze_tran
sfer_session
_remote

available_tra
nsfer_modules

create_remot
e_root_transf
er_session

create_remot
e_user_trans
fer_session

delete_accou
nt_archives

enqueue_tra
nsfer_item

fetch_transfe
r_session_log

get_transfer_
session_state

pause_transf
er_session

remote_basic
_credential_c
heck

retrieve_tran
sfer_session
_remote_ana
lysis

start_transfer
_session

transfer_mod
ule_schema

validate_syst
em_user

accept_eula

get_available
_tiers

get_current_l
ts_expiration
_status

get_lts_wexpi
re

getlongterms
upport

installed_ver
sions

set_cpanel_u
pdates

set_tier

update_upda
teconf

version