

How to Prevent cPanel Users from Creating Certain Domains

[Overview](#)

[Add to the list of user-denied domains](#)

[Additional documentation](#)

Overview

cPanel & WHM allows you to deny cPanel users the ability to create certain domains or use certain top-level domains (TLDs). This feature is useful, for example, to deny cPanel users the ability to park a well-known domain (such as `google.com`) on top of a domain.

For more information about the domains that cPanel users can create, read our [Aliases](#) and [Addon Domains](#) documentation.

Add to the list of user-denied domains

To add to the list of domains that cPanel & WHM does not allow users to create, perform the following steps:

1. From the command line, run the following command to view the default list of domains that cPanel & WHM does not allow users to create.

```
cat /usr/local/cpanel/etc/commondomains
```

- If the file contains a large number of entries, run the `grep 'example.com' /usr/local/cpanel/etc/commondomains` command to determine whether the `example.com` domain exists in the list.



Warning:

Do **not** edit this file directly. System updates overwrite any changes to this file. Instead, follow the next step to create a new file.

2. With a text editor, add the domains and TLDs that you do not want to allow users to create to the `/var/cpanel/commondomains` file.
 - Add each domain or TLD on a separate line, and do **not** prepend or append a dot to the domains. For example:

```
a.com  
b.com  
c.com  
.cat  
.ninja
```

- **Only** add domain names and TLDs to this file (for example, `example.com`). When you list a domain name, cPanel & WHM will automatically prevent the creation of subdomains for that domain or domains under a TLD. For example, if you list the `example.com` domain, users also cannot create the `sub.example.com` domain.
3. In the [Domains](#) section of WHM's [Tweak Settings](#) interface (*WHM >> Home >> Server Configuration >> Tweak Settings*), set the *Prevent cPanel users from creating specific domains* setting to *On*.

Additional documentation

- [Service Subdomains Use the cPanel Service SSL](#)
- [How to Prevent cPanel Users from Creating Certain Domains](#)
- [How to Copy Addon Domains to a New Account](#)
- [What is Domain TLS](#)